

Chapter 2

C++

By: AFAK learning platform



C++ Output (Print Text)

- The cout object, together with the << operator, is used to output values and print text.
- Just remember to surround the text with double quotes (""):

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World!";
    return 0;
}
```



C++ Output (Print Text)

- You can add as many cout objects as you want. However, note that it does not insert a new line at the end of the output:

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World!";
    cout << "I am learning C++";
    return 0;
}
```



C++ Print Numbers

- You can also use `cout()` to print numbers.
- However, unlike text, we don't put numbers inside double quotes:

```
#include <iostream>
using namespace std;

int main() {
    cout << 3;
    return 0;
}
```

- You can also perform mathematical calculations:

```
cout << 3 + 3;
```

```
cout << 2 * 5;
```



C++ New Lines

- To insert a new line in your output, you can use the `\n` character:

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World! \n";
    cout << "I am learning C++";
    return 0;
}
```

- You can also use another `<<` operator and place the `\n` character after the text, like this:

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World!" << "\n";
    cout << "I am learning C++";
    return 0;
}
```



C++ New Lines

- Two \n characters after each other will create a blank line:

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World!" << "\n\n";
    cout << "I am learning C++";
    return 0;
}
```

- Another way to insert a new line, is with the **endl** manipulator:

```
#include <iostream>
using namespace std;

int main() {
    cout << "Hello World!" << endl;
    cout << "I am learning C++";
    return 0;
}
```



C++ New Lines

Both **\n** and **endl** are used to break lines. However, **\n** is most used.

But what is \n exactly?

The newline character (**\n**) is called an escape sequence, and it forces the cursor to change its position to the beginning of the next line on the screen. This results in a new line.

Examples of other valid escape sequences are:

Escape Sequence	Description
\t	Creates a horizontal tab
\\	Inserts a backslash character (\)
\"	Inserts a double quote character



References

- [C++ Output \(Print Text\)](#)

