Status	Finished
Started	Wednesday, 21 October 2026, 8:18 PM
Completed	Wednesday, 21 October 2026, 8:27 PM
Duration	8 mins 23 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums`, return *an integer array* `counts` *where* `counts[i]` *is the number of smaller elements to the right of* `nums[i]`.

Example 1:

```
Input: nums = [5,2,6,1]
Output: [2,1,1,0]
Explanation:
To the right of 5 there are 2 smaller elements (2 and 1).
To the right of 2 there is only 1 smaller element (1).
To the right of 6 there is 1 smaller element (1).
To the right of 1 there is 0 smaller element.
```

Example 2:

```
Input: nums = [-1]
Output: [0]
```

Example 3:

```
Input: nums = [-1,-1]
Output: [0,0]
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^4 <= nums[i] <= 10^4`

For example:

Test	Result
`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`
`print(countSmaller([-1]))`	`[0]`

Answer: (penalty regime: 0 %)

Reset answer

```
def countSmaller(nums):
    offset = 10001
    size = 20002
    tree = [0] * size
    counts = []

    def update(i):
        while i < size:
            tree[i] += 1
            i += i & -i

    def query(i):
        total = 0
        while i > 0:
            total += tree[i]
            i -= i & -i
        return total

    for num in reversed(nums):
        idx = num + offset
        counts.append(query(idx - 1))
        update(idx)

    return counts[::-1]
```

	Test	Expected	Got	
✓	`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`	`[2, 1, 1, 0]`	✓
✓	`print(countSmaller([50,20,60,10]))`	`[2, 1, 1, 0]`	`[2, 1, 1, 0]`	✓
✓	`print(countSmaller([-1]))`	`[0]`	`[0]`	✓
✓	`print(countSmaller([-1, -1]))`	`[0, 0]`	`[0, 0]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Objective:

Develop a Python program to find the k-th maximum value in a given list of integers. The program should handle various edge cases, including lists with duplicate values, empty lists, and invalid values of k. The k-th maximum value refers to the k-th largest distinct element in the list.

Background:

Finding the k-th maximum value in a list is a common problem in computer science, often encountered in fields like data analysis, competitive programming, and software development. This problem requires an understanding of sorting algorithms, data structures, and efficient problem-solving techniques. By solving this problem, one gains insights into how to handle large datasets and optimize performance in practical applications.

Problem Description:

Given a list of integers, the task is to determine the k-th maximum value in the list. The program should meet the following requirements:

1. **Input:**
   - A list of integers, which can contain both positive and negative values.
   - An integer k, representing the position of the maximum value to find.
2. **Output:**
   - The k-th maximum value in the list.
   - If k is greater than the number of distinct elements in the list or if the list is empty, the program should return an appropriate message indicating the error.

Constraints:

- The list may contain duplicate values.
- The value of k should be a positive integer.
- The list may contain up to 10^6 elements, and each element can be as large as 10^9 in magnitude.

Examples:

Consider the following examples for better understanding:

1. **Example 1:**
   - **Input:** list = [3, 1, 5, 4, 2], k = 2
   - **Output:** 4
   - **Explanation:** The distinct elements in the list are [1, 2, 3, 4, 5]. The 2nd maximum value is 4.
2. **Example 2:**
   - **Input:** list = [7, 7, 7, 7, 7], k = 1
   - **Output:** 7
   - **Explanation:** The distinct elements in the list are [7]. The 1st maximum value is 7.
3. **Example 3:**
   - **Input:** list = [2, 1, 2, 1, 2], k = 3
   - **Output:** -1
   - **Explanation:** The distinct elements in the list are [1, 2]. There is no 3rd maximum value.

For example:

Input	Result
5 3 1 5 4 2 2	4

Input	Result
6 7 7 7 7 7 7 1	7
10 2 1 2 1 2 1 2 1 2 1 3	-1

Answer: (penalty regime: 0 %)

```
def kth_maximum(nums, k):
    if not nums:
        return "Error: List is empty"

    if not isinstance(k, int) or isinstance(k, bool) or k <= 0:
        return "Error: Invalid value of k"

    distinct_nums = sorted(set(nums), reverse=True)

    if k > len(distinct_nums):
        return -1

    return distinct_nums[k - 1]


n = int(input())
nums = list(map(int, input().split()))
k = int(input())

print(kth_maximum(nums, k))
```

	Input	Expected	Got	
✓	5 3 1 5 4 2 2	4	4	✓
✓	6 7 7 7 7 7 7 1	7	7	✓
✓	10 2 1 2 1 2 1 2 1 2 1 3	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

```
Array is sorted in 3 swaps.
```

```
First Element: 1
```

```
Last Element: 6
```

Input Format

The first line contains an integer,n , the size of the list a .
The second line contains n, space-separated integers a[i].

Constraints

· 2<=n<=600

· 1<=a[i]<=$2x10^6$.

Output Format

You must print the following three lines of output:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

1 2 3

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0 %)

```
1
2 n = int(input())
3 a = list(map(int, input().split()))
```

```
a = list(map(int, input().split()))

numSwaps = 0

for i in range(n):
    for j in range(n - 1):
        if a[j] > a[j + 1]:
            a[j], a[j + 1] = a[j + 1], a[j]
            numSwaps += 1

print(f"List is sorted in {numSwaps} swaps.")
print(f"First Element: {a[0]}")
print(f"Last Element: {a[-1]}")
```

	Input	Expected	Got	
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	✓
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

Given an array of integers `arr`, replace each element with its rank.

The rank represents how large the element is. The rank has the following rules:

- Rank is an integer starting from 1.
- The larger the element, the larger the rank. If two elements are equal, their rank must be the same.
- Rank should be as small as possible.

Example 1:

```
Input: arr = [40,10,20,30]
Output: [4,1,2,3]
Explanation: 40 is the largest element. 10 is the smallest. 20 is the second smallest. 30 is the third smallest.
```

Example 2:

```
Input: arr = [100,100,100]
Output: [1,1,1]
Explanation: Same elements share the same rank.
```

Example 3:

```
Input: arr = [37,12,28,9,100,56,80,5,12]
Output: [5,3,4,2,8,6,7,1,3]
```

Constraints:

- `0 <= arr.length <= 10^5`
- `-10^9 <= arr[i] <= 10^9`

For example:

Test	Result
`print(arrayRankTransform([40,10,20,30]))`	`[4, 1, 2, 3]`

Answer: (penalty regime: 0 %)

Reset answer

```
def arrayRankTransform(arr):
    rank = {}
    for i, num in enumerate(sorted(set(arr)), 1):
        rank[num] = i
    return [rank[num] for num in arr]
```

	Test	Expected	Got	
✓	`print(arrayRankTransform([40,10,20,30]))`	`[4, 1, 2, 3]`	`[4, 1, 2, 3]`	✓
✓	`print(arrayRankTransform([100,100,100]))`	`[1, 1, 1]`	`[1, 1, 1]`	✓
✓	`print(arrayRankTransform([37,12,28,9,100,56,80,5,12]))`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted list.

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))

for i in range(n):
    for j in range(n - i - 1):
        if arr[j] > arr[j + 1]:
            arr[j], arr[j + 1] = arr[j + 1], arr[j]

print(*arr)
```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums`, sort the array in **increasing** order based on the frequency of the values. If multiple values have the same frequency, sort them in **decreasing** order.

Print the *sorted array*.

Example 1:

```
Input:
6
1 1 2 2 2 3

Output:
3 1 1 2 2 2

Explanation: '3' has a frequency of 1, '1' has a frequency of 2, and '2' has a frequency of 3.
```

Example 2:

```
Input:
5
2 3 1 3 2
Output:
1 3 3 2 2
Explanation: '2' and '3' both have a frequency of 2, so they are sorted in decreasing order.
```

Example 3:

```
Input:
9
-1 1 -6 4 5 -6 1 4 1
Output:
5 -1 4 4 -6 -6 1 1 1
```

Constraints:

- `1 <= nums.length <= 100`
- `-100 <= nums[i] <= 100`

For example:

Input	Result
6 1 1 2 2 2 3	3 1 1 2 2 2
5 2 3 1 3 2	1 3 3 2 2

Answer: (penalty regime: 0 %)

```
from collections import Counter

n = int(input())
nums = list(map(int, input().split()))

freq = Counter(nums)
nums.sort(key=lambda x: (freq[x], -x))

print(*nums)
```

	Input	Expected	Got	
✓	6 1 1 2 2 2 3	3 1 1 2 2 2	3 1 1 2 2 2	✓
✓	5 2 3 1 3 2	1 3 3 2 2	1 3 3 2 2	✓
✓	9 -1 1 -6 4 5 -6 1 4 1	5 -1 4 4 -6 -6 1 1 1	5 -1 4 4 -6 -6 1 1 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

Answer: (penalty regime: 0 %)

```
from collections import Counter

arr = list(map(int, input().split()))
freq = Counter(arr)

for num in sorted(freq):
    print(num, freq[num])
```

	Input	Expected	Got	
✓	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	✓

	Input	Expected	Got	
✓	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	✓
✓	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

The problem is that we want to reverse a array in O(N) linear time complexity and we want the algorithm to be in-place as well!
For example: input is [1,2,3,4,5] then the output is [5,4,3,2,1]
Input
5
1 2 3 4 5
Output
5 4 3 2 1

For example:

Input	Result
5 1 2 3 4 5	5 4 3 2 1

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))

left = 0
right = n - 1

while left < right:
    arr[left], arr[right] = arr[right], arr[left]
    left += 1
    right -= 1

print(*arr)
```

	Input	Expected	Got	
✓	5 1 2 3 4 5	5 4 3 2 1	5 4 3 2 1	✓
✓	10 0 2 4 6 8 1 3 5 7 9	9 7 5 3 1 8 6 4 2 0	9 7 5 3 1 8 6 4 2 0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums` sorted in **non-decreasing** order, return *an array of **the squares of each number** sorted in non-decreasing order*.

Example 1:

```
Input: nums = [-4,-1,0,3,10]
Output: [0,1,9,16,100]
Explanation: After squaring, the array becomes [16,1,0,9,100].
After sorting, it becomes [0,1,9,16,100].
```

Example 2:

```
Input: nums = [-7,-3,2,3,11]
Output: [4,9,9,49,121]
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 <= nums[i] <= 10^4`
- `nums` is sorted in **non-decreasing** order.

For example:

Test	Result
`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`

Answer: (penalty regime: 0 %)

Reset answer

```
def sortedSquares(nums):
    return sorted(x * x for x in nums)
```

	Test	Expected	Got	
✓	`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`	`[0, 1, 9, 16, 100]`	✓

	Test	Expected	Got	
✓	`print(sortedSquares([-7,-3,2,3,11]))`	`[4, 9, 9, 49, 121]`	`[4, 9, 9, 49, 121]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8

Answer: (penalty regime: 0 %)

```
def merge_sort(arr):
    if len(arr) <= 1:
        return arr

    mid = len(arr) // 2
    left = merge_sort(arr[:mid])
    right = merge_sort(arr[mid:])

    result = []
    i = j = 0

    while i < len(left) and j < len(right):
        if left[i] <= right[j]:
            result.append(left[i])
            i += 1
        else:
            result.append(right[j])
            j += 1

    result.extend(left[i:])
    result.extend(right[j:])

    return result


n = int(input())
arr = list(map(int, input().split()))

print(*merge_sort(arr))
```

	Input	Expected	Got	
✓	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	✓
✓	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 57 70	✓
✓	4 86 43 23 49	23 43 49 86	23 43 49 86	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Status	Finished
Started	Wednesday, 21 October 2026, 8:07 PM
Completed	Wednesday, 21 October 2026, 8:15 PM
Duration	7 mins 54 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Complete

Mark 1.00 out of 1.00

Which sorting algorithm is described as making multiple passes through a list, comparing elements, and swapping adjacent items that are out of order?

- a. Insertion Sort
- b. Bubble Sort
- c. Merge Sort
- d. Quick Sort

The correct answer is: Bubble Sort

Question **2**

Complete

Mark 1.00 out of 1.00

What is Bubble Sort known for?

- a. Sorting data in a non-sequential manner
- b. Bubbling up the largest element to its correct position with each pass
- c. Being the most efficient sorting algorithm
- d. Using the divide-and-conquer approach

The correct answer is: Bubbling up the largest element to its correct position with each pass

Question **3**

Complete

Mark 1.00 out of 1.00

What type of problems can sorting help solve efficiently?

- a. All of the above
- b. Searching
- c. Duplicates
- d. Selection

The correct answer is: All of the above

Question **4**

Complete

Mark 1.00 out of 1.00

What is mean by stable sorting algorithm?

- a. A sorting algorithm is stable if it preserves the order of all keys
- b. A sorting algorithm is stable if it preserves the order of non-duplicate keys
- c. A sorting algorithm is stable if it preserves the order of duplicate keys
- d. A sorting algorithm is stable if it doesn't preserver the order of duplicate keys

The correct answer is:
A sorting algorithm is stable if it preserves the order of duplicate keys

Question **5**

Complete

Mark 0.00 out of 1.00

Very slow way of sorting is_____

- a. Quick sort
- b. Insertion sort
- c. Bubble sort
- d. Heap sort

The correct answer is:
Insertion sort

Question **6**

Complete

Mark 1.00 out of 1.00

Which sorting algorithm is known for its simplicity and sequential comparison of elements?

- a. Merge Sort
- b. Quick Sort
- c. Heap Sort
- d. Bubble Sort

The correct answer is: Bubble Sort

Question **7**

Complete

Mark 1.00 out of 1.00

What is the primary benefit of using sorting algorithms in programming?

- a. Makes code execution slower
- b. Provides a basis for other algorithms to work efficiently
- c. Makes data harder to manage
- d. Decreases the efficiency of algorithms

The correct answer is: Provides a basis for other algorithms to work efficiently

Question **8**

Complete

Mark 1.00 out of 1.00

In the context of sorting, what does the divide-and-conquer approach involve?

- a. Dividing the input into parts, solving each part, and combining the solutions
- b. Sorting data sequentially
- c. Rearranging data without sorting
- d. Sorting data in a single pass

The correct answer is: Dividing the input into parts, solving each part, and combining the solutions

Question **9**

Complete

Mark 1.00 out of 1.00

What is sorting in the context of computer science?

- a. Searching for data in a list
- b. Arranging data in a particular format
- c. Deleting data from a list
- d. Inserting data into a list

The correct answer is: Arranging data in a particular format

Question **10**

Complete

Mark 1.00 out of 1.00

Which of the following is a key reason for the importance of sorting algorithms?

- a. Sorting is rarely used in programming
- b. Sorting makes it harder to search for items
- c. Sorting decreases the efficiency of selection operations
- d. Sorting helps in finding duplicates quickly

The correct answer is: Sorting helps in finding duplicates quickly

Question **11**

Complete

Mark 1.00 out of 1.00

Why is sorting important for selection operations?

- a. It makes the data unsorted
- b. It complicates the selection of items
- c. It makes it easier to select items based on their relationship to the rest of the items
- d. It slows down the process

The correct answer is: It makes it easier to select items based on their relationship to the rest of the items

Question **12**

Complete

Mark 1.00 out of 1.00

_____is putting an element in the appropriate place in a sorted list yields a larger sorted order list.

- a. Distribution
- b. Extraction
- c. Selection
- d. Insertion

The correct answer is:
Insertion

Question **13**

Complete

Mark 1.00 out of 1.00

Algorithm design technique used in merge sort algorithm is

- a. Backtracking
- b. Divide and conquer
- c. Dynamic programming
- d. Greedy method

The correct answer is:
Divide and conquer

Question **14**

Complete

Mark 1.00 out of 1.00

Which of the following best describes the term "sorting" in computer science?

- a. Arranging data in a specific order
- b. Removing duplicates from a list
- c. Finding a specific element in a list
- d. Merging two datasets

The correct answer is: Arranging data in a specific order

Question **15**

Complete

Mark 1.00 out of 1.00

Which algorithm is efficient for analyzing the frequency distribution of items in a list?

- a. Linear Search
- b. Quick Sort
- c. Bubble Sort
- d. Merge Sort

The correct answer is: Merge Sort