Summary in Graph


Exam Summary (GO Classes DA Test Series 2026 | Data Structures and Algorithms | Topic Wise Test 3)

Qs. Attempted:	0 (0 + 0)	Correct Marks:	0 (0 + 0)
Correct Attempts:	0 (0 + 0)	Penalty Marks:	0 (0 + 0)
Incorrect Attempts:	0 (0 + 0)	Resultant Marks:	0 (0 + 0)

Total Questions:	15 (5 + 10)
Total Marks:	25 (5 + 20)
Exam Duration:	45 Minutes
Time Taken:	0 Minutes

Individual Question Statistics

Select Metric: Marks Obtained



* Average Stats based on first-attempt stats of Top 10% (48) out of 476 users

EXAM RESPONSE | EXAM STATS | FEEDBACK

Technical

Q #1 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Data Structures

The following operations are performed on an initially empty queue of ints. What is the contents of the queue afterwards? The queue is displayed with the front to the left.

```
    q.enqueue (1)
    q.enqueue (2)
    i=q.getfront ()
    q.enqueue (3)
5.  q.enqueue (4)
    q.enqueue (5)
    i=q.dequeue ()
    q.enqueue (6)
```

Notes: getfront operates analogously to the stack method "top()".

enqueue and dequeue operate as one would expect standard queue operations with those names.


A. 1 2 3 4 5 6
B. 6 5 4 3 1
C. 2 3 4 5 6
D. 1 2 3 4 6

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 03sec | Discuss

Q #2 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Data Structures

A *double* stack is a variation of a stack that allows access to the top and to the bottom of the stack. A double stack ADT provides operations **pushTop**(T x) that adds x to the top of the stack, **pushBottom**(T x) that adds x to the bottom of the stack, **popTop()** that removes the element at the top of the stack, and **popBottom()** that removes the element at the bottom of the stack.

Consider a double-stack ds implemented using an array as shown in the following figure.



When **pushTop**(T x) (**popTop** ()) is executed the value of **top** is increased (decreased); similarly when **pushBottom**(T x) (**popBottom** ( )) is executed the value of **bottom** is decreased (increased). Consider the following code fragment.

```
    for i in range(3):
            ds.pushTop(ds.popBottom());
    for i in range(2):
            x= ds. popTop();
5.  ds.pushBottom(x)
```

After this code fragment is executed on the double stack **ds** represented by the above figure which are the final values for top and **bottom**?

A. top $= 8$, bottom $= 4$
B. top $= 9$, bottom $= 5$
C. top $= 7$, bottom $= 3$
D. top $= 10$, bottom $= 3$

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #3 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Data Structures

Consider the following pseudocode:

```
    Declare a stack of characters
    while ( there are more characters in the word to read )
    {
        read a character
 5.     push the character on the stack
    }
    while ( the stack is not empty )
    {
        pop a character off the stack
10.     write the character to the screen
    }
```

What is written to the screen for the input "carpets"?

A. serc
B. carpets
C. steprac
D. ccaarrppeettss

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #4 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Data Structures

Suppose we have a queue $= [3, 14, 1, 20]$ (here 3 is on the front) and an empty stack. We are allowed to make only two actions:

1. Action "x": Dequeue an element from the queue and push it to the stack.
2. Action "o": Pop an element from the stack and enqueue it in the queue.

Which of the following sequences sort the queue in ascending order:

A. $xxoxooxoxo$
B. $xxoxoxooxo$
C. $xoxxooxoxo$
D. $xxoxooxxoo$

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #5 | Multiple Choice Type | Award: 1 | Penalty: 0.33 | Data Structures

Let s be a sorted array of n integers. Let $t(n)$ denote the time taken for the most efficient algorithm to determine if there are two elements with sum less than 1000 in s.

Which of the following statements is true?

A. $t(n)$ is $O(1)$

B. $n < t(n) < n \log_2 n$

C. $n \log_2 n < t(n) < {}^{n}\mathrm{C}_2$

D. $t(n) = {}^{n}\mathrm{C}_2$

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #6 | Numerical Type | Award: 2 | Penalty: 0 | Data Structures

Consider the following pseudo-code that uses a stack. What will be the output of $n = 50$.

```
    while n > 0:
        stack.push (n % 2)
        n //= 2 # Integer division

5.
    while stack:
        print(stack.pop(), end='')
```

Your Answer: | Correct Answer: 110010 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #7 | Multiple Select Type | Award: 2 | Penalty: 0 | Data Structures

Suppose we want to implement a stack data structure using just one queue. push() and pop() are two functions on stack that may use enqueue() and dequeue() functions of queue Q.

Which of the following pair(s) of implementations for push() and pop() work?

A.
```
    def push(x, Q):
            Q.enqueue(x)


5.  def pop(Q):
            for k in range(1, len(Q)):
                    Q.enqueue(Q.dequeue())
                    return Q.dequeue()
```

B.
```
    def push(x, Q):
            Q.enqueue(x)
            for k in range(1, len(Q)):
                    Q.enqueue(Q.dequeue())
5.

    def pop(Q):
            return Q.dequeue()
```

C.
```
    def push(x, Q):
            Q.enqueue(x)
            for k in range(1, len(Q)):
                    Q.enqueue(Q.dequeue())
5.

    def pop(Q):
            for k in range(1, len(Q)):
                    Q.enqueue(Q.dequeue())
10.                 return Q.dequeue()
```

D.
```
    def push(x, Q):
            Q.enqueue(x)


5. def pop(Q):
            return Q.dequeue()
```

Your Answer: | Correct Answer: A;B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #8 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Data Structures

Consider the following pseudocode of function mystery() which takes one stack orig_stack as input and modify its content using another stack calles helper_stack

```
    def mystery(orig_stack):
          helper_stack = Stack()
          while orig_stack: # not empty
                element = orig_stack.pop()
 5.             while helper_stack and helper_stack.top() < element:
                            orig_stack.push(helper_stack.pop())
                helper_stack.push(element)

          while helper_stack:
10.             orig_stack.push(helper_stack.pop())
```

Suppose the content of orig_stack initially is $-1, 7, 0, 3, -2$, where -1 is on the top.

What will be the content of orig_stack() after the function call mystery()?

A. $7, 3, 0, -1, -2$ where 7 is on the top.
B. $7, -1, 0, 3, -2$, where 7 is on the top.
C. $7, -1, 0, -2, 3$, where 7 is on the top.
D. $-2, -1, 0, 3, 7$, where -2 is on the top.

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #9 | Multiple Select Type | Award: 2 | Penalty: 0 | Data Structures

A queue of int is implemented using a circular array as the following class:
Fill up the missing codes in the IsEmpty and IsFull operations of the Queue. q->front and q->rear both have been initialized to -1.

```
    class Queue:
          def __init__(self):
                self.SIZE = 20
                self.data = [None] * self.SIZE
 5.             self.front = -1
                self.rear = -1


          def is_empty(self):
10.                # Line X


          def is_full(self):
                    # Line Y return
```

A.
```
    Line X is return self.front == self.rear
```

B.
```
    Line X is return self.front == -1
```

C.
```
    Line X is return self.rear == -1
```

D.
```
    Line Y is return (self.rear + 1) % self.SIZE == self.front
```

Your Answer: | Correct Answer: B;C;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #10 | Multiple Select Type | Award: 2 | Penalty: 0 | Data Structures

Consider an array A storing $m > 1$ different integer values sorted in increasing order. At least one value in A is negative and at least one of them is positive. We want to change the positions of the positive values stored in A so the positive values appear in decreasing order. So, for example, if the array A is as in the figure on the left, the modified array is as in the figure on the right.



If we use stack or queue but not both to accomplish this task. Which of the following is/are true?
Let n be the number of positive values.

A. For a queue, we need a minimum of n enqueues and n dequeues operations.
B. For a stack, we need a minimum of n push and n pop operations.
C. For a queue, we need a minimum of $n + 1$ enqueues and $n + 1$ dequeues operations.
D. For a stack, we need a minimum of $n + 1$ push and $n + 1$ pop operations.

Your Answer: | Correct Answer: A;B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #11 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Data Structures

Consider a data structure StackWithMax that supports all operations of a stack, and in addition supports getMax.

- getMax() is a function that returns the maximum without deleting it.
- StackWithMax is implemented using a singly linked list, and each node of the linked list has 3 fields to store.

Two fields are the usual element and next pointer, one extra field is there to facilitate getMax operation in efficient time.
We can efficiently implement getMax of such data structure in -

A. $\theta(1)$ time
B. $\theta(n)$ time
C. $\theta(n \log n)$ time
D. $\theta(\log n)$ time

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss



Q #12 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Data Structures

The queue is implemented using two stacks, denoted by incoming and outgoing. The implementation rules are fixed as follows.

Enqueue(Q, x) :
  Push x into incoming

Dequeue(Q) :
  if outgoing $\neq \varnothing$ **then**
    Pop and return the top element from outgoing
  else
    Do Something (Which is not given to you)
    Return the required element
  end if

Let n enqueue operations and exactly 1 dequeue operation are performed in some sequence.
Using the above implementation, determine the minimum and maximum number of pop operations possible.
(Maximum pop means there exists a sequence of enqueue and dequeue operations for which the number of pop operations cannot be less than the stated maximum.)

A. Minimum pop $= 1$, Maximum pop $= n$
B. Minimum pop $= 1$, Maximum pop $= n + 1$
C. Minimum pop $= n$, Maximum pop $= 2n$
D. Minimum pop $= n$, Maximum pop $= 2n - 1$

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #13 | Multiple Select Type | Award: 2 | Penalty: 0 | Data Structures

Consider a problem: Given an array of elements, replace every element with the nearest greater element on the right of that element. You have to solve this problem with the use of stack.
Which of the following is/are correct ?

A. Minimum number of extra stack(s) is 1
B. Time Complexity is $O(n)$
C. Space Complexity is $O(1)$
D. Space Complexity is $O(n)$

Your Answer: | Correct Answer: A;B;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #14 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Data Structures

Consider a stack *S* that stores integers.

The operation `push(S, i)` returns a new stack obtained by inserting integer i on top of *S*.

For example:

- If *S* is empty, then after *S* = `push(S, 2)`, the $\mathrm{push}(\mathrm{S}, 2)$ operation returns the new stack [2], so *S* becomes [2].
- After one more push: *S* = `push(S, 3)` the $\mathrm{push}(\mathrm{S}, 3)$ operation returns the new stack [2,3], so *S* becomes [2, 3].

A function $f : \mathrm{Stack} \to \mathrm{Integer}$ is defined as:

$$f(\varphi) = 0$$

$$f(\mathrm{push}(S, i)) = \begin{cases} 2^{\max(f(S),0)} + i, & \text{if } i \text{ is even} \\ 2^{\max(f(S),0)} - i, & \text{if } i \text{ is odd} \end{cases}$$

where φ denotes the empty stack.

The stack *S* contains (from **bottom to top**): $[\,2,\ 1,\ 2\,]$

What is the value of $f(S)$?

A. 7

B. 9

C. 128

D. 130

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #15 | Numerical Type | Award: 2 | Penalty: 0 | Data Structures

Consider a queue which supports print() function in addition to enqueue() and dequeue(). print() is a function that prints an element of the head of the queue without removing the element. Suppose the initial content of the queue is $1, 2, 3, 4, 5$ where 1 is on the head. How Many number of calls to enqueue(), dequeue() or print() is required to print queue content in reverse order (output should be printed as $5, 4, 3, 2, 1$) such that the final content of the queue should be the same as the initial content. We are not allowed to use anything else other than enqueue(), dequeue() or print() function calls.

Your Answer: | Correct Answer: 45 | Not Attempted | Time taken: 00min 00sec | Discuss

Copyright & Stuff