Summary in Graph

Exam Summary (GO Classes Test Series 2026 | Database Management and Warehousing | Subject Wise Test 2)


Qs. Attempted:	0 (0 + 0)	Correct Marks:	0 (0 + 0)
Correct Attempts:	0 (0 + 0)	Penalty Marks:	0 (0 + 0)
Incorrect Attempts:	0 (0 + 0)	Resultant Marks:	0 (0 + 0)

Total Questions:	25 (0 + 25)
Total Marks:	50 (0 + 50)
Exam Duration:	75 Minutes
Time Taken:	0 Minutes

Q12). Link
Type: Multiple Choice
Topic: goclasses,databases
Marks Obtained: 0
Time Taken: 00min 00sec
Avg. Time Taken: 01min 11sec
Avg. Accuracy: 100 %
Avg. Skipped: 0 %

Individual Question Statis

Select Metric: Marks Obtained



* Average Stats based on first-attempt stats of Top 10% (5) out of 50 users

EXAM RESPONSE | EXAM STATS | FEEDBACK

Technical

Q #1 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

A data warehouse is modeled with a Star Schema having 4 dimensions: D_1, D_2, D_3, and D_4. The concept hierarchies are defined as follows:

- D_1: City $\rightarrow$ State $\rightarrow$ Country

- D_2: Day $\rightarrow$ Month $\rightarrow$ Year
- D_3: Brand $\rightarrow$ Category
- D_4: Has no concept hierarchy defined (Flat dimension).

If the "Base Cuboid" contains the most detailed data, and the "Apex Cuboid" contains the total aggregation (ALL), what is the total number of cuboids in the full data cube lattice?

A. 48

B. 72

C. 96

D. 120

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #2 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

You are designing a stream-processing data warehouse that must compute the Variance of a sensor stream in real-time. The system has strict memory constraints and cannot store the window of raw data. To compute the variance of the next window algebraically without re-scanning data, what is the minimum number of aggregate registers (floating point values) you must maintain in memory?

A. 1

B. 2

C. 3

D. Infinite

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #3 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider a data cube with schema $C(A, B, \text{Measure})$.

- Dimension A has hierarchy: A_1 (Base) $\rightarrow A_2 \rightarrow A_3 \rightarrow \text{ALL}$.
- Dimension B has hierarchy: B_1 (Base) $\rightarrow B_2 \rightarrow \text{ALL}$.

The system is currently displaying a view materialized at the aggregation level (A_2, ALL).

Which of the following sequences of OLAP operations is VALID to reach the view (A_1, B_2)?

A. Drill-down on A, then Drill-down on B.

B. Roll-up on A, then Drill-down on B.

C. Drill-down on A, then Roll-up on B.

D. Operations are not possible; the path requires going through the base cuboid.

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #4 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider a Snowflake Schema where the Product dimension is normalized into three tables:

$$\text{Item}(10^6\text{rows}) \rightarrow \text{Brand}(10^3\text{rows}) \rightarrow \text{Category}(10^2\text{rows}).$$

The Fact table has 10^9 rows.A query requires aggregating Sales by Category. The optimizer chooses to join the tables before aggregating. If we convert this design to a Star Schema (denormalizing Brand and Category into Item), which of the following describes the impact on the query execution plan?

A. Storage size increases, and the number of join operations decreases from 3 to 1.

B. Storage size decreases, and the number of join operations decreases from 3 to 1.

C. Storage size increases, and the number of join operations remains the same because Category is still needed.

D. Storage size increases, and the number of join operations decreases from 2 to 0.

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #5 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Normalization is a foundational process in relational database design, aiming to systematically minimize redundancy and anomalies through decomposition based on dependency preservation and lossless joins.

Among the following statements, identify the INCORRECT one concerning the principles and implications of normalization and normal forms.

A. Every decomposition that achieves Boyce-Codd Normal Form (BCNF) is both lossless and dependency-preserving by definition.

B. A relation in First Normal Form (1 NF) ensures atomicity of attributes but may still exhibit insertion, update, and deletion anomalies due to partial or transitive dependencies.

C. Normalization beyond a certain normal form (such as 4NF or 5NF) can potentially lead to performance degradation, despite achieving higher theoretical soundness in design.

D. The process of normalization can be viewed as systematically minimizing redundancy under the constraints of functional, multivalued, and join dependencies, while balancing the trade-off between dependency preservation and lossless join properties.

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #6 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider the following relational schemas:

- PROJ (PNO, Budget) Primary key: PNO
- EMP (ENO, EName, Position) - Primary key: ENO

- DSG (ENO, PNO, Dur, Resp) - Primary key: {ENO, PNO}
- DSG.PNO is a foreign key referencing PROJ.PNO
- DSG.ENO is a foreign key referencing EMP.ENO

Consider the following SQL query:

```
    SELECT EName
    FROM EMP, PROJ, DSG
    WHERE EMP.ENO = DSG.ENO
        AND PROJ.PNO = DSG.PNO
5.      AND DSG.Dur > 36;
```

A. $\pi_{\text{EName}}\left(\text{PROJ} \bowtie_{\text{PNO}} \left(\text{EMP} \bowtie_{\text{ENO}} \sigma_{\text{Dur}>36}(\text{DSG})\right)\right)$

B. $\pi_{\text{EName}}\left(\text{PROJ} \bowtie_{\text{PNO}} \left(\pi_{\{\text{EName}\}}(\text{EMP}) \bowtie_{\text{ENO}} \sigma_{\text{Dur}>36}(\text{DSG})\right)\right)$

C. $\pi_{\text{EName}}\left(\text{PROJ} \bowtie_{\text{PNO}} \left(\sigma_{\text{Dur}>36}(\text{EMP}) \bowtie_{\text{ENO}} \text{DSG}\right)\right)$

D. $\pi_{\text{EName}}\left(\text{PROJ} \bowtie_{\text{PNO}} \left(\text{EMP} \bowtie_{\text{ENO}} \sigma_{\text{Dur}>36}\left(\pi_{\{\text{Dur}\}}(\text{DSG})\right)\right)\right)$

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #7 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider the following tables in a relational database:

Department(DeptCode, DeptName)

Employee(EmpCode, EmpName, DeptCode)

We want to obtain a table in which each row is the concatenation of a row from the Department table with a row from the Employee table.

If a department has no employees, its row in the result must contain empty (NULL) fields for the employee attributes.
The relational algebra operation that must be applied to combine these two tables is:

A. Division

B. Inner join

C. Outer join

D. Union

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #8 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider the following relations:

Department(DeptCode, DeptName)

Employee(EmployeeID, EmployeeName, DeptCode, Salary)

Examine the SQL query:

```
    SELECT D.DeptCode, D.DeptName, SUM(E.Salary)
    FROM Department D, Employee E
    WHERE D.DeptCode = E.DeptCode
    GROUP BY D.DeptCode, D.DeptName
5. HAVING COUNT(*) > 2 AND AVG(E.Salary) > 40;
```

Which of the following best describes the result of this query?

A. For each employee who works in more than two departments with an average salary greater than 40, the query lists the department details and total salary.

B. For each department having more than two employees and whose average salary exceeds 40, the query lists the department code, department name, and the total of all salaries in that department.

C. For each department, the query lists every employee whose salary exceeds 40 and whose department has more than two employees.

D. The query is invalid because $\mathrm{AVG}($ E.Salary $)$ cannot be used with COUNT(*) in the same HAVING clause.

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #9 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

Consider a relation $\mathrm{R}(\mathrm{A}, \mathrm{B}, \mathrm{C}, \mathrm{D})$ with a set of functional and multivalued dependencies defined on it.
Let 3NF, BCNF, and 4NF denote the Third Normal Form, Boyce-Codd Normal Form, and Fourth Normal Form, respectively.

Which one of the following statements is/are TRUE?

A. Every relation in BCNF is also in 3NF, but the reverse need not hold.

B. If a relation R has only one candidate key, then it is always in BCNF, irrespective of its dependencies.

C. A relation R in 3NF, where all candidate keys are simple (i.e., single-attribute), is not guaranteed to be in BCNF.

D. A multivalued dependency $X \rightarrow\rightarrow Y$ in a relation R is trivial only if either $Y \subseteq X$ or $XY = R$.

Your Answer: | Correct Answer: A;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #10 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

Consider a relation schema $\mathrm{R}(\mathrm{A}, \mathrm{B}, \mathrm{C}, \mathrm{D}, \mathrm{E}, \mathrm{F})$ with the following set of non-trivial functional dependencies:

$$\mathrm{F} = \{\mathrm{E} \rightarrow \mathrm{C}, \mathrm{C} \rightarrow \mathrm{B}, \mathrm{A} \rightarrow \mathrm{D}, \mathrm{CDE} \rightarrow \mathrm{A}\}$$

Three attribute sets are given:

- $S_1 = \{C, D, E\}$
- $S_2 = \{D, E, F\}$
- $S_3 = \{A, E, F\}$

Which of the following statements is/are TRUE regarding candidate keys of R?

A. S_1 and S_2 are candidate keys of R.

B. S_2 and S_3 are candidate keys of R.

C. S_1 is the only candidate key for R.

D. S_3 is the only candidate key for R.

Your Answer: | Correct Answer: B | Not Attempted | Time taken: 00min 00sec | Discuss

Q #11 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Indexes are auxiliary access structures used to speed up record retrieval based on search conditions. Consider the following statements about index structures:

I. A sparse index contains an entry for each search key value in the data file, whereas a dense index contains entries only for some key values.

II. An index file is itself a sequential file, with key-pointer pairs stored as records sorted by the search key.

III. A file can have only one primary index (on the field that defines the physical ordering of records) but may have multiple secondary indexes on non-ordering fields.

IV. Insertion or deletion of records in the data file causes corresponding insertions or deletions in the index file, if the index is dense.

Which of the above statements is/are correct?

A. Only I and II

B. Only II and IV

C. Only III and IV

D. Only II, III, and IV

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 05sec | Discuss

Q #12 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

In an m-order B-tree,

- each internal node (except the root) contains at least m keys (and hence $m + 1$ children) and at most $2m$ keys (and $2m + 1$ children);
- All leaves appear at the same level;

- The root may contain between 1 and $2m$ keys.

Which one of the following statements regarding B-tree insertion behaviour is TRUE?

A. Node partitioning (split) occurs when a record must be inserted into a node that already contains $2m$ keys.

B. Node partitioning occurs when a record must be inserted into a node that contains fewer than $2m$ keys.


C. Node partitioning occurs when the inserted key's value is intermediate between existing keys in the same node.

D. Node partitioning occurs when it is necessary to reduce the height of the B-tree after insertion.

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #13 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Analyse the following Entity-Relationship diagram.



The above ER diagram has two entity sets, EntA and EntB, with the following cardinality:
Each entity of EntA can be related to several entities of EntB, and each entity of EntB is related to exactly one entity of EntA.
Assume all attributes are simple and single-valued.
If this ER diagram is mapped to the relational model such that the resulting schema is in Third Normal Form (3NF), which one of the following sets of relations is most appropriate?

A. EntA(idA, attrib1, attrib2), EntB(idB, attrib3)

B. EntAB(idA, idB, attrib1, attrib2, attrib3)


C. EntA(idA, attrib1, attrib2), EntB(idB, attrib3, idA)

D. EntA(idA, attrib1, attrib2), AB(idA, idB), EntB(idB, attrib3)

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #14 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

Consider the following ER diagram representing doctors (Médico), their specialities, and their various phone numbers.



When converting this ER diagram into the relational model in Third Normal Form (3NF), consider the following statements:

I. The primary key of the Telephone table will consist of (CRM, number).
II. Separate tables will be created for Doctor and Telephone, with a foreign key in Telephone referencing Doctor (CRM).
III. A separate table will be created for Doctor (Médico) and Telephone, without any foreign keys.
IV. A separate table will be created for the speciality attribute, with a foreign key to the Doctor (Médico) table.
V. A separate table will be created for the relationship between Doctor (Médico) and Telephone, containing the respective foreign keys.

Which of the following sequences (True/False) is correct for statements I-V?

A. $\mathrm{T}, \mathrm{T}, \mathrm{F}, \mathrm{T}, \mathrm{F}$

B. $\mathrm{T}, \mathrm{T}, \mathrm{F}, \mathrm{F}, \mathrm{F}$

C. $\mathrm{T}, \mathrm{F}, \mathrm{F}, \mathrm{F}, \mathrm{T}$

D. $\mathrm{F}, \mathrm{T}, \mathrm{F}, \mathrm{F}, \mathrm{T}$

Your Answer: | Correct Answer: A | Not Attempted | Time taken: 00min 00sec | Discuss

Q #15 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

Regarding the basic relational algebra operations, identify the statement that is/are INCORRECT:

A. SELECT (σ) extracts specific tuples from a relation, according to a specified condition.

B. UNION ($\cup$) builds a relation consisting of all tuples that appear in either of two relations that are union-compatible.

C. JOIN ($\bowtie$) constructs a relation from two relations, consisting of all possible pairs of tuples, one from each relation.

D. DIFFERENCE ($-$) constructs a relation from two union-compatible relations, consisting of all tuples that appear in the first but not in the second.

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #16 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A database file contains $1,000,000$ records, each of fixed size.

The file is stored on disk using unclustered indexing on the primary key.

- Each disk block can store 10 records or 100 index entries.
- Each block access (read) takes 10 ms.
- The index is organized as a B^{+}-tree of order 100 (each node can hold up to 100 pointers).
- The root of the B^{+}-tree always resides in main memory.

If a query requests a record by its primary key, estimate the average time (in milliseconds) to retrieve that record from disk.
Assume that every non-root node and the data block must be read from disk, and ignore CPU time.

(Give your answer up to two decimal places.)

Your Answer: | Correct Answer: 30.00 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #17 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

A database file consists of r variable-length records, each having an average size of R bytes.
The disk block size is B bytes, of which K bytes are reserved for the block header (metadata).
Assume spanned organization, i.e., a record may cross block boundaries if it doesn't fit completely in the remaining space of a block.
There is no unused space in any block other than the header area.

Which one of the following gives the minimum number of blocks (n) required to store the entire file?

A. $n = \lfloor \frac{(r \times R)}{B} \rfloor$

B. $n = \lceil \frac{(r \times R)}{B} \rceil$

C. $n = \lceil \frac{(r \times R)}{(B-K)} \rceil$

D. $n = \lceil \frac{(r \times (R+K))}{B} \rceil$

Your Answer: | Correct Answer: C | Not Attempted | Time taken: 00min 00sec | Discuss

Q #18 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A record in a database system consists of the following fields in the given order:

Field	Type	Size (bytes)
Name	Character string	15
Age	Integer	2
DateOfJoining	SQL DATE	10
LoginTime	SQL TIME (no fractional seconds)	8

Assume:

- Fields are stored in the same order as listed.
- Each record begins at a block address that is a multiple of **8** bytes.
- Each field must start at an address that is a multiple of **8** bytes (alignment rule).
- No compression or variable-length storage is used.
- No extra padding is allowed at the end of the record beyond alignment requirements.

Find the total size (in bytes) required to store one record, including any padding required for alignment?

Your Answer: | Correct Answer: 48 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #19 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A student database contains $20,000$ records, each of fixed length.

Each record stores the following fields, in order: Name (30 bytes), SSN (9 bytes), Address (40 bytes), Phone (9 bytes), Birthdate (8 bytes), Gender (1 byte), MajorDeptCode (4 bytes), MinorDeptCode (4 bytes), ClassCode (4 bytes), and DegreeProgram (3 bytes).

- Additionally, each record includes 1 extra byte used as a deletion marker.
- The file is stored on a disk with a block size of 512 bytes.
- There is no header or control information in the blocks.
- The organization is unspanned, meaning no record is allowed to cross block boundaries.

Assume all values are stored as raw bytes (no compression, no alignment padding).
Find the minimum number of blocks required to store the entire file?

Your Answer: | Correct Answer: 5000 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #20 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A university stores $20,000$ student records in a variable-length file on disk. Each record consists of the following fields, in order: Name (30 bytes), SSN (9 bytes), Address (40 bytes), Phone (9 bytes, present in only 80% of the records), Birthdate (8 bytes), Sex (1 byte), MajorDeptCode (4 bytes, present in 85% of the records), MinorDeptCode (4 bytes, present in 15% of the records), ClassCode (4 bytes), and DegreeProgram (3 bytes, present in 90% of the records). Each record also contains 1 byte for a deletion marker, 1 byte for an end-of-record marker, and 1 additional byte per field to store the field-type identifier. The file uses a spanned record organization, meaning a record may span across multiple blocks if it does not completely fit in the remaining space of the current block. Each disk block reserves 5 bytes for a pointer to the next block, which cannot be used for data storage. The block size is 512 bytes, and the file header is negligible. Estimate the total number of blocks required to store all $20,000$ records.

Your Answer: | Correct Answer: 4600 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #21 | Numerical Type | Award: 2 | Penalty: 0 | Databases

Consider a disk with B data blocks, each identified by a unique address requiring D bits. To track free space, the file system uses either:

- A bitmap, which uses 1 bit per block, or
- A free list, which stores the D-bit address of each free block in a linked list.

Assume the following:

- Each disk block is 4 KB in size.
- The disk uses a single free list; only free block addresses are stored.
- There is no compression or extra overhead besides what is described.

Let F blocks be free, and Assume unique address requiring bits $\mathrm{D} = 16$

Find the minimum percentage of disk blocks that must be free so that the bitmap uses less space than the

free list.
(Answer as a percent, rounded to two decimal places.)

Your Answer: | Correct Answer: 6.25 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #22 | Multiple Choice Type | Award: 2 | Penalty: 0.67 | Databases

For a disk with 4 KB blocks and 16-bit addresses, which of the following statements is/are TRUE?

A. A free list uses less space than a bitmap if fewer than 6.25% of blocks are free.

B. A bitmap always uses less space than a free list regardless of free blocks.

C. A bitmap uses less space than a free list only when more than 6.25% of blocks are free.

D. Both (A) and (C) are logically equivalent and true under different interpretations.

Your Answer: | Correct Answer: D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #23 | Multiple Select Type | Award: 2 | Penalty: 0 | Databases

Consider a relation schema $\mathrm{R}(\mathrm{A}, \mathrm{B}, \mathrm{C}, \mathrm{D}, \mathrm{E}, \mathrm{F})$ with the following set of functional dependencies (FDs):

$$\mathrm{F} = \{\mathrm{A} \rightarrow \mathrm{BC}, \mathrm{CD} \rightarrow \mathrm{E}, \mathrm{E} \rightarrow \mathrm{F}, \mathrm{F} \rightarrow \mathrm{D}\}$$

Which of the following sets is/are candidate key(s) for the relation R ?

A. A

B. AC

C. AD

D. AE

Your Answer: | Correct Answer: C;D | Not Attempted | Time taken: 00min 00sec | Discuss

Q #24 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A file containing $300,000$ fixed-length records is stored on disk. The record size is 100 bytes, and the block size is 4096 bytes. The file is organized in order of an ordering key field K, making it an ordered (sequential) file on K . The ordering key field K is 9 bytes long, and each block pointer occupies 6 bytes. The file uses unspanned organization, and the blocks are assumed to be fully packed. To speed up searches on K, a primary index is constructed on the data file. Each index entry consists of a key value and a block pointer to the corresponding data block containing that key as its first record. The index itself is stored in blocks of the same size as the data file (4096 bytes). If the primary index does not fit in a single block, additional index levels are recursively built, each index level being a primary index on the previous level until the topmost index fits in exactly one block. Assume that there are no header blocks and that all index levels are completely filled (no partial blocks or wasted space). Under these conditions, how many blocks in total (across all levels of the index) are required to store the complete multi-level primary index? (Round off your answer to the nearest integer.)

Your Answer: | Correct Answer: 29 | Not Attempted | Time taken: 00min 00sec | Discuss

Q #25 | Numerical Type | Award: 2 | Penalty: 0 | Databases

A database index is implemented using a B+ tree structure, where both the internal nodes and leaf nodes are stored on disk blocks. Each disk block is of size 4096 bytes. Every key value is a 4-byte integer, and every pointer (to a child block or to a record) occupies 8 bytes. There is no header information or other metadata stored in the block. In this B+ tree, each internal node stores a collection of key-pointer pairs in the format:

$$\mathrm{P}_1,\ \mathrm{K}_1, \mathrm{P}_2,\ \mathrm{K}_2, \ldots,\ \mathrm{K}_{n-1}, \mathrm{P}_\mathrm{n}$$

where each K_i is a key and each P_i is a pointer to a child node. The order (m) of the $B+$ tree is defined as the maximum number of pointers that can fit in a single node. Assume that the leaf nodes follow the same structure but also include an extra pointer to the next leaf node for sequential access. Find the order ($\mathbf{m}$) of the B+ tree, i.e., the maximum number of pointers that can fit in one node under these conditions. (Round down to the nearest integer if required.)

Your Answer: | Correct Answer: 341 | Not Attempted | Time taken: 00min 00sec | Discuss

Copyright & Stuff