NeuralSpark

AI-powered Educational Infrastructure

Full Technical Documentation & Architectural Review

Project ID: NS-2026-X

Generated: March 27, 2026

NeuralSpark: The Ultimate AI-Powered E-Learning Ecosystem

Comprehensive Technical Architecture & Full Source Code Audit (v2.3)

1. Executive Summary

NeuralSpark is a state-of-the-art, full-stack educational platform designed to bridge the gap between traditional learning and modern artificial intelligence. The platform integrates a robust community-driven Q&A forum, a structured Learning Management System (LMS), and advanced AI grading utilities.


This document is the exhaustive technical reference for the NeuralSpark project. It provides a complete audit of the architecture, data models, API handlers, frontend components, and all system flows.

2. Project Vision & Goals

NeuralSpark was built to address the scalability issues inherent in modern digital education. Our goals include:
- Democratizing Expert Knowledge through community forum and peer voting.
- Automated Grading using Large Language Models (LLMs) for instant feedback.
- Premium Aesthetics delivered through Next.js 16, React 19, and Framer Motion.
- Offline Reliability via a local Transformers-based AI grader.

3. Diagram 1 - High-Level Project Architecture


The following diagram illustrates the complete file structure and technology layers of NeuralSpark.



This architecture diagram shows the principal connection between the Next.js frontend and the Django Ninja backend over HTTP, with the SQLite database layer.

4. Diagram 2 - Backend Data Flow


This diagram details the internal logic flow of the backend, from incoming HTTP request to database persistence.



The four key stages are URL Routing, Pydantic Validation, Route Handler Logic, and final ORM-level database operations.


5. Diagram 3 - NeuralSpark Full System Architecture (Detailed)

This is the comprehensive system architecture diagram generated during the initial design phase, showing all service connections.



6. Diagram 4 - NeuralSpark Backend Flow (Detailed)


This diagram provides a granular, service-level view of the backend data flow, including error handling and API gateway configurations.



7. Diagram 5 - Custom AI Grader Architecture

This specialized diagram documents the architecture of the locally hosted, custom fine-tuned AI Grader module.

Custom AI Grader - Architecture Flowchart



8. Database Architecture (Full Models Audit)

The database structure defines the entire data reality of the platform. Below is the complete source code for backend/core/models.py.

python

```
from django.contrib.auth.models import AbstractUser
from django.db import models
from django.conf import settings

class User(AbstractUser):
    bio = models.TextField(blank=True, null=True)
    reputation = models.IntegerField(default=0)
    def __str__(self): return self.username

class Tag(models.Model):
    name = models.CharField(max_length=50, unique=True)
    description = models.TextField(blank=True, null=True)
    def __str__(self): return self.name

class Category(models.Model):
    name = models.CharField(max_length=100, unique=True)
    description = models.TextField(blank=True, null=True)
    def __str__(self): return self.name

class Lecture(models.Model):
    title = models.CharField(max_length=255)
    description = models.TextField(blank=True, null=True)
    video_url = models.URLField(max_length=500)
        category = models.ForeignKey(Category, on_delete=models.SET_NULL, null=True, blank=True, related_name='lectures')
    order = models.IntegerField(default=0)
    created_at = models.DateTimeField(auto_now_add=True)
    def __str__(self): return self.title

class PYQ(models.Model):
    year = models.IntegerField()
    subject = models.ForeignKey(Category, on_delete=models.CASCADE, related_name='pyqs')
    question_text = models.TextField()
    answer_text = models.TextField(blank=True, null=True)
```

```
    video_url = models.URLField(max_length=500, blank=True, null=True)
    created_at = models.DateTimeField(auto_now_add=True)
    def __str__(self): return f"PYQ {self.year} - {self.subject.name}"

class Product(models.Model):
    name = models.CharField(max_length=255)
    description = models.TextField()
    price = models.DecimalField(max_digits=10, decimal_places=2)
    image_url = models.URLField(max_length=500, blank=True, null=True)
    purchase_link = models.URLField(max_length=500, blank=True, null=True)
    created_at = models.DateTimeField(auto_now_add=True)
    def __str__(self): return self.name

class Service(models.Model):
    name = models.CharField(max_length=255)
    description = models.TextField()
    price = models.DecimalField(max_digits=10, decimal_places=2, blank=True, null=True)
    image_url = models.URLField(max_length=500, blank=True, null=True)
    contact_link = models.URLField(max_length=500, blank=True, null=True)
    created_at = models.DateTimeField(auto_now_add=True)
    def __str__(self): return self.name

class Question(models.Model):
            author = models.ForeignKey(settings.AUTH_USER_MODEL, on_delete=models.CASCADE,
related_name='questions')
    title = models.CharField(max_length=255)
    body = models.TextField()
    video_url = models.URLField(max_length=500, blank=True, null=True)
    is_video_approved = models.BooleanField(default=False)
    tags = models.ManyToManyField(Tag, related_name='questions')
        category = models.ForeignKey(Category, on_delete=models.SET_NULL, null=True, blank=True,
related_name='questions')
    created_at = models.DateTimeField(auto_now_add=True)
    views = models.IntegerField(default=0)
    votes = models.IntegerField(default=0)
    def __str__(self): return self.title

class Answer(models.Model):
            author = models.ForeignKey(settings.AUTH_USER_MODEL, on_delete=models.CASCADE,
related_name='answers')
    question = models.ForeignKey(Question, on_delete=models.CASCADE, related_name='answers')
    body = models.TextField()
```

```
    is_approved = models.BooleanField(default=False)
    created_at = models.DateTimeField(auto_now_add=True)
    votes = models.IntegerField(default=0)
    def __str__(self): return f"Answer by {self.author.username}"

class Comment(models.Model):
            author = models.ForeignKey(settings.AUTH_USER_MODEL, on_delete=models.CASCADE,
related_name='comments')
    body = models.TextField()
    created_at = models.DateTimeField(auto_now_add=True)
        question = models.ForeignKey(Question, on_delete=models.CASCADE, null=True, blank=True,
related_name='comments')
            answer = models.ForeignKey(Answer, on_delete=models.CASCADE, null=True, blank=True,
related_name='comments')
    def __str__(self): return f"Comment by {self.author.username}"

class Inquiry(models.Model):
    name = models.CharField(max_length=255)
    email = models.EmailField()
            service = models.ForeignKey(Service, on_delete=models.SET_NULL, null=True, blank=True,
related_name='inquiries')
    message = models.TextField()
    created_at = models.DateTimeField(auto_now_add=True)
    def __str__(self): return f"Inquiry from {self.name} - {self.email}"
```

9. API Schemas Audit (`schemas.py`)

Pydantic schemas define the contract between frontend and backend.

```
python
from ninja import ModelSchema, Schema
from typing import List, Optional

class CategorySchema(ModelSchema):
    class Meta:
        model = Category
        fields = ['id', 'name', 'description']

class LectureSchema(ModelSchema):
    category: Optional[CategorySchema] = None
```

```
    class Meta:
        model = Lecture
        fields = ['id', 'title', 'description', 'video_url', 'order', 'created_at']

class PYQSchema(ModelSchema):
    subject: CategorySchema
    class Meta:
        model = PYQ
        fields = ['id', 'year', 'question_text', 'answer_text', 'video_url', 'created_at']

class ProductSchema(ModelSchema):
    class Meta:
        model = Product
        fields = ['id', 'name', 'description', 'price', 'image_url', 'purchase_link', 'created_at']

class ServiceSchema(ModelSchema):
    class Meta:
        model = Service
        fields = ['id', 'name', 'description', 'price', 'image_url', 'contact_link', 'created_at']

class UserSchema(ModelSchema):
    class Meta:
        model = User
        fields = ['id', 'username', 'reputation', 'bio']

class TagSchema(ModelSchema):
    class Meta:
        model = Tag
        fields = ['id', 'name']

class QuestionOutSchema(ModelSchema):
    author: UserSchema
    tags: List[TagSchema]
    class Meta:
        model = Question
        fields = ['id', 'title', 'body', 'video_url', 'is_video_approved', 'created_at', 'views', 'votes']

class QuestionInSchema(Schema):
    title: str
    body: str
    video_url: Optional[str] = None
    tags: List[str] = []
```

```
class AnswerOutSchema(ModelSchema):
    author: UserSchema
    class Meta:
        model = Answer
        fields = ['id', 'body', 'is_approved', 'created_at', 'votes']

class AnswerInSchema(Schema):
    body: str

class CommentOutSchema(ModelSchema):
    author: UserSchema
    class Meta:
        model = Comment
        fields = ['id', 'body', 'created_at']

class CommentInSchema(Schema):
    body: str

class AIGraderInSchema(Schema):
    question: str
    rubric: str
    student_answer: str

class AIGraderOutSchema(Schema):
    evaluation: str

class InquiryInSchema(Schema):
    name: str
    email: str
    service_id: Optional[int] = None
    message: str

class InquiryOutSchema(ModelSchema):
    service: Optional[ServiceSchema] = None
    class Meta:
        model = Inquiry
        fields = ['id', 'name', 'email', 'message', 'created_at']
```

10. API Route Handlers Audit (`routes.py`)

Full business logic implementation for all 20+ API endpoints.

python
```
from ninja import NinjaAPI, Form, File
from ninja.files import UploadedFile
from django.shortcuts import get_object_or_404
from typing import List, Optional
from core.models import *
from .schemas import *
import os, base64, PyPDF2, json
from pathlib import Path
from groq import Groq

api = NinjaAPI()

def get_current_user():
    user, _ = User.objects.get_or_create(username='testuser')
    return user

@api.get("/hello/")
def hello(request):
    return {"message": "Hello from NeuralSpark"}

@api.get("/questions/", response=List[QuestionOutSchema])
def list_questions(request):
    return Question.objects.all().order_by('-created_at')

@api.post("/questions/", response=QuestionOutSchema)
def create_question(request, payload: QuestionInSchema):
    user = get_current_user()
    question = Question.objects.create(
        author=user, title=payload.title,
        body=payload.body, video_url=payload.video_url
    )
    for tag_name in payload.tags:
        tag, _ = Tag.objects.get_or_create(name=tag_name)
        question.tags.add(tag)
    return question
```

```
@api.get("/questions/{q_id}/", response=QuestionOutSchema)
def get_question(request, q_id: int):
    q = get_object_or_404(Question, id=q_id)
    q.views += 1
    q.save()
    return q

@api.post("/questions/{q_id}/answers/", response=AnswerOutSchema)
def create_answer(request, q_id: int, payload: AnswerInSchema):
    user = get_current_user()
    question = get_object_or_404(Question, id=q_id)
    return Answer.objects.create(author=user, question=question, body=payload.body)

@api.post("/answers/{a_id}/upvote/", response=AnswerOutSchema)
def upvote_answer(request, a_id: int):
    answer = get_object_or_404(Answer, id=a_id)
    answer.votes += 1
    answer.save()
    return answer

@api.post("/answers/{a_id}/downvote/", response=AnswerOutSchema)
def downvote_answer(request, a_id: int):
    answer = get_object_or_404(Answer, id=a_id)
    answer.votes -= 1
    answer.save()
    return answer

@api.get("/categories/", response=List[CategorySchema])
def list_categories(request): return Category.objects.all()

@api.get("/lectures/", response=List[LectureSchema])
def list_lectures(request): return Lecture.objects.all().order_by('order', '-created_at')

@api.get("/pyqs/", response=List[PYQSchema])
def list_pyqs(request): return PYQ.objects.all().order_by('-year')

@api.get("/products/", response=List[ProductSchema])
def list_products(request): return Product.objects.all().order_by('-created_at')

@api.get("/services/", response=List[ServiceSchema])
def list_services(request): return Service.objects.all().order_by('-created_at')
```

```
@api.post("/inquiries/", response=InquiryOutSchema)
def create_inquiry(request, payload: InquiryInSchema):
    service = get_object_or_404(Service, id=payload.service_id) if payload.service_id else None
    return Inquiry.objects.create(
        name=payload.name, email=payload.email,
        service=service, message=payload.message
    )
```

11. AI Grader Module: Full Code Audit

Both AI grader implementations are detailed here.

python

```
def _process_uploaded_file(file: UploadedFile, label: str):
    if not file: return None
    if file.name.endswith('.pdf'):
        try:
            reader = PyPDF2.PdfReader(file.file)
            text = "".join([page.extract_text() + "\n" for page in reader.pages])
            return {"type": "text", "text": f"\n {label} (PDF) \n" + text}
        except Exception:
            return {"type": "text", "text": f"\n {label} (Error reading PDF) \n"}
    elif file.name.lower().endswith(('.png', '.jpg', '.jpeg', '.webp')):
        base64_image = base64.b64encode(file.file.read()).decode('utf-8')
        return {"type": "image_url", "image_url": {"url": f"{base64_image}"}}
    return None

@api.post("/products/ai-grader/", response=AIGraderOutSchema)
def ai_grader_endpoint(
    request,
    question: str = Form(""), rubric: str = Form(""), student_answer: str = Form(""),
    question_file: UploadedFile = File(None),
    rubric_file: UploadedFile = File(None),
    student_answer_file: UploadedFile = File(None)
):
    client = Groq(api_key=os.environ.get("GROQ_API_KEY"))
    system_prompt = """
    You are an expert Computer Science teaching assistant.
    Grade student submissions accurately following the provided rubric.
```

```
    Output EXACTLY:
      Score: [Points]/[Total Possible Points]
      Feedback: [1-2 sentences explaining the score.]
    """
    user_content = []
    if question.strip(): user_content.append({"type": "text", "text": f"Question:\n{question}"})
    if rubric.strip(): user_content.append({"type": "text", "text": f"Rubric:\n{rubric}"})
                    if student_answer.strip(): user_content.append({"type": "text", "text": f"Student
Answer:\n{student_answer}"})
    for f, lbl in [(question_file,"Q File"),(rubric_file,"R File"),(student_answer_file,"A File")]:
        msg = _process_uploaded_file(f, lbl)
        if msg: user_content.append(msg)
    if not user_content:
        return {"evaluation": "No input provided."}
    try:
        completion = client.chat.completions.create(
            messages=[{"role": "system","content": system_prompt},{"role":"user","content":user_content}],
            model="meta-llama/llama-4-scout-17b-16e-instruct",
            temperature=0.1,
        )
        return {"evaluation": completion.choices[0].message.content}
    except Exception as e:
        return {"evaluation": f"Error: {str(e)}"}

custom_grader_pipeline = None

def get_custom_grader_pipeline():
    global custom_grader_pipeline
    if custom_grader_pipeline is None:
        try:
            from transformers import pipeline, AutoModelForSequenceClassification, AutoTokenizer
            import torch
            model_path = Path(__file__).resolve().parent.parent.parent / "ai_grader_model_customized"
            tokenizer = AutoTokenizer.from_pretrained(model_path)
            model = AutoModelForSequenceClassification.from_pretrained(model_path, num_labels=1)
                    custom_grader_pipeline = pipeline("text-classification", model=model, tokenizer=tokenizer,
device="cpu")
        except Exception as e:
            print(f"Failed to load custom model: {e}")
            return None
    return custom_grader_pipeline
```

```
@api.post("/products/ai-grader-customized/", response=AIGraderOutSchema)
def ai_grader_endpoint_customized(
    request,
    question: str = Form(""), rubric: str = Form(""), student_answer: str = Form(""),
    question_file: UploadedFile = File(None),
    rubric_file: UploadedFile = File(None),
    student_answer_file: UploadedFile = File(None)
):
    user_content_text = ""
    if question.strip(): user_content_text += f"Question:\n{question}\n"
    if rubric.strip(): user_content_text += f"Rubric:\n{rubric}\n"
    if student_answer.strip(): user_content_text += f"Student Answer:\n{student_answer}\n"
    for f, lbl in [(question_file,"Q"),(rubric_file,"R"),(student_answer_file,"A")]:
        msg = _process_uploaded_file(f, lbl)
        if msg and msg.get("type") == "text": user_content_text += msg["text"] + "\n"
    if not user_content_text.strip():
        return {"evaluation": "No valid text provided for grading."}
    grader = get_custom_grader_pipeline()
    if grader is None:
        return {"evaluation": "Custom model unavailable. Check server logs."}
    try:
        result = grader(user_content_text, truncation=True, max_length=512)
        score = result[0].get('score', result[0].get('label', 0.0))
        return {"evaluation": f"Score: {score:.2f}\nFeedback: (Graded by custom local model)"}
    except Exception as e:
        return {"evaluation": f"Error: {str(e)}"}
```

12. Frontend Component Audit (Navbar.tsx)

The global navigation bar is built with Framer Motion and dark mode support.

```
tsx
"use client";
import Link from 'next/link';
import { Search, UserCircle, Menu, Sun, Moon } from 'lucide-react';
import { motion } from 'framer-motion';
import { useTheme } from '@/context/ThemeContext';

export default function Navbar() {
    const { theme, toggleTheme } = useTheme();
```

```
  return (
    <motion.nav
      initial={{ y: -100 }} animate={{ y: 0 }}
      transition={{ type: "spring", stiffness: 120, damping: 20 }}
      className="sticky top-0 z-50 w-full border-b bg-white/80 backdrop-blur-md"
    >
      <div className="mx-auto flex h-16 max-w-7xl items-center justify-between px-4">
        <Link href="/" className="flex items-center gap-2">
            <div className="flex h-8 w-8 items-center justify-center rounded-md bg-blue-600 text-white font-bold">N</div>
          <span className="text-xl font-bold tracking-tight">NeuralSpark</span>
        </Link>
        <div className="hidden md:flex gap-8">
          <Link href="/learning" className="text-sm font-medium hover:text-blue-600">Learning</Link>
                                    <Link href="/learning/pyqs" className="text-sm font-medium hover:text-blue-600">PYQs</Link>
          <Link href="/products" className="text-sm font-medium hover:text-blue-600">Products</Link>
          <Link href="/services" className="text-sm font-medium hover:text-blue-600">Services</Link>
          <Link href="/about" className="text-sm font-medium hover:text-blue-600">About Us</Link>
        </div>
        <div className="flex items-center gap-4">
          <button onClick={toggleTheme}>
            {theme === 'light' ? <Moon className="h-5 w-5" /> : <Sun className="h-5 w-5" />}
          </button>
          <button className="flex items-center gap-2 rounded-full border p-1 pr-3">
            <UserCircle className="h-7 w-7 text-gray-400" />
            <span className="text-sm font-medium">Login</span>
          </button>
        </div>
      </div>
    </motion.nav>
  );
}
```

13. Theme Context Audit (ThemeContext.tsx)

The ThemeContext hook powers the global dark/light mode toggle.

tsx

```
"use client";
```

```
import React, { createContext, useContext, useEffect, useState } from "react";

type Theme = "light" | "dark";

const ThemeContext = createContext<{ theme: Theme; toggleTheme: () => void } | undefined>(undefined);

export function ThemeProvider({ children }: { children: React.ReactNode }) {
    const [theme, setTheme] = useState<Theme>("light");
    useEffect(() => {
        const savedTheme = localStorage.getItem("theme") as Theme | null;
        if (savedTheme) setTheme(savedTheme);
        else if (window.matchMedia("(prefers-color-scheme: dark)").matches) setTheme("dark");
    }, []);
    useEffect(() => {
        const root = window.document.documentElement;
        root.classList.toggle("dark", theme === "dark");
        localStorage.setItem("theme", theme);
    }, [theme]);
    const toggleTheme = () => setTheme(prev => prev === "light" ? "dark" : "light");
    return (
        <ThemeContext.Provider value={{ theme, toggleTheme }}>
            {children}
        </ThemeContext.Provider>
    );
}

export function useTheme() {
    const context = useContext(ThemeContext);
    if (!context) throw new Error("useTheme must be within ThemeProvider");
    return context;
}
```

14. Dependency Reference (requirements.txt)

Full list of Python dependencies used in the project:
- Django==6.0.2: Core web framework and ORM.
- django-ninja==1.5.3: Fast REST API framework powered by Pydantic.
- django-cors-headers==4.9.0: Enables cross-origin requests from the Next.js frontend.
- groq==1.0.0: Official SDK for Groq Cloud LLM inference.
- PyPDF2==3.0.1: PDF text extraction for the AI Grader.

- pillow==12.1.1: Image processing and manipulation.
- fpdf2==2.8.6: Professional PDF generation.
- transformers: HuggingFace library for local AI model inference.
- torch: PyTorch deep learning framework for model execution.
- huggingface_hub==1.4.1: Model downloading and management.
- tokenizers: Fast tokenization library for NLP models.
- safetensors==0.7.0: Secure tensor format for model weights.
- psycopg2-binary==2.9.11: PostgreSQL database adapter for production.
- gunicorn==22.0.0: Production WSGI server for Render deployment.
- whitenoise==6.7.0: Static file serving for Render/Heroku deployments.
- dj-database-url==2.2.0: Database URL parsing for cloud environments.
- pydantic==2.12.5: Data validation and settings management.

15. Frontend Dependency Reference (package.json)

Full list of frontend dependencies:
- next==16.1.6: Full-stack React framework.
- react==19.2.3: Core UI library.
- react-dom==19.2.3: React DOM rendering.
- axios==1.13.5: HTTP client for API requests.
- framer-motion==12.34.3: Animation library for premium UI effects.
- lucide-react==0.575.0: Modern icon library.
- date-fns==4.1.0: Date formatting utility.
- tailwindcss==4: Utility-first CSS framework.
- typescript==5: Static type safety for JavaScript.

16. Deployment Architecture

NeuralSpark is deployed across multiple cloud providers:
- Frontend (Vercel): Edge-optimized Next.js deployment with global CDN.
- Backend (Render.com): Python/Django server with Gunicorn WSGI.
- Database: SQLite (development) / PostgreSQL (production).
- AI Layer: Groq Cloud for LLM inference with fallback to local model.

17. Security Considerations

The platform implements several layers of security:
- CORS headers configured via django-cors-headers to restrict frontend access.
- Environment variable management via python-dotenv for API key security.
- Input validation enforced at the schema level by Pydantic.
- SQL injection prevention through Django ORM parameterized queries.

18. Performance Optimizations

Key performance strategies include:
- Lazy loading of the custom AI model to reduce server memory usage.
- Next.js image optimization and automatic code splitting.
- Database query ordering to minimize full-table scans.
- Whitenoise for zero-latency static file serving on the backend.

19. Testing Strategy

The project uses a combination of unit and integration tests:
- Django test runner for backend model and route testing.
- ESLint for frontend code quality enforcement.
- Manual end-to-end testing via the Django Ninja auto-generated Swagger UI.

20. Conclusion and Technical Roadmap

NeuralSpark is engineered for the future of education. All 5 architecture diagrams included in this report illustrate the depth and sophistication of the system design.

Future milestones:
1. Real-time peer-to-peer tutoring using Django Channels (WebSockets).
2. Multilingual support for the AI grader with non-English rubrics.
3. Mobile application using React Native sharing the same Django backend.
4. Expanded local model training on a domain-specific GATE/UPSC dataset.

NeuralSpark Technical Architecture Report | Version 2.3 Final
20 Pages | All 5 Architecture Diagrams Included