

Lab 5

Connection values:

Server Type = Database Engine

Server Name = is-swang01.ischool.uw.edu

Authentication = SQL Server Authentication

Login = INF06210

Password = NEUHusky!

```
/*  
    SQL variables start with either @ or @@.  
    @ indicates a local variable, which is in effect in the current  
    scope.  
    @@ indicates a global variable, which is in effect for all  
    scopes of the current connection.  
*/
```

-- A simple example of Stored Procedure

-- Set the database context

USE "The name of a database you have created." ;

--Create a stored procedure with INPUT and OUTPUT parameters

/* A parameter has a data type, such as INT (integer).
If a parameter will return a value, we specify the OUTPUT keyword.
If we have only a single SQL statement after IF and/or ELSE,
we don't have to use BEGIN END, but if we have multiple
statements, we have to put them in the BEGIN END block. */

```
CREATE PROCEDURE MyFirstProcedure
    @InNumber INT,
    @OutNumber INT OUTPUT
AS
BEGIN
    IF @InNumber < 0
        SET @OutNumber = 0;
    ELSE
        BEGIN
            SET @OutNumber=@InNumber + 1;
        END
    PRINT @OutNumber;
END
```

-- The statements highlighted in yellow must be executed together

-- Declare variables

```
DECLARE @MyInput INT;
DECLARE @MyOutput INT;
```

-- Initilize variable

```
SET @MyInput = 3;
```

-- Execute the procedure

```
EXEC MyFirstProcedure @MyInput, @MyOutput OUTPUT;
```

-- See result

```
SELECT @MyOutput;
```

-- Drop the procedure so that you can recreate it

```
DROP PROC MyFirstProcedure;
```

-- Use TRY and CATCH for error handling in a Stored Procedure

/*

TRY contains regular SQL statements we execute to accomplish a task.

CATCH contains SQL statements used to handle the error if an error has Occurred.

*/

USE "The name of a database you have created." ;

GO

-- The statements highlighted in yellow must be executed together

BEGIN TRY

BEGIN TRANSACTION;

DELETE FROM AdventureWorks2008R2.Production.Product
WHERE ProductID = 980;

-- If the delete operation succeeds, commit the transaction.

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

PRINT 'UNABLE TO DELETE PRODUCT!';

-- Roll back any active or uncommittable transactions

IF XACT_STATE() <> 0

BEGIN

ROLLBACK TRANSACTION;

END;

END CATCH;

-- Simple examples of Functions

USE "The name of a database you have created." ;

-- Create a scalar function
-- FUNCTION accepts Argument(s)
-- In this example, @Country is the argument.
-- FUNCTION uses the RETURN statement to return the value

```
CREATE FUNCTION whichContinent
(@Country nvarchar(15))
RETURNS varchar(30)
AS
BEGIN
    DECLARE @ReturnC varchar(30);

    SELECT @ReturnC = CASE @Country
        when 'Argentina' then 'South America'
        when 'Belgium' then 'Europe'
        when 'Brazil' then 'South America'
        when 'Canada' then 'North America'
        when 'Denmark' then 'Europe'
        when 'Finland' then 'Europe'
        when 'France' then 'Europe'
        ELSE 'Unknown'
    END;

    RETURN @returnC;
END

-- Execute the new function

SELECT dbo.whichContinent('Canada');
```

```
USE "The name of a database you have created." ;
```

```
-- Create a table-valued function
```

```
CREATE FUNCTION dbo.GetDateRange
(@StartDate date, @NumberOfDays int)
RETURNS @DateList TABLE (Position int, DateValue date)
AS BEGIN
    DECLARE @Counter int = 0;
    WHILE (@Counter < @NumberOfDays)
    BEGIN
        INSERT INTO @DateList
            VALUES(@Counter + 1,
                DATEADD(day,@Counter,@StartDate));
        SET @Counter += 1;
    END
    RETURN;
END
GO
```

```
-- Execute the new function
```

```
SELECT * FROM dbo.GetDateRange('2009-12-31',14);
```

```
USE "The name of a database you have created." ;
```

```
-- Create a table-valued function
```

```
CREATE FUNCTION GetLastOrdersForCustomer  
(@CustomerID int, @NumberOfOrders int)  
RETURNS TABLE  
AS  
RETURN (SELECT TOP(@NumberOfOrders)  
        SalesOrderID,  
        OrderDate,  
        PurchaseOrderNumber  
        FROM AdventureWorks2008R2.Sales.SalesOrderHeader  
        WHERE CustomerID = @CustomerID  
        ORDER BY OrderDate DESC, SalesOrderID DESC  
        );  
GO
```

```
-- Execute the new function
```

```
SELECT * FROM GetLastOrdersForCustomer(17288,2);
```

-- A simple example of WHILE Statement

```
/*  
    We need to make sure that we have a way to stop the WHILE loop.  
    Otherwise, we'll have an endless WHILE loop which may run forever.  
    We use the variable @counter to determine when to terminate  
    the WHILE loop in this example.  
    We use CAST to convert an integer to character(s) so that we  
    can concatenate the integer with other characters.  
*/
```

```
DECLARE @counter INT;  
SET @counter = 0;  
WHILE @counter <> 5  
BEGIN  
    SET @counter = @counter + 1;  
    PRINT 'The counter : ' + CAST(@counter AS CHAR);  
END;
```


Lab 5 Questions

Note: 3 points for each question.

Lab 5-1

/* Create a function in your own database that takes two parameters:

- 1) A year parameter
- 2) A month parameter

The function then calculates and returns the total sale for the requested year and month. If there was no sale for the requested period, returns 0.

Hints:

- a) Use the TotalDue column of the Sales.SalesOrderHeader table in an AdventureWorks database for calculating the total sale.
- b) The year and month parameters should use the INT data type.
- c) Make sure the function returns 0 if there was no sale in the database for the requested period. */

Lab 5-2

/* With three tables as defined below: */

```
CREATE TABLE Customer
(CustomerID INT PRIMARY KEY,
 CustomerLName VARCHAR(30),
 CustomerFName VARCHAR(30));
```

```
CREATE TABLE SaleOrder
(OrderID INT IDENTITY PRIMARY KEY,
 CustomerID INT REFERENCES Customer(CustomerID),
 OrderDate DATE,
 LastModified datetime);
```

```
CREATE TABLE SaleOrderDetail
(OrderID INT REFERENCES SaleOrder(OrderID),
 ProductID INT,
 Quantity INT,
 UnitPrice INT,
 PRIMARY KEY (OrderID, ProductID));
```

/* Write a trigger to put the change date and time in the LastModified column of the Order table whenever an order item in SaleOrderDetail is changed. */

Useful Links

Create a Stored Procedure

<http://msdn.microsoft.com/en-us/library/ms345415.aspx>

Create a Function

<http://msdn.microsoft.com/en-us/library/ms186755.aspx>

Use TRY and CATCH for Error Handling

<http://msdn.microsoft.com/en-us/library/ms175976.aspx>

XACT_STATE

<http://msdn.microsoft.com/en-us/library/ms189797.aspx>

DATEADD

<http://msdn.microsoft.com/en-us/library/ms186819.aspx>

DATEPART

<https://docs.microsoft.com/en-us/sql/t-sql/functions/datepart-transact-sql>

CROSS APPLY vs INNER JOIN

<https://stackoverflow.com/questions/1139160/when-should-i-use-cross-apply-over-inner-join>