A Radio Relay System for Remote Sensors in the Antarctic

Proposal Seminar

Mark Jessop

March 19, 2010

Supervisor: Dr Chris Coleman   Co-Supervisor: Dr Said Al-Sarawi

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Project Background
Project Aim

Project Background

- ▶ Research team operating ionospheric measurement equipment in Antarctica.
- ▶ Equipment left in the field for many months at a time.
- ▶ Results are obtained only when the equipment is retrieved.
- ▶ Not much can be accomplished while the equipment is in the field.
- ▶ Need some way to gain access to the data!

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Project Background
Project Aim

Project Aim

- Design and build a low power short wave data transmitter that can translate low rate data into a modulated short wave output with sufficient power to transmit the data over several hundred kilometres on an Antarctic communication path.

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Project Background
Project Aim

Block Overview

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Limitations & Challenges

- Low power budget
- Extremely cold temperatures
- Ionospheric absorption loss

Figure: Layers of the Ionosphere

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Power Budget

- ▶ Equipment operates from battery power for many months at a time.
- ▶ Efficiency is extremely important.
- ▶ Components will need to be carefully selected for minimal power consumption.
- ▶ Transmission frequency may need to be lowered to keep within constraints.

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Preliminary Sizing Calculations

If we make a few assumptions, we can use the Friis transmission equation and the Shannon-Hartley Theorem to calculate the theoretical maximum bit rate of a radio link.
Assume:

- 200km Distance between TX and RX (on ground)
- 400km radio path (via near-vertical skywave)
- 5MHz Transmission frequency ($\lambda = 60$m)
- No ionospheric absorption loss (Not Realistic!)
- Dipole antennas one each end ($G_t = G_r = 1.5$)
- 10dB SNR required
- -114dB[2] background noise at 5MHz

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Preliminary Sizing Calculations - SNR

Using 1W transmission power, we can calculate the power at the receiving antenna:

$$P_r = \frac{P_t G_t G_r}{(4\pi R/\lambda)^2}$$

$$= \frac{1 \times 1.5 \times 1.5}{(4\pi \times 400000/60)^2} = 0.3206nW = -94.94dB$$

$$SNR = 114 - 94.94 = 19.06dB = 80.54$$

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Preliminary Sizing Calculations - Capacity

We can use the Shannon-Hartley theorem to calculate the theoretical maximum channel capacity of the link:

$$C = B \log_2(1 + SNR)$$

Where C is the channel capacity (in bits/s) and B is the signal bandwidth. Assuming Binary FSK modulation is used with a 600Hz frequency shift, we calculate the maximum channel capacity as:

$$C = 600 \log_2(1 + 80.54) = 3809.66 \text{ bits/s}$$

To ensure reliability, a much lower bit-rate (~ 600 bits/s) would be used.

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Preliminary Sizing Calculations - Power Usage

To get a rough idea of the power usage, let us assume we are transmitting at 600 bit/s for one hour (263.67 kB of data).
The power usage of some devices that could be used are as follows:

- ► Microcontroller - 75mW in active mode [3]
- ► Signal Generator - 40mW when active [4]
- ► Power Amplifier - 1W (idealised)

So under these ideal conditions, the transmitter will draw 1.115W when transmitting, which is 4014 Joules of energy for one hour of transmission.

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Power Budget
Preliminary Sizing Calculations
Temperature

Temperature

- ▶ Mean annual temperature for Antarctica's interior is -57°C.
- ▶ Standard industry specification is -55°C to $+125^{\circ}$C.
- ▶ Not all devices conform to this spec, and many will be unreliable at these limits!


Figure: Monthly Temperature Statistics for the Amundsen Scott Research Station [1]

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Budget
Timeline
Deliverables
Risks & Dependencies

Budget

Maximum cost = $250

- ▶ Devices for stress testing (i.e. micro-controllers) - $50
- ▶ RF System - $50
- ▶ Control System - $50
- ▶ PCB Construction - $50

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Budget
Timeline
Deliverables
Risks & Dependencies

Timeline

Task	Expected Completion
Background Research	S1 Week 3
Simulation & Component Research	S1 Week 5
High-level design	S1 Week 7
Software Design & Coding	End of S1
Hardware Design	End of S1
Data-Tap	
Controller	
RF System	
Prototype construction	Early S2
Testing & Optimisation	Mid S2

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Budget
Timeline
Deliverables
Risks & Dependencies

Deliverables

- ▶ Proposal Seminar (Now!)
- ▶ Stage 1 Design Document (S1 Week 5)
- ▶ Progress report (S1 Week 11)
- ▶ Interim Performance Report (S1 Week 12)
- ▶ Final Seminar (S2 Mid-semester break)
- ▶ Final Report (S2 Week 11)
- ▶ Final Performance Report (S2 Week 12)
- ▶ Project Exhibition (S2 Week 12)

Introduction
Limitations & Challenges
Project Plan
References
Q & A

Budget
Timeline
Deliverables
Risks & Dependencies

Risks & Dependencies

- ▶ No life-threatening risks involved with this project.
- ▶ Minor risks involving electrical/RF safety.
- ▶ Minor risks involving hardware damage, shipping problems, etc.
- ▶ Medium-level risk involved if project leader becomes ill.

References

[1] G. Marshall. "Monthly mean surface temperature at Amundsen-Scott station"
http://www.nerc-bas.ac.uk/icd/gjma/pole.temps.html Mar. 9, 2010 [Mar. 11, 2010]
[2] S.K. Datta. "Radio Noise Measurement in HF/VHF Band at Antarctica"
http://dspace.ncaor.org:8080/dspace/bitstream/123456789/707/1/115-119.pdf (Google Cache), 1995 [Mar. 15, 2010]
[3] Atmel, "ATMega168PA Electrical Characteristics", ATMega168PA Datasheet, Dec. 2009

[4] Analog Devices, "AD9834 Specifications", AD9834 Datasheet, Feb. 2003

Questions & Answers

Any Questions?