

Modeling in R and Tidying Results

linear models and broom

2022-03-11


 **This is not a course in a
regression**

Modeling in R

```
lm(y ~ x + z, data = df)
```

Modeling in R

```
lm(y ~ x + z, data = df)
```



model
function

Modeling in R

```
lm(y ~ x + z, data = df)
```

variables
in your
data



your
data



Modeling in R

```
lm(y ~ x + z, data = df)
```

outcome

predictors
or
exposure

Modeling in R

lm() = **Linear Regression (OLS)**

Modeling in R

`lm()` = Linear Regression (OLS)

`glm()` = Generalized Linear Model
(default family = Gaussian)

Modeling in R

```
lm(price ~ carat, data = diamonds)
```

Modeling in R

```
lm(price ~ carat, data = diamonds)
```

```
##
```

```
## Call:
```

```
## lm(formula = price ~ carat, data = diamonds)
```

```
##
```

```
## Coefficients:
```

```
## (Intercept)          carat
```

```
##          -2256          7756
```

Modeling in R

```
lm(price ~ carat, data = diamonds) %>%  
summary()
```

Modeling in R

```
##  
## Call:  
## lm(formula = price ~ carat, data = diamonds)  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -18585.3   -804.8    -18.9    537.4   12731.7   
##  
## Coefficients:  
##              Estimate Std. Error t value Pr(>|t|)      
## (Intercept)  -2256.36      13.06  -172.8 <0.00000000000000002 ***  
## carat         7756.43      14.07   551.4 <0.00000000000000002 ***  
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1  
##  
## Residual standard error: 1549 on 53938 degrees of freedom  
## Multiple R-squared:  0.8493,    Adjusted R-squared:  0.8493   
## F-statistic: 3.041e+05 on 1 and 53938 DF,  p-value: < 0.0000000000000000
```

Modeling in R

```
##  
## Call:  
## lm(formula = price ~ carat, data = diamonds)  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -18585.3   -804.8    -18.9    537.4  12731.7   
##  
## Coefficients:  
##              Estimate Std. Error t value      Pr(>|t|)      
## (Intercept)  -2256.36      13.06  -172.8 <0.00000000000000002 ***  
## carat         7756.43      14.07   551.4 <0.00000000000000002 ***  
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1  
##  
## Residual standard error: 1549 on 53938 degrees of freedom  
## Multiple R-squared:  0.8493,    Adjusted R-squared:  0.8493   
## F-statistic: 3.041e+05 on 1 and 53938 DF,  p-value: < 0.0000000000000000
```

broom: tidy models

`tidy()`

`glance()`

`augment()`



broom: tidy models

tidy() = **model coefficients**

glance()

augment()



broom: tidy models

tidy()

glance() = **model fit**

augment()



broom: tidy models

tidy()

glance()

augment() = model predictions



broom: tidy models

tidy()

glance()

augment()

NOT a core member of the tidyverse. Need to load
with library(broom)



Modeling in R

```
library(broom)  
lm(price ~ carat, data = diamonds) %>%  
  tidy()
```

Modeling in R

```
library(broom)
lm(price ~ carat, data = diamonds) %>%
  tidy()
```

```
## # A tibble: 2 × 5
```

	term	estimate	std.error	statistic	p.value
	<chr>	<dbl>	<dbl>	<dbl>	<dbl>
1	(Intercept)	-2256.	13.1	-173.	0
2	carat	7756.	14.1	551.	0

Modeling in R

```
lm(price ~ carat, data = diamonds) %>%  
  glance()
```

Modeling in R

```
lm(price ~ carat, data = diamonds) %>%  
  glance()
```

```
## # A tibble: 1 × 12  
##   r.squared adj.r.squared sigma statistic p.value    df  
##   <dbl>      <dbl> <dbl>      <dbl>    <dbl> <dbl>  
## 1    0.849        0.849 1549.    304051.      0      1  
## # ... with 6 more variables: logLik <dbl>, AIC <dbl>,  
## #   BIC <dbl>, deviance <dbl>, df.residual <int>,  
## #   nobs <int>
```

Modeling in R

```
lm(price ~ carat, data = diamonds) %>%  
  augment()
```

Modeling in R

```
lm(price ~ carat, data = diamonds) %>%  
  augment()
```

```
## # A tibble: 53,940 × 8  
##   price carat .fitted .resid      .hat .sigma      .cooksd  
##   <int> <dbl>   <dbl>   <dbl>   <dbl> <dbl>      <dbl>  
## 1    326  0.23  -472.    798. 0.0000452 1549. 0.00000600  
## 2    326  0.21  -628.    954. 0.0000471 1549. 0.00000892  
## 3    327  0.23  -472.    799. 0.0000452 1549. 0.00000602  
## 4    334  0.29   -7.00   341. 0.0000398 1549. 0.000000966  
## 5    335  0.31   148.    187. 0.0000382 1549. 0.000000278  
## 6    336  0.24  -395.    731. 0.0000442 1549. 0.00000493  
## 7    336  0.24  -395.    731. 0.0000442 1549. 0.00000493  
## 8    337  0.26  -240.    577. 0.0000424 1549. 0.00000294  
## 9    337  0.22  -550.    887. 0.0000461 1549. 0.00000756  
## 10   338  0.23  -472.    810. 0.0000452 1549. 0.00000618  
## # ... with 53,930 more rows, and 1 more variable:  
## #   .std.resid <dbl>
```


Try it yourself

Work your way through the exercises. If anything in particular is giving you trouble, we'll work through it together.

Resources

R for Data Science: A comprehensive but friendly introduction to the tidyverse.
Free online.

UCLA IDRE: Useful resources on modeling in R and other languages