

# Reading and Writing Data

**readr and haven**

2022-03-11

# readr



Function	Reads
<code>read_csv()</code>	Comma separated values
<code>read_csv2()</code>	Semi-colon separate values
<code>read_delim()</code>	General delimited files
<code>read_fwf()</code>	Fixed width files
<code>read_log()</code>	Apache log files
<code>read_table()</code>	Space separated files
<code>read_tsv()</code>	Tab delimited values

# Importing Data


```
dataset <- read_csv("file_name.csv")  
dataset
```

# R functions

```
x <- f(arg = 1)
```

# R functions

`x <- f(arg = 1)`



function  
name

arguments

# R functions



*this saves it in your  
global environment*

**x**

**<-**

f(arg = 1)

assign  
results of  
f() to x

the name of  
your results

# Your Turn 1

**Find diabetes.csv on your computer. Then read it into an object. Then view the results.**

# Your Turn 1

**Find diabetes.csv on your computer. Then read it into an object. Then view the results.**

```
diabetes <- read_csv("diabetes.csv")
```





# new data alert!



## diabetes

	id	chol	stabglu	hdl	ratio	glyhb	location	age	gender	height	weight	frame	bp.
1	1000	203	82	56	3.6	4.31	Buckingham	46	female	62	121	medium	118
2	1001	165	97	24	6.9	4.44	Buckingham	29	female	64	218	large	112
3	1002	228	92	37	6.2	4.64	Buckingham	58	female	61	256	large	190
4	1003	78	93	12	6.5	4.63	Buckingham	67	male	67	119	large	110
5	1005	249	90	28	8.9	7.72	Buckingham	64	male	68	183	medium	138
6	1008	248	94	69	3.6	4.81	Buckingham	34	male	71	190	large	132
7	1011	195	92	41	4.8	4.84	Buckingham	30	male	69	191	medium	161
8	1015	227	75	44	5.2	3.94	Buckingham	37	male	59	170	medium	NA
9	1016	177	87	49	3.6	4.84	Buckingham	45	male	69	166	large	160
10	1022	263	89	40	6.6	5.78	Buckingham	55	female	63	202	small	108
11	1024	242	82	54	4.5	4.77	Louisa	60	female	65	156	medium	130
12	1029	215	128	34	6.3	4.97	Louisa	38	female	58	195	medium	102
13	1030	238	75	36	6.6	4.47	Louisa	27	female	60	170	medium	130
14	1031	183	79	46	4.0	4.59	Louisa	40	female	59	165	medium	NA
15	1035	191	76	30	6.4	4.67	Louisa	36	male	69	183	medium	100
16	1036	213	83	47	4.5	3.41	Louisa	33	female	65	157	medium	130
17	1037	255	78	38	6.7	4.33	Louisa	50	female	65	183	medium	130
18	1041	230	115	64	3.6	4.52	Louisa	30	male	67	150	medium	100

Where does it come from?  
diabetes.csv (etc)  
study: diabetes in  
African Americans

How can I use it?  
`diabetes <-  
readr::read_csv("diabetes.csv")  
View(diabetes)`



*this saves it in your  
global environment*

## diabetes

```
## # A tibble: 403 × 19
##       id chol stab.glu   hdl ratio glyhb location  age
##   <dbl> <dbl>   <dbl> <dbl> <dbl> <dbl> <chr>    <dbl>
## 1  1000   203     82    56  3.60  4.31 Buckingham  46
## 2  1001   165     97    24  6.90  4.44 Buckingham  29
## 3  1002   228     92    37  6.20  4.64 Buckingham  58
## 4  1003    78     93    12  6.5   4.63 Buckingham  67
## 5  1005   249     90    28  8.90  7.72 Buckingham  64
## 6  1008   248     94    69  3.60  4.81 Buckingham  34
## 7  1011   195     92    41  4.80  4.84 Buckingham  30
## 8  1015   227     75    44  5.20  3.94 Buckingham  37
## 9  1016   177     87    49  3.60  4.84 Buckingham  45
## 10 1022   263     89    40  6.60  5.78 Buckingham  55
## # ... with 393 more rows, and 11 more variables:
## #   gender <chr>, height <dbl>, weight <dbl>, frame <chr>,
## #   bp.1s <dbl>, bp.1d <dbl>, ...
```

# Tibbles

**data.frames** are the basic form of rectangular data in R (columns of variables, rows of observations)

# Tibbles

data.frames are the basic form of rectangular data in R (columns of variables, rows of observations"

`read_csv()` reads the data into a **tibble**, a modern version of the data frame.

# Tibbles

data.frames are the basic form of rectangular data in R (columns of variables, rows of observations"

read\_csv() reads the data into a tibble, a modern version of the data frame.

a tibble **is** a data frame

# Missing values

It's common to use codes for **missing values** (-99, 8888)

# Missing values

It's common to use codes for missing values (-99, 8888)

The **na** option can change these values to NA

```
read_csv(  
  "a,b,c,d  
  1,-99,3,4  
  5,6,-99,8",  
  na = "-99"  
)
```

```
## # A tibble: 2 × 4  
##       a      b      c      d  
##   <dbl> <dbl> <dbl> <dbl>  
## 1     1    NA     3     4  
## 2     5     6    NA     8
```



# Parsing data types

The read functions in readr try to **guess** each data type, but sometimes it's **wrong**

# Parsing data types

The read functions in readr try to guess each data type, but sometimes it's wrong

To tell readr how to parse the columns, add the argument **col\_types** to `read_csv()`

# Parsing data types

The read functions in readr try to guess each data type, but sometimes it's wrong

To tell readr how to parse the columns, add the argument **col\_types** to `read_csv()`

```
diabetes <- read_csv(  
  "diabetes.csv",  
  col_types = list(id = col_character())  
)
```

# Parsing data types

Or use a string for  
each variable type:

```
col_type = "cci"
```

# Parsing data types

Or use a string for  
each variable type:  
`col_type = "cci"`

letter	type
c	character
i	integer
n	number
d	double
l	logical
D	date
T	date time
t	time
?	guess the type
_ or -	skip the column

## Your Turn 2

**Set the 4 column types to be: integer, double, character, and unknown (guess)**

```
read_csv(  
  "a,b,c,d"  
  1,2,3,4  
  5,6,7,8",  
  col_types = ""  
)
```

# Your Turn 2

Set the 4 column types to be: integer, double, character, and unknown (guess)

```
read_csv(  
  "a,b,c,d  
  1,2,3,4  
  5,6,7,8",  
  col_types = "idc?"  
)
```

```
## # A tibble: 2 × 4  
##       a      b c      d  
##   <int> <dbl> <chr> <dbl>  
## 1     1     2 3      4  
## 2     5     6 7      8
```

# haven

Function	Software
<code>read_sas()</code>	SAS
<code>read_xpt()</code>	SAS
<code>read_spss()</code>	SPSS
<code>read_sav()</code>	SPSS
<code>read_por()</code>	SPSS
<code>read_stata()</code>	Stata
<code>read_dta()</code>	Stata





# haven



Function	Software
read_sas()	SAS
read_xpt()	SAS
read_spss()	SPSS
read_sav()	SPSS
read_por()	SPSS
read_stata()	Stata
read_dta()	Stata

**haven is not a core member of the tidyverse. That means you need to load it with `library(haven)`.**

## Your Turn 3

**There are several versions of the diabetes file besides CSV. Pick a file format you or your colleagues use and import them using the corresponding function from haven.**

# Your Turn 3

```
library(haven)  
diabetes <- read_sas("diabetes.sas7bdat")
```

# Your Turn 3

```
diabetes
```

```
## # A tibble: 403 × 19
##       id   chol stab_glu   hdl ratio glyhb location   age
##   <dbl> <dbl>   <dbl> <dbl> <dbl> <dbl> <chr>   <dbl>
## 1  1000    203     82    56  3.60  4.31 Buckingham  46
## 2  1001    165     97    24  6.90  4.44 Buckingham  29
## 3  1002    228     92    37  6.20  4.64 Buckingham  58
## 4  1003     78     93    12  6.5   4.63 Buckingham  67
## 5  1005    249     90    28  8.90  7.72 Buckingham  64
## 6  1008    248     94    69  3.60  4.81 Buckingham  34
## 7  1011    195     92    41  4.80  4.84 Buckingham  30
## 8  1015    227     75    44  5.20  3.94 Buckingham  37
## 9  1016    177     87    49  3.60  4.84 Buckingham  45
## 10 1022    263     89    40  6.60  5.78 Buckingham  55
## # ... with 393 more rows, and 11 more variables:
## #   gender <chr>, height <dbl>, weight <dbl>, frame <chr>,
## #   bp_1s <dbl>, bp_1d <dbl>, ...
```

# Writing data

Function	Writes
<code>write_csv()</code>	Comma separated values
<code>write_excel_csv()</code>	CSV that you plan to open in Excel
<code>write_delim()</code>	General delimited files
<code>write_file()</code>	A single string, written as is
<code>write_lines()</code>	A vector of strings, one string per line
<code>write_tsv()</code>	Tab delimited values
<code>write_rds()</code>	A data type used by R to save objects
<code>write_sas()</code>	SAS .sas7bdat files
<code>write_xpt()</code>	SAS transport format, .xpt
<code>write_sav()</code>	SPSS .sav files
<code>write_stata()</code>	Stata .dta files

# Writing data

Function	Writes
<code>write_csv()</code>	Comma separated values
<code>write_excel_csv()</code>	CSV that you plan to open in Excel
<code>write_delim()</code>	General delimited files
<code>write_file()</code>	A single string, written as is
<code>write_lines()</code>	A vector of strings, one string per line
<code>write_tsv()</code>	Tab delimited values
<code>write_rds()</code>	A data type used by R to save objects
<code>write_sas()</code>	SAS .sas7bdat files
<code>write_xpt()</code>	SAS transport format, .xpt
<code>write_sav()</code>	SPSS .sav files
<code>write_stata()</code>	Stata .dta files

```
write_csv(diabetes, file = "diabetes-clean.csv")
```

## Your Turn 4

**R has a few data file types, such as RDS and .Rdata. Save diabetes as "diabetes.Rds".**

## Your Turn 4

R has a few data file types, such as RDS and .Rdata. Save diabetes as "diabetes.Rds".

```
write_rds(diabetes, "diabetes.Rds")
```