

## 17.11 Stream<String> Manipulations

*[This section demonstrates how lambdas and streams can be used to simplify programming tasks that you learned in [Chapter 14](#), [Strings](#), [Characters](#) and [Regular Expressions](#).]*

So far, we've manipulated only streams of `int` values and `Integer` objects. [Figure 17.12](#) performs similar stream operations on a `Stream<String>`. In addition, we demonstrate *case-insensitive sorting* and sorting in *descending* order. Throughout this example, we use the `String` array `strings` (lines 9–10) that's initialized with color names—some with an initial uppercase letter. Line 13 displays the contents of `strings` *before* we perform any stream processing. We walk through the rest of the code in [Sections 17.11.1–17.11.3](#).

```
1  // Fig. 17.12: ArraysAndStreams2.java
2  // Demonstrating lambdas and streams with an array
3      import java.util.Arrays;
4      import java.util.Comparator;
5      import java.util.stream.Collectors;
6
7      public class ArraysAndStreams2 {
8          public static void main(String[] args) {
9              String[] strings =
10                 {"Red", "orange", "Yellow", "green", "Blue", "purple"};
11          }
```

```

12          // display original strings
13      System.out.printf("Original strings: %s%n"
14
15          // strings in uppercase
16      System.out.printf("strings in uppercase: %
17          Arrays.stream(strings)
18          .map(String::toUpperCase)
19          .collect(Collectors.toList()));
20
21      // strings less than "n" (case insensitive
22      System.out.printf("strings less than n sor
23          Arrays.stream(strings)
24          .filter(s -> s.compareToIgnoreCase
25          .sorted(String.CASE_INSENSITIVE_0
26          .collect(Collectors.toList()));
27
28      // strings less than "n" (case insensitive
29      System.out.printf("strings less than n sor
30          Arrays.stream(strings)
31          .filter(s -> s.compareToIgnoreCase
32          .sorted(String.CASE_INSENSITIVE_0
33          .collect(Collectors.toList()));
34      }
35  }

```

Original strings: [Red, orange, Yellow, green, Blue,  
strings in uppercase: [RED, ORANGE, YELLOW, GREEN, BL  
strings less than n sorted ascending: [Blue, green, i  
strings less than n sorted descending: [indigo, green

**Fig. 17.12**

Demonstrating lambdas and streams with an array of

Strings.

## 17.11.1 Mapping Strings to Uppercase

The stream pipeline in lines 17–19

```
Arrays.stream(strings)
    .map(String::toUpperCase)
    .collect(Collectors.toList());
```

displays the `Strings` in uppercase letters. To do so, line 17 creates a `Stream<String>` from the array `strings`, then line 18 maps each `String` to its uppercase version by calling `String` instance method `toUpperCase` on each stream element.

`Stream` method `map` receives an object that implements the `Function` functional interface, representing a one-parameter method that performs a task with its parameter then returns the result. In this case, we pass to `map` an **unbound instance method reference** of the form

*ClassName::instanceMethodName*

(`String::toUpperCase`). “Unbound” means that the method reference does not indicate the specific object on which the method will be called—the compiler converts this to a one-parameter lambda that invokes the instance method on the lambda’s parameter, which must have type *ClassName*. In

this case, the compiler converts `String::toUpperCase` into a lambda like

```
s -> s.toUpperCase()
```

which returns the uppercase version of the lambda's argument. Line 19 collects the results into a `List<String>` that we output as a `String`.

## 17.11.2 Filtering Strings Then Sorting Them in Case-Insensitive Ascending Order

The stream pipeline in lines 23–26

```
Arrays.stream(strings)
    .filter(s -> s.compareToIgnoreCase("n") < 0)
    .sorted(String.CASE_INSENSITIVE_ORDER)
    .collect(Collectors.toList())
```

filters and sort the `Strings`. Line 23 creates a `Stream<String>` from the array `strings`, then line 24 calls `Stream` method `filter` to locate all the `Strings` that are less than "n", using a *case-insensitive* comparison in the `Predicate` lambda. Line 25 sorts the results and line 26 collects them into a `List<String>` that we output as a

String.

In this case, line 25 invokes the version of `Stream` method `sorted` that receives a `Comparator` as an argument. A `Comparator` defines a `compare` method that returns a negative value if the first value being compared is less than the second, 0 if they're equal and a positive value if the first value is greater than the second. By default, method `sorted` uses the *natural order* for the type—for `Strings`, the natural order is case sensitive, which means that "Z" is less than "a".

Passing the predefined `Comparator`

`String.CASE_INSENSITIVE_ORDER` performs a *case-insensitive* sort.

## 17.11.3 Filtering Strings Then Sorting Them in Case- Insensitive Descending Order

The stream pipeline in lines 30–33

```
Arrays.stream(strings)
    .filter(s -> s.compareToIgnoreCase("n") < 0)
    .sorted(String.CASE_INSENSITIVE_ORDER.reversed())
    .collect(Collectors.toList());
```

performs the same tasks as lines 23–26, but sorts the `Strings`

in *descending* order. Functional interface `Comparator` contains default method `reversed`, which reverses an existing `Comparator`'s ordering. When you apply `reversed` to `String.CASE_INSENSITIVE_ORDER`, `sorted` performs a case-insensitive sort and places the `Strings` in *descending* order