



Registration, segmentation, and visualization of multimodal brain images

M.A. Viergever*, J.B.A. Maintz, W.J. Niessen, H.J. Noordmans, J.P.W. Pluim, R. Stokking,
K.L. Vincken

Image Sciences Institute, University Medical Center Utrecht, Heidelberglaan 100, 3584 CX Utrecht, The Netherlands

Received 20 April 2000

Abstract

This paper gives an overview of the studies performed at our institute over the last decade on the processing and visualization of brain images, in the context of international developments in the field. The focus is on multimodal image registration and multimodal visualization, while segmentation is touched upon as a preprocessing step for visualization. The state-of-the-art in these areas is discussed and suggestions for future research are given. © 2001 Elsevier Science Ltd. All rights reserved.

Keywords: Brain imaging; Multimodality registration; Segmentation; Visualization; Image fusion

1. Introduction

In a growing number of clinical studies, images are acquired from multiple imaging modalities. For an optimal interpretation of the multimodal information, integration of the images is called for.

Image integration (or image fusion) consists of two steps:

- (1) (co)registration (or matching, or alignment), where the images are brought into spatial agreement; and
- (2) integrated or multimodality display (or presentation, or visualization), where the registered multimodality (or intermodality) information is rendered.

The second step implies some form of image segmentation or classification.

The scope of the present paper is the registration and integrated presentation of intermodality, intrasubject volumetric clinical brain images. The work of the last decade in Utrecht, in registering, segmenting and visualizing multimodal brain images is briefly described, and the state-of-the-art developments in the field are briefly reviewed so as to put our work into perspective; a full coverage of the field is not aimed at. In Section 5, a number of open questions will be discussed and directions for further research will be suggested.

2. Registration

Techniques to bring multimodal images into register can be classified according to various criteria as, e.g. elasticity of the transformation (rigid, affine, projective, curved), or extrinsic vs. intrinsic matching (i.e. using external fiducial markers vs. using the image information per se). A recent, comprehensive review of medical image registration with a classification scheme comprising the above criteria as well as many others is given in Refs. [1,2].

Registration in intermodality brain imaging is usually restricted to rigid transformations. Curved (elastic) transformations are relevant for intramodality matching, which occurs in atlas based registration, in comparative population studies, and in longitudinal studies of a single patient; however, this is beyond the scope of the present paper. Scaling may be important, but scaling parameters can generally be derived from the header information and thus be disregarded in the computational registration process, leaving only rotation and translation to be considered.

Extrinsic and intrinsic matching have both been applied extensively in brain image registration. The artificial fiducial markers that underlie extrinsic matching may be skull screws, stereotactic frames, head or dental adapters, or skin markers. Skin markers are the most patient-friendly fiducials, applicable in all imaging modalities, and are — slightly surprisingly — at least as accurate as the invasive frames [3]. However, extrinsic matching cannot be applied retrospectively; the marker placement has to be included in the clinical protocol, which is a serious disadvantage. Furthermore, since intrinsic matching has improved significantly over the last few years,

* Corresponding author. Tel.: +31-30-250-7771; fax: +31-30-251-3399.
E-mail address: max@isi.uu.nl (M.A. Viergever).

extrinsic registration is losing ground, and is applied only when image information is sparse (as in EEG or MEG) or when markers have to be applied anyway, notably in stereotactic frame based neurosurgery.

The oldest form of intrinsic matching is based on manual placement of corresponding landmarks in two images. This procedure is subjective, inaccurate and time-consuming, and is thus no longer used in rigid registration; for elastic registration, landmarks are still quite useful. Surface-based matching requires the segmentation of the skin or the cerebral cortex from the images to be registered. This is a high-level image processing operation which may be performed accurately, but is inherently imprecise (non-robust). Surface-based registration is still used in many centres, but is ripe for replacement.

The method of choice for multimodality brain image registration has become voxel based matching. There are two approaches: (i) based on the image intensities directly; and (ii) based on feature images derived from the original images by, e.g., edge or ridge detectors. The latter approach has been studied extensively by us [1,3–5] and has been quite successful. Nonetheless, approach (i) seems preferable because it provides results that are at least as good [6], at less computational costs. The paradigm is simple: the histograms of two images to be registered define a 2D feature space (a scatter plot, see Fig. 1), which has the property of becoming more fuzzy with increasing misregistration. The registration of two images can thus be performed by maximizing the ‘crispness’ in some sense. The optimum criterion has been derived to be maximization of the mutual information of the two images, an information theory measure that is a generalization of joint entropy minimization. An extensive description and a comparison with similar, earlier attempts can be found in Refs. [7–13].

3. Segmentation

Segmentation has been, is, and probably will long remain the key problem of image analysis. It is well beyond the scope of this paper to give a survey of image segmentation, or even of medical image segmentation. We will confine ourselves to the segmentation of brain images in so far as it is relevant to multimodality image integration. The main segmentation task in brain image matching is the extraction of the total brain (i.e., distinction between brain tissue and CSF). This task can be automated for a given MR protocol, even with a simple threshold-based technique [14,15]. Automated segmentation has proven sufficiently accurate for volumetric display (Fig. 2) and may also be adequate for estimates of total brain volume [16,17]. However, more detailed studies of brain anatomy and physiology will require more powerful segmentation methods.

Multiscale image analysis [18–20] has appeared pre-eminently suited for intricate segmentation tasks in a variety of applications. The inclusion of partial volume effects in the




Fig. 1. Scatter-plot of the histograms of a pair of PET (horizontal axis) and MR (vertical axis) images. Left frame: images in register. Right frame: images misregistered by a translation of 10 mm along the two in-plane axes.




Fig. 2. Comparison of volume renderings of the brain, based on automatic (left) and manual (right) segmentation of T_1 -weighted MR data.

segmentation paradigm has especially proven valuable [19,21]. The ‘hyperstack’ segmentation approach has yielded reproducible results for tasks like grey matter/white matter separation or segmentation of the ventricles. The approach deliberately provides an oversegmentation of the object to be defined, typically by a factor of five, whereupon a merging process completes the segmentation. The merging process is usually performed manually, but can be automated for well-defined tasks [22].

4. Visualization

Registered volumetric images can be displayed in 2D (single slices) without a pre-segmentation, e.g., by juxtaposition with a linked cursor or by non-selective integration as subtraction, alternate pixel (‘chessboard’) display or colour washing [14]. However, the information transfer of this type of display is limited.

Contoured 2D or 3D display (Fig. 3) paradigms all require some form of segmentation or classification. In contoured 2D display the delineation of the cerebral cortex is generally required, while other structures like the ventricles or the lesion at issue may also be outlined. However simple these techniques may seem, the gain in accuracy in localizing lesions may be considerable [14,17].

Volumetric visualization is more powerful still. There are basically two approaches to 3D display [23]. One is by defining the surfaces to be visualized by a binary segmentation




Fig. 3. SPECT/MRI multimodality display of a patient with a right frontal lobe tumour. Left frame: 2D contoured display. The grey values represent a slice of the SPECT image; the brain contour and the tumour area were delineated in a corresponding registered MR slice. Right frame: 3D normal fusion display. The brain surface was (automatically) segmented from an MR- T_1 image; the SPECT perfusion values were integrated along the surface normal and colour coded onto the surface. The dark area in the right frontal lobe signals increased perfusion and was found to surround the tumour.

(i.e. a voxel is either on one side of the surface, or on the other). This approach, surface rendering, has the advantage of allowing visualization by standard graphics tools, but has the drawback that the binary segmentation leads to errors in the surface definition. The second approach, volume rendering, has the significant advantage that a ‘hard’ segmentation is not needed. The method just requires a rough classification of the tissues traversed by the rays cast into the volume. The partial volume hyperstack segmentation [19] has turned out to be a good pre-processor for volume rendering, although in many cases simpler methods, e.g. based on histograms, may suffice.

Volume rendering is — much more than surface rendering — suitable for multimodality display [23,24].

The ‘fuzzy’ surface definition allows a more natural integration of the functional image modality (SPECT, PET). We have developed an approach (normal fusion) where the functional information is integrated along the inward normal to the cortical surface; the result is colour coded onto the cortex. An example of SPECT/MRI fusion is given in Fig. 3b. By varying the depth of integration of the functional modality, an insight can be gained into the functional anatomy of the cortical processes; see Fig. 4.

For neurosurgical procedures, the combined visualization of cortical structures and functional information is beneficial both in the planning phase and for intraoperative guidance. Fig. 5 gives an integrated presentation of cortical anatomy and functional MRI information, which shows critical cortical areas (the motor strip) in relation to a nearby tumour which is to be surgically removed.

For more examples of multimodality visualization, we refer the interested reader to our website: <http://www.isi.uu.nl>.

5. Conclusions and discussion

Maximization of mutual information has appeared to be a powerful method for registering volumetric (CT/MRI, PET/MRI, SPECT/MRI) brain image pairs [6–13]. It has also appeared successful for rigid monomodality (MRI/MRI, etc.) registration [10]. Despite its success in the comprehensive Vanderbilt multicentre trial [6], the approach still needs to be evaluated extensively, in particular as concerns its dependency on the choice of entropy in the information measure, on the optimization paradigm,




Fig. 4. Integrated SPECT/MRI visualization of a patient with Gilles de la Tourette syndrome. The normal fusion paradigm was used. The three frames show integration of functional SPECT information over 1 mm (left), 5 mm (middle), 15 mm (right).




Fig. 5. Integrated visualization of functional MRI information and cortical anatomy. In the left frame, the standard visualization approach is shown. The deeper fMRI voxels are not visible owing to occlusion by brain tissue. In the middle frame, transparency has been used to bring out the deeper fMRI voxels, at the expense of a degraded view of the gyral–sulcal pattern. The right frame presents a multispectral display (see Ref. [25] for details of the technique). The brain is transparent for light scattered by the fMRI voxels. The subcortical fMRI areas are visible without disturbing the view on the cortex.

and on the resampling technique [26] applied in the transformations. An as yet underrated issue is that mutual information does not include spatial connectivity. Paradigms which would combine the advantageous statistical characteristics of mutual information maximization with spatial correlation as exhibited, e.g. by feature-based methods, are worthy of further investigation. Another interesting point of research is the influence of the imaging physics on the registration. MRI distortion correction [6] and SPECT or PET scatter modelling may aid significantly in reducing the registration error. The main directions of future research in image registration will, however, be real-time matching for intraoperative image guidance and curved (elastic) matching for both intermodality and intramodality image alignment.

Segmentation of brain images can be done automatically for well-defined tasks as total brain segmentation or white matter/grey matter differentiation. More complex tasks require an interactive procedure. Interactive segmentation will require substantial guidance by model knowledge, which may include both imaging physics and characteristics of the object to be segmented. Interactive segmentation of volumetric data furthermore calls for fast visualization techniques and suitable user interfaces. Finally, registered multimodal images facilitate multimodality (multispectral, multiparameter) segmentation methods. This is a largely unexplored research area, which will probably be developed in the coming years.

Multimodality visualization has proven to have great clinical potential [14,17]. A major research issue is the design and evaluation of display approaches for specific applications, since visualization is highly task-driven. Clinical validation of such procedures requires both a thorough methodological set-up and significant efforts of multiple experts. The latter aspect especially makes the evaluation of visualization techniques a rarity in scientific literature.

For interventional multimodality visualization, where preoperative images are combined with intraoperative images, other problems have to be solved first, notably as regards computational speed. While the preoperatively acquired images can be pre-segmented, which removes the need for on-line segmentation, real-time multimodality visualization does require real-time registration. Fiducial markers can provide on-line alignment, except for changes in geometry during the intervention as, notably, the brain shift occurring upon trepanation. Accordingly, correction for such changes will be the primary research objective in interventional image guidance.

References

- [1] Maintz JBA. Retrospective registration of tomographic brain images. PhD thesis, Utrecht University, 1996.
- [2] Maintz JBA, Viergever MA. A survey of medical image registration. *Medical Image Analysis* 1998;2:1–36.
- [3] Van den Elsen PA. Multimodality matching of brain images. PhD thesis, Utrecht University, 1993.
- [4] Van den Elsen PA, Maintz JBA, Pol EJD, Viergever MA. Automatic registration of CT and MR brain images using correlation of geometrical features. *IEEE Transactions on Medical Imaging* 1995;14:384–98.
- [5] Maintz JBA, Van den Elsen PA, Viergever MA. Evaluation of ridge seeking operators for multimodality image matching. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 1996;18:353–65.
- [6] West J, Fitzpatrick JM, Wang MY, et al. Comparison and evaluation of retrospective intermodality brain image registration techniques. *Journal of Computer Assisted Tomography* 1997;21:554–66.
- [7] Viola PA. Alignment by maximization of mutual information. PhD thesis, Massachusetts Institute of Technology, 1995.
- [8] Studholme C. Measures of 3D medical image alignment. PhD thesis, University of London, 1997.
- [9] Collignon A. Multimodality medical image registration by maximization of mutual information. PhD thesis, University of Leuven, 1998.
- [10] Maes F. Segmentation and registration of multimodal medical images. PhD thesis, University of Leuven, 1998.
- [11] Maes F, Collignon A, Vandermeulen D, Marchal G, Suetens P. Multimodality image registration by maximization of mutual information. *IEEE Transactions on Medical Imaging* 1997;16:187–98.
- [12] Studholme C, Hill DLG, Hawkes DJ. Automated three-dimensional registration of magnetic resonance and positron emission tomography brain images by multiresolution optimization of voxel similarity measures. *Medical Physics* 1997;24:25–35.
- [13] Viola PA, Wells III WM. Alignment by maximization of mutual information. *International Journal of Computer Vision* 1997;24:137–54.
- [14] Stokking R. Integrated visualization of functional and anatomical brain images. PhD thesis, Utrecht University, 1998.
- [15] Lemieux L, Hagemann G, Krakow K, Woermann FG. Fast, accurate, and reproducible automatic segmentation of the brain in T1-weighted volume MRI data. *Magnetic Resonance in Medicine* 1999;42:127–35.
- [16] Stokking R, Zuiderveld KJ, Hulshoff Pol HE, Van Rijk PP, Viergever MA. Normal fusion for three-dimensional integrated visualization of SPECT and magnetic resonance brain images. *Journal of Nuclear Medicine* 1997;38:624–9.
- [17] Stokking R, Van Isselt JW, Van Rijk PP, et al. Integrated visualization of functional and anatomical brain data: a validation study. *Journal of Nuclear Medicine* 1999;40:311–6.
- [18] Koster ASE. Linking models for multiscale image segmentation. PhD thesis, Utrecht University, 1995.
- [19] Vincken KL. Probabilistic multiscale image segmentation by the hyperstack. PhD thesis, Utrecht University, 1995.
- [20] Niessen WJ. Multiscale medical image analysis. PhD thesis, Utrecht University, 1997.
- [21] Vincken KL, Koster ASE, Viergever MA. Probabilistic multiscale image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 1997;19:109–20.
- [22] Niessen WJ, Vincken KL, Weickert J, Ter Haar Romeny BM, Viergever MA. Multiscale segmentation of three-dimensional MR brain images. *International Journal of Computer Vision* 1999;31:185–202.
- [23] Zuiderveld KJ. Visualization of multimodality medical volume data using object-oriented methods. PhD thesis, Utrecht University, 1995.
- [24] Zuiderveld KJ, Koning AHJ, Stokking R, Maintz JBA, Appelman FA, Viergever MA. Multimodality visualization of medical volume data. *Computer and Graphics* 1996;20:775–91.
- [25] Noordmans HJ, Van der Voort HTM, Rutten GJM, Viergever MA. Physically realistic visualization of embedded volume structures for medical image data. *Proceedings of the SPIE* 1999;3658:613–20 (Medical Imaging: Image Display).
- [26] Pluim JPW, Maintz JBA, Viergever MA. Interpolation artefacts in mutual information-based image registration. *Computer Vision and Image Understanding* 2000;77:211–32.

Max A. Viergever received the MSc degree in Applied Mathematics in 1972 and the DSc degree with a thesis on Cochlear Mechanics in 1980, both from Delft University of Technology, The Netherlands. From 1972 to 1988 he was Assistant/Associate Professor of Applied Mathematics at this university. Since 1988 he has been Professor and Head of the Department of Medical Imaging at Utrecht University, since 1996 Adjunct Professor of Computer Science at the same university, and the Scientific Director of the Image Sciences Institute of the University Medical Center Utrecht, and as of 1998 Director of the Graduate School of Biomedical Image Sciences (ImagO). He is (co)author of over 350 refereed scientific articles (abstracts excluded) on biophysics and medical image processing, guest editor of six journal issues, and (co)author/editor of 14 books. His research interests comprise all aspects of computer vision and medical imaging. He is a Board Member of IAPR, IPMI and MICCAI, Editor of the book series *Computational Imaging and Vision* of Kluwer Academic Publishers, Associate Editor-in-Chief of the *IEEE Transactions on Medical Imaging*, Editor of the *Journal of Mathematical Imaging and Vision*, and participates on the editorial boards of five other international journals.

J.B. Antoine Maintz received the MSc degree in Applied Mathematics in 1992 from Delft University of Technology, and the PhD degree with a thesis on Medical Image Registration in 1996 from Utrecht University. After a year as a Post-Doctoral Fellow at the Department of Neurosurgery and the Image Sciences Institute of the University Medical Center Utrecht, he joined the Department of Computer Science at Utrecht University as an Assistant Professor and Student Advisor in 1997. He is (co)author of 35 refereed papers on medical image processing, three of which were awarded. His research interests are medical and general image processing, with a focus on image registration. His teaching tasks include graduate courses on image processing, student counselling, and (co)authoring and implementing the University MSc curriculum for Medical Computer Science. In 1999, he was one of four nominees for the Utrecht University 'teacher of the year' award.

Wiro J. Niessen received the MSc degree in Physics in 1993 and the PhD degree with a thesis on Multiscale Medical Image Analysis in 1997, both from Utrecht University. Since 1997 he has had a research position at the Image Sciences Institute of the University Medical Center Utrecht, where, since 1999, he has been the Head of the Clinical Image Processing and Visualization Group. He is (co)author of over 50 scientific articles in medical image processing and computer vision. His current research interests cover a broad spectrum in the fields of medical image processing and computer aided surgery. He is Associate Editor of the *IEEE Transactions on Medical Imaging* and of *Medical Image Analysis*.

Herke Jan Noordmans studied Applied Physics at the University of Twente, Enschede, The Netherlands, and received the MSc degree in 1991 with a thesis on the subject of Light Scattering Properties of White Blood Cells in a Flow Cytometer. From 1992 to 1997 he worked as a PhD student at the University of Amsterdam, where he received his PhD with a thesis on Interactive Analysis of 3D Microscope Images. After a brief period while he worked for Cornerstone Technology BV, Dordrecht to redesign their millennium tool, he returned to academia in 1998 and has since been a Post-Doctoral Fellow at the Department of Neurosurgery and the Image Sciences Institute of the University Medical Center Utrecht, investigating and applying image analysis and visualization algorithms to epilepsy surgery.

Josien P.W. Pluim received the MSc degree in Computer Science from the University of Groningen, The Netherlands, in 1996. She is currently employed as a PhD student at the Image Sciences Institute of the University Medical Center Utrecht focusing on registration of multimodal medical images.

Rik Stokking received the MSc degree in Medical Biology from Utrecht University in 1990. After his military service as a Lieutenant at the RIVM public health research facilities in Bilthoven, he worked as a PhD student at the Image Sciences Institute of the University Medical Center Utrecht where he obtained his PhD degree in 1998 with a thesis entitled 'Integrated Visualization of Functional and Anatomical Brain Images'. He then joined the Yale Image Processing Analysis Group in New Haven, USA, as a Post-Doctoral Researcher working on SPECT difference analysis in epilepsy. Currently he is employed as an Associate Research Scientist at the Montreal Neurological Institute of McGill University, Montreal, Canada.

Koen L. Vincken received the MSc degree in Computer Science from Delft University of Technology in 1989. He then joined Utrecht University as a PhD student and received the PhD degree with a thesis on multiscale image segmentation in 1995. He is currently a Research Associate at the Image Sciences Institute of the University Medical Center Utrecht. His research interests comprise medical image segmentation and computer aided diagnosis in radiology.