

AIQDA PROFESSIONAL GUIDE

Tracking Implementation Guide

This guide documents Aiqda's current analytics architecture and the exact steps required to complete Google Tag Manager, Google Analytics 4, and Meta Pixel configuration using the live implementation now present in the codebase.

PREPARED ON

August 4, 2026

GTM CONTAINER

GTM-MF72G76S

META PIXEL

1022093374056344

1. Current Implementation Status

Current model: Aiqda now uses a GTM-managed GA4 architecture. Direct GA4 event dispatch from frontend code has been removed.

The frontend currently does the following:

- Pushes structured events into `window.dataLayer` for GTM.
- Sends internal product analytics events to the backend for Aiqda's own reporting.
- Sends Meta Pixel events through `fbq`.

The frontend no longer loads `gtag.js` or sends GA4 events directly. GA4 should now be configured entirely inside Google Tag Manager.

2. Aiqda Event Model

The following key events are already produced by the site and pushed into the GTM data layer:

page_view

session_start

page_engagement

scroll_depth

search

file_download

navigation_click

outbound_click

cta_click

sign_up

generate_lead

begin_checkout

add_payment_info

purchase

aiqda_user_context

aiqda_user_context_cleared

The same event stream is also used for internal dashboard analytics. GTM should therefore only be used for external analytics/tagging destinations and should not replace the internal backend event ingestion.

3. Data Layer Variables To Create In GTM

Create the following Data Layer Variables in Google Tag Manager:

- `page_title`
- `page_path`
- `page_location`
- `locale`
- `visitor_id`
- `session_id`
- `referrer`
- `utm_source`
- `utm_medium`
- `utm_campaign`

- `utm_term`
- `utm_content`
- `label`
- `href`
- `destinationPath`
- `percent`
- `searchTerm`
- `engagementTimeMs`
- `maxScrollPercent`
- `user_role` and `subscription_status`

4. GTM Configuration Steps

4.1 Create The Google Tag

1. Open Google Tag Manager.
2. Select container `GTM-MF72G76S`.
3. Go to **Tags** and create a new tag.
4. Select tag type **Google tag**.
5. Enter your GA4 Measurement ID: `G-DXPP8Z7FVT`.
6. Set the trigger to **Initialization - All Pages**.
7. Save the tag.

4.2 Create Custom Event Triggers

Create one Custom Event trigger for each Aiqda event listed in Section 2.

TRIGGER NAME	EVENT NAME
CE - page_view	page_view
CE - session_start	session_start
CE - page_engagement	page_engagement
CE - scroll_depth	scroll_depth
CE - search	search
CE - file_download	file_download
CE - navigation_click	navigation_click
CE - outbound_click	outbound_click
CE - cta_click	cta_click
CE - sign_up	sign_up
CE - generate_lead	generate_lead
CE - begin_checkout	begin_checkout
CE - add_payment_info	add_payment_info
CE - purchase	purchase

4.3 Create GA4 Event Tags

Recommended mapping:

AIQDA EVENT	GA4 EVENT NAME	MAIN PARAMETERS
page_view	page_view	page_title , page_path , page_location , locale , visitor_id , session_id
session_start	session_start	page_path , locale

AIQDA EVENT	GA4 EVENT NAME	MAIN PARAMETERS
page_engagement	page_engagement	engagement_time_msec , max_scroll_percent
scroll_depth	scroll	percent_scrolled
search	search	search_term
file_download	file_download	link_url , link_text
navigation_click	select_content	item_name , link_url , destination_path
outbound_click	click	link_url , link_text
cta_click	select_content	item_name
sign_up	sign_up	default payload plus any registration metadata
generate_lead	generate_lead	lead context parameters if applicable
begin_checkout	begin_checkout	package, value, currency when available
add_payment_info	add_payment_info	payment-related context
purchase	purchase	value, currency, transaction/package identifiers

5. GA4 Property Configuration

5.1 Custom Definitions

Create event-scoped custom dimensions in GA4 for the most important custom parameters:

- locale
- visitor_id
- session_id
- destinationPath
- maxScrollPercent

If you later send user properties through GTM, create user-scoped custom dimensions for:

- user_role
- subscription_status

5.2 Key Events

Mark these as GA4 key events:

- `sign_up`
- `generate_lead`
- `begin_checkout`
- `purchase`
- Optionally `add_payment_info` if you want to analyze payment-step drop-off.

6. Meta Pixel Configuration

Meta Pixel ID `1022093374056344` is already integrated in the frontend code.

The implementation currently maps the following events:

- `PageView`
- `Search`
- `CompleteRegistration`
- `Lead`
- `InitiateCheckout`
- `AddPaymentInfo`
- `Purchase`
- Custom Meta events for everything else

7. Testing Procedure

7.1 GTM Preview

1. Open GTM and click **Preview**.
2. Connect to the target site URL.
3. Navigate through the site and confirm the expected events appear in Tag Assistant.

7.2 GA4 Realtime

1. Open GA4 **Realtime**.
2. Perform the same actions on the site.

3. Confirm events are arriving in Realtime.

7.3 Meta Events Manager

1. Open Meta Events Manager and select Pixel `1022093374056344`.
2. Use **Test Events**.
3. Confirm `PageView`, `Lead`, `InitiateCheckout`, and `Purchase` appear when expected.

Use GTM Preview before publishing container changes. This reduces the risk of duplicate or malformed GA4 events.

8. Production Notes

For production builds, ensure the frontend environment includes:

- `VITE_GTM_CONTAINER_ID=GTM-MF72G76S`
- `VITE_META_PIXEL_ID=1022093374056344`

The old `VITE_GA4_MEASUREMENT_ID` value can remain documented for reference, but GA4 dispatch now happens through GTM rather than direct frontend code.

9. Official References

- Google Tag setup in GTM: support.google.com/tagmanager/answer/9442095
- GA4 events in GTM: support.google.com/tagmanager/answer/13034206
- GTM Preview and debug: support.google.com/tagmanager/answer/6107056
- GA4 event-scoped custom dimensions:
support.google.com/analytics/answer/14239696
- GA4 user-scoped custom dimensions:
support.google.com/analytics/answer/14239618
- GA4 key events: support.google.com/analytics/answer/9267568