

1. **Vue logique (conceptuelle)**
2. **Schéma relationnel détaillé**
3. **SQL PostgreSQL (DDL) prêt à implémenter**

1 Vue logique globale (conceptuelle)

Entités majeures

- Users (clients, fournisseurs, admins)
- Companies / Professionals
- Categories & Domains
- Locations (pays / régions / villes)
- IA Scraping & Enrichment
- Social Feed (posts, likes, comments, follows)
- Services & Products
- Orders / Reservations
- Reviews & Recommendations
- Documents (devis, contrats, factures)
- Payments (référence uniquement – paiement externe)
- Notifications

2 Schéma relationnel (liste des tables)

Utilisateurs & rôles

- users
- roles
- user_roles

Entreprises & professionnels

- companies
- company_claims
- professionals
- company_professionals

Localisation & international

- countries

- regions
- cities

Catégorisation

- categories
- subcategories
- company_categories

IA & Scraping

- scraped_sources
- scraped_companies
- ai_enrichment_logs
- company_contacts_log

Réseau social

- posts
- post_media
- post_likes
- post_comments
- follows

Services & Produits

- services
- service_availability
- products
- product_images

Commandes & réservations

- orders
- order_items
- reservations

Avis & recommandations

- reviews
- recommendations

Documents légaux

- documents

- document_templates
- document_signatures

Paiements (référence)

- payment_references

Notifications

- notifications

Schéma SQL PostgreSQL (livrable)

 Le développeur peut copier-coller directement.

USERS

```
CREATE TABLE users (
    id UUID PRIMARY KEY,
    email VARCHAR(255) UNIQUE NOT NULL,
    password_hash TEXT,
    full_name VARCHAR(255),
    phone VARCHAR(50),
    avatar_url TEXT,
    is_active BOOLEAN DEFAULT TRUE,
    created_at TIMESTAMP DEFAULT NOW()
);

CREATE TABLE roles (
    id SERIAL PRIMARY KEY,
    name VARCHAR(50) UNIQUE
);

CREATE TABLE user_roles (
    user_id UUID REFERENCES users(id),
    role_id INT REFERENCES roles(id),
    PRIMARY KEY (user_id, role_id)
);
```

ENTREPRISES / PROFESSIONNELS

```
CREATE TABLE companies (  
    id UUID PRIMARY KEY,  
    name VARCHAR(255),  
    description TEXT,  
    website TEXT,  
    email VARCHAR(255),  
    phone VARCHAR(50),  
    logo_url TEXT,  
    cover_url TEXT,  
    country_id INT,  
    region_id INT,  
    city_id INT,  
    is_claimed BOOLEAN DEFAULT FALSE,  
    created_by_ai BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMP DEFAULT NOW()  
);
```

```
CREATE TABLE company_claims (  
    id SERIAL PRIMARY KEY,  
    company_id UUID REFERENCES companies(id),  
    user_id UUID REFERENCES users(id),  
    status VARCHAR(30), -- pending, approved, rejected  
    created_at TIMESTAMP DEFAULT NOW()  
);
```

LOCALISATION

```
CREATE TABLE countries (  
    id SERIAL PRIMARY KEY,  
    name VARCHAR(100),  
    code VARCHAR(5)  
);
```

```
CREATE TABLE regions (  
    id SERIAL PRIMARY KEY,  
    country_id INT REFERENCES countries(id),  
    name VARCHAR(100)  
);  
  
CREATE TABLE cities (  
    id SERIAL PRIMARY KEY,  
    region_id INT REFERENCES regions(id),  
    name VARCHAR(100)  
);
```

CATÉGORIES

```
CREATE TABLE categories (  
    id SERIAL PRIMARY KEY,  
    name VARCHAR(100)  
);  
  
CREATE TABLE subcategories (  
    id SERIAL PRIMARY KEY,  
    category_id INT REFERENCES categories(id),  
    name VARCHAR(100)  
);  
  
CREATE TABLE company_categories (  
    company_id UUID REFERENCES companies(id),  
    subcategory_id INT REFERENCES subcategories(id),  
    PRIMARY KEY (company_id, subcategory_id)  
);
```

IA SCRAPING & ENRICHISSEMENT

```
CREATE TABLE scraped_sources (  
    id SERIAL PRIMARY KEY,  
    source_type VARCHAR(50), -- website, google, social
```

```

    source_url TEXT
);
CREATE TABLE scraped_companies (
    id SERIAL PRIMARY KEY,
    source_id INT REFERENCES scraped_sources(id),
    raw_data JSONB,
    processed BOOLEAN DEFAULT FALSE,
    created_at TIMESTAMP DEFAULT NOW()
);
CREATE TABLE ai_enrichment_logs (
    id SERIAL PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    action VARCHAR(100),
    details JSONB,
    created_at TIMESTAMP DEFAULT NOW()
);
CREATE TABLE company_contacts_log (
    id SERIAL PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    channel VARCHAR(50), -- email, whatsapp, linkedin
    message TEXT,
    sent_at TIMESTAMP DEFAULT NOW()
);

```

RÉSEAU SOCIAL

```

CREATE TABLE posts (
    id UUID PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    content TEXT,
    created_at TIMESTAMP DEFAULT NOW()
);

```

```

CREATE TABLE post_media (
    id SERIAL PRIMARY KEY,
    post_id UUID REFERENCES posts(id),
    media_url TEXT,
    media_type VARCHAR(20)
);

CREATE TABLE post_likes (
    post_id UUID REFERENCES posts(id),
    user_id UUID REFERENCES users(id),
    PRIMARY KEY (post_id, user_id)
);

CREATE TABLE post_comments (
    id SERIAL PRIMARY KEY,
    post_id UUID REFERENCES posts(id),
    user_id UUID REFERENCES users(id),
    comment TEXT,
    created_at TIMESTAMP DEFAULT NOW()
);

CREATE TABLE follows (
    user_id UUID REFERENCES users(id),
    company_id UUID REFERENCES companies(id),
    PRIMARY KEY (user_id, company_id)
);

```

SERVICES & PRODUITS

```

CREATE TABLE services (
    id UUID PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    name VARCHAR(255),
    description TEXT,
    price NUMERIC,

```

```
    duration INT
);
CREATE TABLE products (
    id UUID PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    name VARCHAR(255),
    description TEXT,
    price NUMERIC,
    stock INT
);
```

COMMANDES & RÉSERVATIONS

```
CREATE TABLE orders (
    id UUID PRIMARY KEY,
    user_id UUID REFERENCES users(id),
    company_id UUID REFERENCES companies(id),
    total_amount NUMERIC,
    status VARCHAR(30),
    created_at TIMESTAMP DEFAULT NOW()
);
CREATE TABLE reservations (
    id UUID PRIMARY KEY,
    service_id UUID REFERENCES services(id),
    user_id UUID REFERENCES users(id),
    scheduled_at TIMESTAMP,
    status VARCHAR(30)
);
```

AVIS & RECOMMANDATIONS

```
CREATE TABLE reviews (
    id SERIAL PRIMARY KEY,
```



```
company_id UUID REFERENCES companies(id),
user_id UUID REFERENCES users(id),
rating INT,
comment TEXT,
created_at TIMESTAMP DEFAULT NOW()
);

CREATE TABLE recommendations (
    id SERIAL PRIMARY KEY,
    from_user UUID REFERENCES users(id),
    to_company UUID REFERENCES companies(id),
    message TEXT
);
```

DOCUMENTS

```
CREATE TABLE document_templates (
    id SERIAL PRIMARY KEY,
    type VARCHAR(50), -- contract, invoice, quote
    template TEXT
);

CREATE TABLE documents (
    id UUID PRIMARY KEY,
    company_id UUID REFERENCES companies(id),
    user_id UUID REFERENCES users(id),
    type VARCHAR(50),
    file_url TEXT,
    created_at TIMESTAMP DEFAULT NOW()
);
```

PAIEMENTS (RÉFÉRENCE)

```
CREATE TABLE payment_references (
    id SERIAL PRIMARY KEY,
```

```
order_id UUID REFERENCES orders(id),  
provider VARCHAR(50),  
external_reference VARCHAR(255),  
status VARCHAR(30)  
);
```

NOTIFICATIONS

```
CREATE TABLE notifications (  
    id SERIAL PRIMARY KEY,  
    user_id UUID REFERENCES users(id),  
    title VARCHAR(255),  
    message TEXT,  
    is_read BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMP DEFAULT NOW()  
);
```