Student Attendance System

A simple attendance-recording algorithm, designed as a Flowgorithm flowchart with matching pseudocode. A teacher enters a class name and date, records each student as Present, Absent or Late, and gets a summary with the present percentage.

Files

File	Description
`Student_Attendance_System.fprg`	Flowgorithm flowchart (open with Flowgorithm)
`Student_Attendance_Pseudocode.txt`	Pseudocode of the same algorithm
`README.md`	This file

How to run the flowchart

1. Install Flowgorithm (free) from the official Flowgorithm website.
2. Open Flowgorithm and choose **File > Open**, then select `Student_Attendance_System.fprg`.
3. Press **Run** (the green play button) to execute it in the console.

How the program works

1. Enter the class name and attendance date.
2. Counters for present, absent, late and total start at zero.
3. For each student, enter the ID, name and status (`P` , `A` or `L`).
4. Any other status is rejected and asked for again.
5. The matching counter and the total increase, and a confirmation is shown.
6. Type `yes` to record another student, or anything else to finish.
7. The program shows the present, absent and late totals and the present percentage.

Inputs and outputs

- **Inputs:** class name, date, student ID, student name, status (`P` / `A` / `L`), continue answer (`yes` / `no`).
- **Outputs:** confirmation line per student; final present, absent and late counts; present percentage.

Key variables

Variable	Type	Purpose
`className` , `attDate`	String	Class and date
`studentID` , `studentName`	String	Student details
`status`	String	`P` , `A` or `L`
`another`	String	Loop control (`yes` continues)
`presentCount` , `absentCount` , `lateCount` , `totalCount`	Integer	Counters
`presentPercent`	Real	`presentCount / totalCount * 100`

Programming structures used

- **Input / output:** reading and displaying data
- **Processing:** counter updates and percentage calculation
- **Decision:** `IF / ELSE IF / ELSE` to update the correct counter
- **Repetition:** outer `WHILE` for students, inner `WHILE` for status validation

Notes

- Status and the continue answer are case-sensitive: use capital `P` , `A` , `L` and lowercase `yes` .
- The loop always runs at least once, so the total is never zero when the percentage is calculated.