

jQuery

Afrizal Doewes

What is jQuery?

- jQuery is a lightweight, "write less, do more", JavaScript library.
- jQuery also simplifies a lot of the complicated things from JavaScript, like AJAX calls and DOM manipulation.

Why jQuery?

- There are lots of other JavaScript libraries out there, but jQuery is probably the most popular, and also the most extendable.
- Many of the biggest companies on the Web use jQuery, such as:
 - Google
 - Microsoft
 - IBM
 - Netflix

Cross-Browser Compatibility

- The jQuery team knows all about cross-browser issues, and they have written this knowledge into the jQuery library.
- jQuery will run exactly the same in all major browsers.



How to use jQuery?

- Download the jQuery library
 - Production version
 - Development version
- Include jQuery from a CDN (Content Delivery Network), example: Google.
 - Cache
 - Closest server

Test jQuery

```
<script>
```

```
    $(document).ready(function() {  
        $('p').hide();  
    });
```

```
</script>
```

jQuery Syntax

- Basic syntax is: **\$(selector).action()**
 - A **\$** sign to define/access jQuery
 - A **(selector)** to "query (or find)" HTML elements
 - A jQuery **action()** to be performed on the element(s)

Examples

- `$(this).hide()` - hides the current element.
- `$("p").hide()` - hides all `<p>` elements.
- `$(".test").hide()` - hides all elements with `class="test"`.
- `$("#test").hide()` - hides the element with `id="test"`.

Document ready event

- This is to prevent any jQuery code from running before the document is finished loading (is ready).

```
$(document).ready(function() {  
  
    // jQuery methods go here...  
  
});
```

or ...

```
$(function() {  
  
    // jQuery methods go here...  
  
});
```

jQuery GET

- jQuery methods for DOM manipulation are:
 - `text()` - Sets or returns the text content of selected elements
 - `html()` - Sets or returns the content of selected elements (including HTML markup)
 - `val()` - Sets or returns the value of form fields
 - `attr()` method is used to get attribute values

jQuery SET

- jQuery methods for DOM manipulation are:
 - `text()` - Sets or returns the text content of selected elements
 - `html()` - Sets or returns the content of selected elements (including HTML markup)
 - `val()` - Sets or returns the value of form fields
 - `attr()` method is also used to set/change attribute values.

jQuery Append

- 4 jQuery methods that are used to add new content:
 - `append()` - Inserts content at the end of the selected elements
 - `prepend()` - Inserts content at the beginning of the selected elements
 - `after()` - Inserts content after the selected elements
 - `before()` - Inserts content before the selected elements

jQuery Event Methods

- An event represents the precise moment when something happens.
- Examples:
 - moving a mouse over an element
 - selecting a radio button
 - clicking on an element
- The term "fires/fired" is often used with events. Example: "The keypress event is fired, the moment you press a key".

Common Events

Mouse Events	Keyboard Events	Form Events	Document/Window Events
click	keypress	submit	load
dblclick	keydown	change	resize
mouseenter	keyup	focus	scroll
mouseleave		blur	unload

- jQuery syntax:

```
$("p").click(function() {  
    // action goes here!!  
});
```