

## Tutorial No.1

1. Perform the following operations using Python on suitable data sets, read data from different formats(like csv, xls),indexing and selecting data, sort data, describe attributes of data, checking data types of each column, counting unique values of data, format of each column, converting variable data type (e.g. from long to short, vice versa), identifying missing values and fill in the missing values.

```
[63]: import pandas as pd
import numpy as np

[64]: df=pd.read_csv("nba.csv")
```

### Read Csv File

```
[65]: df
```

	Name	Team	Number	Position	Age	Height	Weight	College	Salary
0	Avery Bradley	Boston Celtics	0.0	PG	25	2-Jun	180	Texas	7730337.0
1	Jae Crowder	Boston Celtics	99.0	SF	25	6-Jun	235	Marquette	6796117.0
2	John Holland	Boston Celtics	30.0	SG	27	5-Jun	205	Boston University	NaN
3	R.J. Hunter	Boston Celtics	28.0	SG	22	5-Jun	185	Georgia State	1148640.0
4	Jonas Jerebko	Boston Celtics	8.0	PF	29	10-Jun	231	NaN	5000000.0
...	...	...	...	...	...	...	...	...	...
452	Trey Lyles	Utah Jazz	41.0	PF	20	10-Jun	234	Kentucky	2239800.0
453	Shelvin Mack	Utah Jazz	8.0	PG	26	3-Jun	203	Butler	2433333.0
454	Raul Neto	Utah Jazz	25.0	PG	24	1-Jun	179	NaN	900000.0
455	Tibor Pleiss	Utah Jazz	21.0	C	26	3-Jul	256	NaN	2900000.0
456	Jeff Withey	Utah Jazz	24.0	C	26	Jul-00	231	Kansas	947276.0

```
4 Jonas Jerebko Boston Celtics 8.0 PF 29 10-Jun 231 NaN 5000000.0
... ..
452 Trey Lyles Utah Jazz 41.0 PF 20 10-Jun 234 Kentucky 2239800.0
453 Shelvin Mack Utah Jazz 8.0 PG 26 3-Jun 203 Butler 2433333.0
454 Raul Neto Utah Jazz 25.0 PG 24 1-Jun 179 NaN 900000.0
455 Tibor Pleiss Utah Jazz 21.0 C 26 3-Jul 256 NaN 2900000.0
456 Jeff Withey Utah Jazz 24.0 C 26 Jul-00 231 Kansas 947276.0
```

457 rows x 9 columns

### Select column Here

```
[66]: column=df["Position"]

[67]: column
```

0	PG
1	SF
2	SG
3	SG
4	PF
...	...
452	PF
453	PG
454	PG
455	C
456	C

Name: Position, Length: 457, dtype: object

Sample output: describe

		Utah Jazz	22399000.0	PF	41.0	Trey Lyles	18-Jun	Kentucky	20
453	473	Utah Jazz	24333333.0	PG	30.0	Shelvin Mack	3-Jun	Baylor	26
454	179	Utah Jazz	9000000.0	PG	25.0	Raul Neto	7-Jun	NaN	24
455	236	Utah Jazz	25000000.0	C	21.0	Tibor Pleiss	3-Jul	NaN	26
456	231	Utah Jazz	9472766.0	C	24.0	Jeff Withey	Jul-00	Kansas	26

457 rows x 10 columns

## Describe

```
[1]: df.describe()
```

	Number	Age	Weight	Salary
count	455.000000	457.000000	457.000000	4.450000e+02
mean	17.669132	26.938731	221.522976	4.852190e+06
std	15.945315	4.494016	26.366343	5.230400e+06
min	0.000000	19.888889	161.000000	0.000000e+00
25%	5.000000	24.000000	205.000000	1.074190e+06
50%	13.000000	26.000000	229.000000	2.641960e+06
75%	25.000000	30.000000	245.000000	6.500000e+06
max	66.000000	40.000000	307.000000	2.500000e+07

## Row index

```
[31]: row=df.iloc[1]
```

```
[31]: row
```

```
[31]: Name      Jae Crowder
      Team      Boston Celtics
      Number      99.0
      Position      SF
      Age      25
      Height      6-Jun
      Weight      235
      College      Marquette
      Salary      6796117.0
      Name: 1, dtype: object
```

## Sorting Values

```
[34]: df.sort_index(axis=1,ascending=False)#Sort the in Descend axis=1 mean columnAscending false mean descene
```

	Weight	Team	Salary	Position	Number	Name	Height	College	Age
0	180	Boston Celtics	7730337.0	PG	0.0	Avery Bradley	2-Jun	Texas	25
1	235	Boston Celtics	6796117.0	SF	99.0	Jae Crowder	6-Jun	Marquette	25
2	205	Boston Celtics	NaN	SG	30.0	John Holland	5-Jun	Boston University	27
3	185	Boston Celtics	1148640.0	SG	28.0	R.J. Hunter	5-Jun	Georgia State	22
4	231	Boston Celtics	5000000.0	PF	8.0	Jonas Jerebko	10-Jun	NaN	29

## Checking The DataType

```
[21]: df.dtypes #Checking The Datatype
```

```
[21]: Name      object
      Team      object
      Number  float64
      Position object
      Age      int64
      Height   object
      Weight   int64
      College   object
      Salary   float64
      dtype: object
```

## Unique Values

```
[59]: df.nunique()#Unique Value
```

```
[59]: Name      457
```

## Checking The DataType

```
[21]: df.dtypes #Checking The Datatype
```

```
[21]: Name      object
      Team      object
      Number  float64
      Position object
      Age      int64
      Height   object
      Weight   int64
      College   object
      Salary   float64
      dtype: object
```

## Unique Values

```
[59]: df.nunique()#Unique Value
```

```
[59]: Name      457
      Team      30
      Number    53
      Position     5
      Age       22
      Height    18
      Weight     87
      College   118
      Salary    300
      dtype: int64
```

## Format Of The Column

```
[50]: df.info()#Format of the column
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 457 entries, 0 to 456
Data columns (total 9 columns):
 #   Column      Non-Null Count  Dtype
---  --
 0   Name        457 non-null    object
 1   Team        457 non-null    object
 2   Number      455 non-null    float64
 3   Position    457 non-null    object
 4   Age         457 non-null    int64
 5   Height      457 non-null    object
 6   Weight      457 non-null    int64
 7   College     373 non-null    object
 8   Salary      445 non-null    float64
dtypes: float64(2), int64(2), object(5)
memory usage: 32.3+ KB
```

```
[51]: df.info()
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 457 entries, 0 to 456
Data columns (total 9 columns):
 #   Column      Non-Null Count  Dtype
---  --
 0   Name        457 non-null    object
 1   Team        457 non-null    object
 2   Number      455 non-null    float64
 3   Position    457 non-null    object
 4   Age         457 non-null    int64
 5   Height      457 non-null    object
 6   Weight      457 non-null    int64
 7   College     373 non-null    object
 8   Salary      445 non-null    float64
dtypes: float64(2), int64(2), object(5)
memory usage: 32.3+ KB
```

```
7   College     373 non-null    object
8   Salary      445 non-null    float64
dtypes: float64(2), int64(2), object(5)
memory usage: 32.3+ KB
```

## Converting Variable DataType

```
[27]: var_change=df["Weight"].df["Weight"].astype("float")
```

```
[45]: var_change
```

```
[45]: 0      180.0
      1      235.0
      2      205.0
      3      185.0
      4      231.0
      ...
      452    234.0
      453    203.0
      454    179.0
      455    256.0
      456    231.0
      Name: Weight, Length: 457, dtype: float64
```

## isNull Fun

#It show missing value

```
[60]: df.isnull().sum()
```

```
[60]: Name      0
      Team      0
      Number    2
      Position  0
      Age       0
      Height    0
      Weight    0
      College   84
      Salary   12
      dtype: int64
```

```
[ ]: nan
```