

# HTML-1 CHEATSHEET

Blank Page → 

```
</DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <title> Title </title>
    <link rel="stylesheet" type="text/css" href="style.css">
  </head>
  <body> <!-- Content --> </body>
</html>
```

Headings → 

```
<h1> Welcome </h1> <!-- title -->
<h2> Subheading </h2>
<h3> Sub Subheading </h3>
<h4> - - </h4>
.
<h6> - - </h6>
```

Paragraph → 

```
<p> Text </p> <!-- Defines a paragraph -->
```

Attributes :- class, id, style, title

Image → 

```

```

Attributes → src, alt, height, width, class, id, usemap, style, loading (lazy, eager)

Links → 

```
<a href="https://abc.com" target="_blank"> Click Click Here </a>
```

Attributes → href, target (-blank, -self, -parent, -top), download, ~~rel~~ rel (nofollow - do not follow link, noopener - prevents access to opener's window object, noreferrer - prevents passing referer info to the linked page), title, type, aria-label (for screen reader), style, class, id

Image Link → 

```
<a href="https://abc.com" target="_blank">
```

```
  
</a>
```



Bookmarks → `<h2 id = "A"> A </h2>`

`<a href = "#A"> Jump </a>`

Bookmark on another page

`<a href = "abc.html #A"> Jump </a>`

Bold Text → `<strong> Bold </strong>`

Italic Text → `<em> Italic </em>`

Abbreviation → `<abbr title = "Hypertext Markup Language"> HTML </abbr>`

Horizontal Line → `<hr />`

Line Break → `<br />`

List → Unordered List → `<ul>`  
`<li> A </li>`  
`<li> B </li>`  
`</ul>`

ul attributes → type (square, circle, disc → default), class, id, style, ~~start~~

Ordered List → `<ol>`  
`<li> A </li>`  
`<li> B </li>`  
`</ol>`

ol attributes → type (1, A, a, I, i), start, reversed, class, id, style

Definition List → `<dl>`  
`<dt> HTML </dt>`  
`<dd> Hypertext Markup Language </dd>`  
`</dl>`

Table → `<table>`  
`<tr>`  
`<th> Name </th>`  
`<th> Age </th>`  
`</tr>`



```

<tr>
  <td> Dev </td>
  <td> 20 </td>
</tr>
<tr>
  <td> Ansh </td>
  <td> 25 </td>
</tr>
</table>

```

table attributes → border, cellpadding, cellspacing, width, align, bgcolor, summary (screen reader), border-collapse (collapse, separate)

tr attributes → id, rowspan

td attributes → id, colspan

Form → `<form action = "action.php" method = "get">`  
`</form>`

attributes → action, method (get, post), autocomplete (on, off), novalidate

Inputs → `<input type = "text" name = "text">`

types → button, checkbox, color, date, email, file, hidden, image, month, number, password, radio, range, reset, submit, tel, text, time, url, week, datetime-local

attributes → value, readonly, disabled, size, minlength, min, max, multiple, pattern, placeholder, required, step, autofocus, height, width, list

Input list → `<form>`  
`<input list = "browsers">`  
`<datalist id = "browsers">`  
`<option value = "Edge">`  
`<option value = "Google">`  
`</datalist>`  
`</form>`



Select → `<label for = "cars" > Choose a car: </label >`  
`<select id = "cars" name = "cars" >`  
`<option value = "volvo" > Volvo </option >`  
`<option value = "Audi" > Audi </option >`  
`</select >`

select attributes → size, multiple, id, name