

Introduction to Sorting

Analysis of Algorithm



Faculty of Computing and Information Technology (FCIT)
University of the Punjab, Lahore, Pakistan.

Credit

These notes contain material from Chapter 2, **Design and Analysis of Algorithms** by Cormen, Leiserson, Rivest, and Stein (3rd Edition).

Sorting Problem

Input: A sequence of n numbers $\langle a_1, a_2, \dots, a_n \rangle$.

Output: A permutation (reordering) $\langle a'_1, a'_2, \dots, a'_n \rangle$ of the input sequence such that $a'_1 \leq a'_2 \leq \dots \leq a'_n$.

Insertion Sort (Concept)










Figure 2.1 Sorting a hand of cards using insertion sort.

Insertion Sort (Algorithm)

INSERTION-SORT(A)

```
1  for  $j = 2$  to  $A.length$ 
2       $key = A[j]$ 
3      // Insert  $A[j]$  into the sorted sequence  $A[1..j-1]$ .
4       $i = j - 1$ 
5      while  $i > 0$  and  $A[i] > key$ 
6           $A[i + 1] = A[i]$ 
7           $i = i - 1$ 
8       $A[i + 1] = key$ 
```



Analysing Algorithm

- Analysing algorithm means predicting resources the algorithm requires, for example:
 - memory, communication bandwidth, CPU cycles etc
- **RAM (random-access machine) model:** generic one process model which assumes instructions execute one after another
 - The RAM model contains instructions commonly found in real computers: arithmetic, data movement (load, store, copy), and control (conditional and unconditional branch, subroutine call and return).
 - Each such instruction takes a constant amount of time.

Insertion Sort (Analysis)

INSERTION-SORT(A)

```
1  for  $j = 2$  to  $A.length$ 
2       $key = A[j]$ 
3      // Insert  $A[j]$  into the sorted
        sequence  $A[1 \dots j - 1]$ .
4       $i = j - 1$ 
5      while  $i > 0$  and  $A[i] > key$ 
6           $A[i + 1] = A[i]$ 
7           $i = i - 1$ 
8       $A[i + 1] = key$ 
```

Insertion Sort (Analysis)

INSERTION-SORT(<i>A</i>)	<i>cost</i>	<i>times</i>
1 for <i>j</i> = 2 to <i>A.length</i>	c_1	n
2 $key = A[j]$	c_2	$n - 1$
3 // Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4 $i = j - 1$	c_4	$n - 1$
5 while $i > 0$ and $A[i] > key$	c_5	$\sum_{j=2}^n t_j$
6 $A[i + 1] = A[i]$	c_6	$\sum_{j=2}^n (t_j - 1)$
7 $i = i - 1$	c_7	$\sum_{j=2}^n (t_j - 1)$
8 $A[i + 1] = key$	c_8	$n - 1$

Running Time?

$$\begin{aligned} T(n) = & c_1 n + c_2(n - 1) + c_4(n - 1) + c_5 \sum_{j=2}^n t_j + c_6 \sum_{j=2}^n (t_j - 1) \\ & + c_7 \sum_{j=2}^n (t_j - 1) + c_8(n - 1) . \end{aligned}$$

Insertion Sort (Analysis Cont.)

- What are the **best** and **worst-case** running times of INSERTION-SORT?
- Lets try to solve $T(n)$ for best case and worst case.

Insertion Sort (Analysis Cont.)

Insertion Sort Best Case Running Time

$$\begin{aligned}T(n) &= c_1n + c_2(n-1) + c_4(n-1) + c_5(n-1) + c_8(n-1) \\&= (c_1 + c_2 + c_4 + c_5 + c_8)n - (c_2 + c_4 + c_5 + c_8) .\end{aligned}$$

Insertion Sort Worst Case Running Time

$$\begin{aligned}T(n) &= c_1n + c_2(n-1) + c_4(n-1) + c_5 \left(\frac{n(n+1)}{2} - 1 \right) \\&\quad + c_6 \left(\frac{n(n-1)}{2} \right) + c_7 \left(\frac{n(n-1)}{2} \right) + c_8(n-1) \\&= \left(\frac{c_5}{2} + \frac{c_6}{2} + \frac{c_7}{2} \right) n^2 + \left(c_1 + c_2 + c_4 + \frac{c_5}{2} - \frac{c_6}{2} - \frac{c_7}{2} + c_8 \right) n \\&\quad - (c_2 + c_4 + c_5 + c_8) .\end{aligned}$$