

# 6 Subqueries

# Objectives

**After completing this lesson, you should be able to do the following:**

- **Describe the types of problem that subqueries can solve**
- **Define subqueries**
- **List the types of subqueries**
- **Write single-row and multiple-row subqueries**

# Using a Subquery to Solve a Problem

**Who has a salary greater than Abel's?**

**Main Query:**



**Which employees have salaries greater than Abel's salary?**

**Subquery**



**What is Abel's salary?**



# Subquery Syntax


```
SELECT    select_list  
FROM      table  
WHERE     expr operator
```

```
(SELECT      select_list  
FROM         table);
```

- The subquery (inner query) executes once before the main query.
- The result of the subquery is used by the main query (outer query).

# Using a Subquery

```
SELECT last_name
FROM   employees
WHERE  salary >
      (SELECT salary
       FROM   employees
       WHERE  last_name = 'Abel');
```



LAST_NAME
King
Kochhar
De Haan
Hartstein
Higgins

# Guidelines for Using Subqueries

- **Enclose subqueries in parentheses.**
- **Place subqueries on the right side of the comparison condition.**
- **The ORDER BY clause in the subquery is not needed unless you are performing Top-N analysis.**
- **Use single-row operators with single-row subqueries and use multiple-row operators with multiple-row subqueries.**

# Types of Subqueries

- **Single-row subquery**



- **Multiple-row subquery**





# Single-Row Subqueries

- Return only one row
- Use single-row comparison operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to




# Executing Single-Row Subqueries

```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id = 
              (SELECT job_id
               FROM employees
               WHERE employee_id = 141)
AND salary > 
              (SELECT salary
               FROM employees
               WHERE employee_id = 143);
```

LAST_NAME	JOB_ID	SALARY
Rajs	ST_CLERK	3500
Davies	ST_CLERK	3100


# Using Group Functions in a Subquery

```
SELECT last_name, job_id, salary
FROM   employees
WHERE  salary = 
          (SELECT MIN(salary)
           FROM   employees);
```

LAST_NAME	JOB_ID	SALARY
Vargas	ST_CLERK	2500

# The HAVING Clause with Subqueries

- The Oracle server executes subqueries first.
- The Oracle server returns results into the HAVING clause of the main query.

```
SELECT    department_id, MIN(salary)
FROM      employees
GROUP BY  department_id
HAVING    MIN(salary) > 
           (SELECT MIN(salary)
            FROM      employees
            WHERE      department_id = 50);
```

# What is Wrong with this Statement?

```
SELECT employee_id, last_name
FROM   employees
WHERE  salary =
      (SELECT   MIN(salary)
       FROM     employees
       GROUP BY department_id);
```

```
ERROR at line 4:
ORA-01427: single-row subquery returns more than
one row
```

**Single-row operator with multiple-row subquery**

# Will this Statement Return Rows?

```
SELECT last_name, job_id
FROM   employees
WHERE  job_id =
      (SELECT job_id
       FROM   employees
       WHERE  last_name = 'Haas');
```

no rows selected

**Subquery returns no values**

# Multiple-Row Subqueries

- Return more than one row
- Use multiple-row comparison operators

Operator	Meaning
IN	Equal to any member in the list
ANY	Compare value to each value returned by the subquery
ALL	Compare value to every value returned by the subquery

# Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary < ANY
      (SELECT salary
       FROM   employees
       WHERE  job_id = 'IT_PROG')
AND    job_id <> 'IT_PROG';
```

9000, 6000, 4200


EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
124	Mourgos	ST_MAN	5800
141	Rajs	ST_CLERK	3500
142	Davies	ST_CLERK	3100
143	Matos	ST_CLERK	2600
144	Vargas	ST_CLERK	2500

10 rows selected.

# Using the ALL Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary < ALL
      (SELECT salary
       FROM   employees
       WHERE  job_id = 'IT_PROG')
AND    job_id <> 'IT_PROG';
```

9000, 6000, 4200



EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
141	Rajs	ST_CLERK	3500
142	Davies	ST_CLERK	3100
143	Matos	ST_CLERK	2600
144	Vargas	ST_CLERK	2500



# Null Values in a Subquery

```
SELECT emp.last_name  
FROM   employees emp  
WHERE  emp.employee_id NOT IN  
                                (SELECT mgr.manager_id  
                                FROM   employees mgr);
```

no rows selected

# Summary

In this lesson, you should have learned how to:

- Identify when a subquery can help solve a question
- Write subqueries when a query is based on unknown values

```
SELECT    select_list
FROM      table
WHERE     expr operator
          (SELECT select_list
           FROM    table);
```

# Practice 6 Overview

**This practice covers the following topics:**

- **Creating subqueries to query values based on unknown criteria**
- **Using subqueries to find out which values exist in one set of data and not in another**