


For more information about this product, visit our website at:  
[www.potentiometers.com](http://www.potentiometers.com)



*Series RV5 potentiometers provide a low profile with lateral lug terminals.*

## Features

- Hot molded carbon element
- One piece housing and bushing
- Stainless steel shaft
- Meets or exceeds specifications of MIL-R-94
- QPL Listed
- Commercial equivalent, see [Series T](#)

### Options:

- Special tapers
- Custom shafts
- Customer specified marking

## Electrical Specifications

Resistance Range-linear taper: 100 ohms to 5 meg  
Resistance Range-log taper: 150 ohms to 1 meg  
Resistance Tolerance:  $\pm 10\%$  or  $\pm 20\%$   
Resistance Taper: linear, log, reverse log  
(other tapers by special order)  
Power Rating: .5 watts @ 70 °C derated to 0 watts @ 120 °C  
Insulation Resistance: 10K Meg (dry); 100K Meg (wet)  
Dielectric Strength: 750 V RMS at sea level  
Operating Voltage: 350 V subject to power rating



## Mechanical Specifications

Mechanical Rotation: 300°  
Operating Torque: 1 oz/in to 6 oz/in  
Rotational Life: 25,000 cycles



## Environmental Specifications

Operating Temperature: -65 °C to +125 °C  
Resistance to Soldering Heat: 350 °C to 5 seconds  
Humidity Range: per Mil-R-94  
Vibration Range: per Mil-R-94  
Shock Resistance: per Mil-R-94  
Load Life: 1000 hr at 70 °C


## Standard Configuration



## Locking Bushing




## Flatted Shaft



Note:  
Flatted Shaft is not available if  
Locking Option is selected.

# MIL Style RV5 - 1/2 Watt Carbon Potentiometer

## Panel Mounting Holes



Mounting dimensions for standard potentiometer

## Ordering Information - Commercial Part Numbers

### Carbon element standard.

Conductive Plastic available in some configurations. Contact sales rep for information.

Series	Bushing	Bushing Length:	Taper	Resistance Value:	Tolerance:	Shaft Style:	Shaft Length:
<b>T</b> = Series T	<b>blank</b> = Std. <b>L</b> = Locking	<b>blank</b> = 1/4"	<b>U</b> = Linear <b>A</b> = Log <b>B</b> = Rev. Log	<b>Total Resistance Value in Ohms:</b> First 2 numbers are significant digits, 3rd number is the number of zeros.	<b>1</b> = 10% of Nominal <b>2</b> = 20% of Nominal	<b>R</b> = Round <b>S</b> = Slotted <b>F</b> = Flatted	<b>16</b> = 1/2" <b>20</b> = 5/8" <b>24</b> = 3/4" <b>28</b> = 7/8"

**Example Part Number: TU5021S28**

Note: not all part number combinations are valid.

## Ordering Information - Military Part Numbers

### Carbon or Conductive Plastic element available

Style	Bushing	Switch	Temperature and Moisture Characteristics:	Shaft Style:	Shaft Length:	Resistance Value:	Taper and Tolerance:
<b>RV5</b> = MIL style RV5	<b>N</b> = Standard <b>L</b> = Locking	<b>A</b> = Without Switch	<b>Y</b> = as per MIL-R-94	<b>S</b> = Slotted	<b>L</b> = 3/8" <b>B</b> = 1/2" <b>A</b> = 5/8" <b>D</b> = 7/8"	<b>Total Resistance Value in Ohms:</b> First 2 numbers are significant digits, 3rd number is the number of zeros.	<b>A</b> = Linear ±10% <b>B</b> = Linear ±20% <b>C</b> = Log ±10% <b>D</b> = Log ±20% <b>E</b> = Rev. Log ±10% <b>F</b> = Rev. Log ±20%

**Example Part Number: RV5NAYS103A**

Note: not all part number combinations are valid.

More options and combinations are available on commercial versions

For more information about this product, visit our website at: [www.potentiometers.com](http://www.potentiometers.com)



© State Electronics

36 State Route 10, STE 6 • East Hanover, NJ 07936-0436  
973-887-2550 • Toll Free 1-800-631-8083 • Fax 973-887-1940  
<http://www.potentiometers.com>