

HTML Important Tags

Slide Notes with Easy Explanation and Code Examples

What you will learn

Basic page structure, headings, text, links, images, lists, tables, forms, semantic layout, audio/video, and one complete HTML page example.

1. Basic HTML Structure

Notes

- Every HTML page starts with a standard structure.
- <head> contains page information like title and CSS links.
- <body> contains the content visible on the website.

Code Sample

```
<!DOCTYPE html>
<html>
<head>
  <title>My First Website</title>
</head>
<body>
  <h1>Hello World</h1>
  <p>This is my first HTML page.</p>
</body>
</html>
```

2. Heading Tags

Notes

- Headings are used for titles and sections.
- `<h1>` is the biggest and most important heading.
- `<h6>` is the smallest heading.

Code Sample

```
<h1>Main Heading</h1>  
<h2>Sub Heading</h2>  
<h3>Small Heading</h3>  
<h4>Heading 4</h4>  
<h5>Heading 5</h5>  
<h6>Smallest Heading</h6>
```

3. Paragraph, Line Break, and Horizontal Line

Notes

- <p> is used for normal text.
-
 moves text to the next line.
- <hr> creates a horizontal line between sections.

Code Sample

```
<p>This is a paragraph.</p>  
<p>Hello <br> World</p>  
<hr>  
<p>This text comes after a line.</p>
```

4. Link Tag

Notes

- The <a> tag is used to create links.
- href stores the destination URL.
- target="_blank" opens the link in a new tab.

Code Sample

```
<a href="https://www.google.com">Go to Google</a>

<a href="about.html">Go to About Page</a>

<a href="https://www.google.com" target="_blank">
  Open Google in New Tab
</a>
```

5. Image Tag

Notes

- The tag displays images.
- src is the image path.
- alt is alternative text shown if image does not load.

Code Sample

```
  

```

6. Button Tag

Notes

- The <button> tag creates a clickable button.
- Buttons can submit forms or run JavaScript actions.
- Use clear button text like Submit, Login, or Send Message.

Code Sample

```
<button>Click Me</button>

<button onclick="alert('Hello!')">
  Click Here
</button>
```

7. List Tags

Notes

- creates a bullet list.
- creates a numbered list.
- creates each list item.

Code Sample

```
<ul>
  <li>HTML</li>
  <li>CSS</li>
  <li>JavaScript</li>
</ul>

<ol>
  <li>Open file</li>
  <li>Write code</li>
  <li>Run page</li>
</ol>
```


8. Text Formatting Tags

Notes

- Use formatting tags to highlight or style important text.
- `<b>` makes text bold; `<strong>` means important text.
- `<i>` makes italic; `<mark>` highlights text.

Code Sample

```
<p>My name is <b>Ali</b>.</p>
<p>This is <strong>important</strong> text.</p>
<p>This is <i>italic</i> text.</p>
<p>I am learning <mark>HTML</mark>.</p>
<p>This is <u>underlined</u> text.</p>
```

9. Div and Span Tags

Notes

- <div> is a block-level container used for sections or layout.
- is an inline container used for styling small text parts.
- Both are commonly used with CSS.

Code Sample

```
<div style="background-color: lightblue; padding: 20px;">
  <h2>Welcome</h2>
  <p>This is a box created using div.</p>
</div>

<p>My favorite color is <span style="color: red;">red</span>.</p>
```

10. Table Tags

Notes

- Tables show data in rows and columns.
- `<tr>` creates a row.
- `<th>` creates a heading cell; `<td>` creates a normal cell.

Code Sample

```
<table border="1">
  <tr>
    <th>Name</th>
    <th>Age</th>
    <th>City</th>
  </tr>
  <tr>
    <td>Ali</td>
    <td>20</td>
    <td>Lahore</td>
  </tr>
</table>
```

11. Form Tags

Notes

- Forms collect user data.
- `<label>` explains the input field.
- `<input>` takes user input like name, email, password, number, or date.

Code Sample

```
<form>
  <label>Name:</label>
  <input type="text" placeholder="Enter your name">

  <label>Email:</label>
  <input type="email" placeholder="Enter your email">

  <label>Password:</label>
  <input type="password" placeholder="Enter password">

  <button type="submit">Submit</button>
</form>
```

12. Common Input Types

Notes

- Input type controls what data the user can enter.
- text for names, email for emails, password for hidden password text.
- checkbox allows multiple selections; radio usually allows one selection.

Code Sample

```
<input type="text">
<input type="email">
<input type="password">
<input type="number">
<input type="date">
<input type="file">
<input type="checkbox">
<input type="radio">
<input type="submit" value="Register">
```

13. Select and Textarea

Notes

- `<select>` creates a dropdown menu.
- `<option>` creates dropdown choices.
- `<textarea>` is used for long text like comments or messages.

Code Sample

```
<label>Select City:</label>
<select>
  <option>Lahore</option>
  <option>Karachi</option>
  <option>Islamabad</option>
</select>

<label>Message:</label>
<textarea rows="5" cols="30" placeholder="Write your message"></textarea>
```

14. Semantic HTML Tags

Notes

- Semantic tags make the page structure clear.
- <header> is the top area; <nav> contains navigation links.
- <section> groups content; <footer> is the bottom area.

Code Sample

```
<header>
  <h1>My Website</h1>
</header>

<nav>
  <a href="#">Home</a>
  <a href="#">About</a>
  <a href="#">Contact</a>
</nav>

<section>
  <h2>About Us</h2>
  <p>This is the about section.</p>
</section>

<footer>
  <p>Copyright 2026</p>
</footer>
```

15. Audio and Video Tags

Notes

- <audio> adds audio to a web page.
- <video> adds video to a web page.
- controls shows play, pause, volume, and timeline controls.

Code Sample

```
<audio controls>
  <source src="music.mp3" type="audio/mpeg">
</audio>

<video width="400" controls>
  <source src="video.mp4" type="video/mp4">
</video>
```


16. Complete HTML Page Example - Part 1

Notes

- This example combines structure, navigation, section, paragraph, image, and list tags.
- You can copy this into an index.html file and open it in a browser.

Code Sample

```
<!DOCTYPE html>
<html>
<head>
  <title>Student Profile Page</title>
</head>
<body>
  <header>
    <h1>Welcome to My Profile</h1>
    <p>This is my personal HTML page.</p>
  </header>

  <nav>
    <a href="#">Home</a> |
    <a href="#">About</a> |
    <a href="#">Contact</a>
  </nav>

  <section>
    <h2>About Me</h2>
    <p>My name is <b>Ali</b>. I am learning <mark>HTML</mark>.</p>
    
  </section>
```

17. Complete HTML Page Example - Part 2

Notes

- This part adds skills, a table, and a contact form.
- It shows how multiple HTML tags work together in one page.

Code Sample

```
<section>
  <h2>My Skills</h2>
  <ul>
    <li>HTML</li>
    <li>CSS</li>
    <li>JavaScript</li>
  </ul>
</section>

<section>
  <h2>Education</h2>
  <table border="1">
    <tr><th>Degree</th><th>Institute</th><th>Year</th></tr>
    <tr><td>BS Computer Science</td><td>UAF</td><td>2026</td></tr>
  </table>
</section>

<section>
  <h2>Contact Me</h2>
  <form>
    <input type="text" placeholder="Enter your name">
    <input type="email" placeholder="Enter your email">
    <textarea placeholder="Write your message"></textarea>
    <button type="submit">Send Message</button>
  </form>
</section>
</body>
</html>
```

18. Quick Revision Table

Tag	Use
<html>	Main HTML document
<head>	Page information
<title>	Browser tab title
<body>	Visible page content
<h1> to <h6>	Headings
<p>	Paragraph
<a>	Link
	Image
<button>	Button
, ,	Lists
<div>, 	Containers
<table>, <tr>, <th>, <td>	Tables
<form>, <input>, <label>	Forms
<select>, <option>, <textarea>	Dropdown and long text
<header>, <nav>, <section>, <footer>	Semantic layout
<audio>, <video>	Media