

Unit 2 - Week 1

Course outline

How to access the portal

Week 1

- ☐ Lecture 1: Introduction to Visual Computing
- ☐ Lecture 2: Feature Extraction for Visual Computing
- ☐ Lecture 3: Lab: Feature Extraction with Python
- ☐ Lecture 4: Neural Networks for Visual Computing
- ☐ Lecture 5: Lab: Classification with Perceptron Model
- ☐ Feedback for Week 1
- ☐ Week 1: Lecture Slides
- ☐ Quiz : Assignment 1
- ☐ Week 1: Assignment Solutions

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 1

The due date for submitting this assignment has passed.

Due on 2018-02-05, 23:59 IST.

Assignment submitted on 2018-02-02, 22:56 IST

1) What are the commonly used software tools for visual computing?

- ☒ Pytorch
- ☐ Convolutional neural networks
- ☐ Machine learning
- ☐ Computer Vision

Yes, the answer is correct.

Score: 1

Accepted Answers:

Pytorch

1 point

2) What is the major feature for employing GPUs in machine vision?

- ☐ Better accuracy
- ☐ Less cost
- ☐ Faster convergence
- ☒ Parallel computing

Yes, the answer is correct.

Score: 1

Accepted Answers:

Parallel computing

1 point

3) What is the market for machine vision for 2020?

- ☐ 6 Billion
- ☐ 3.5 Billion
- ☐ 6.5 Billion
- ☒ 9.5 Billion

Yes, the answer is correct.

Score: 1

Accepted Answers:

9.5 Billion

1 point

4) Which of the following is a statistical texture metric?

- ☒ Local Binary Patterns
- ☐ Orientation Histogram
- ☐ Wavelets
- ☐ Fourier Coefficients

No, the answer is incorrect.

Score: 0

Accepted Answers:

Orientation Histogram

1 point

5) The size of the Co-occurrence matrix depends on

- ☐ None of these
- ☐ Image contrast
- ☐ Image entropy
- ☒ Gray levels in image

Yes, the answer is correct.

Score: 1

Accepted Answers:

Gray levels in image

1 point

6) Which of the factors govern high frequency attributes of Gabor wavelet?

1 point

- ☐ Centroid of receptive field
- ☐ Spatial frequency
- ☒ All of these
- ☐ Standard deviation of Gaussian

No, the answer is incorrect.

Score: 0

Accepted Answers:

Spatial frequency

7) What is the output of sigmoid function for an input with dynamic range $[0, \infty]$?

1 point

- ☒ $[0.5, 1]$
- ☐ $[-1, 1]$
- ☐ $[0, 1]$
- ☐ $[0.25, 1]$

Yes, the answer is correct.

Score: 1

Accepted Answers:

$[0.5, 1]$

8) Assume a neural network with 100 input neurons, 50 hidden neurons and 2 output neurons. How many parameters are to be learned?

1 point

- ☐ 5100
- ☐ 50
- ☒ 5152
- ☐ 10000

No, the answer is incorrect.

Score: 0

Accepted Answers:

5100

9) Which of the following function is used for classification?

1 point

- ☐ Mean square error
- ☐ Negative log likelihood
- ☒ Absolute loss
- ☐ KL Divergence

No, the answer is incorrect.

Score: 0

Accepted Answers:

Negative log likelihood

10) What is the local binary pattern of

1 point

9 3 2

5 4 1

2 7 8

- ☒ 00011011
- ☐ 00110110
- ☐ 10001101
- ☐ 11001101

Yes, the answer is correct.

Score: 1

Accepted Answers:

00011011

Previous Page

End

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 3 - Week 2

Course outline

How to access the portal

Week 1

Week 2

- ☐ Lecture 6 : Introduction to Deep Learning with Neural Networks
- ☐ Lecture 7 : Introduction to Deep Learning with Neural Networks
- ☐ Lecture 8 : Multilayer Perceptron and Deep Neural Networks
- ☐ Lecture 9 : Multilayer Perceptron and Deep Neural Networks
- ☐ Lecture 10 : Classification with Multilayer Perceptron
- ☐ Feedback for Week 2
- ☐ Week 2: Lecture Slides
- ☐ Quiz : Assignment 2
- ☐ Week 2: Assignment Solutions

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD

Assignment 2

The due date for submitting this assignment has passed.

Due on 2018-02-07, 23:59 IST.

Assignment submitted on 2018-02-05, 00:35 IST

1) Which of the following algorithms are said to be learning?

1 point

- ☐ Identifying hyper-plane to separate features representing different classes
- ☐ Identifying objects for computer vision task
- ☒ Increase of performance with experience
- ☐ Heuristically constructing intelligent feature descriptors

Yes, the answer is correct.

Score: 1

Accepted Answers:

Increase of performance with experience

2) Which of the following is dependent on other tasks?

1 point

- ☐ Salient segments
- ☐ Part detection
- ☒ Scene description
- ☐ Human detection

Yes, the answer is correct.

Score: 1

Accepted Answers:

Scene description

3) Multi layer perceptron architectures are expected to

1 point

- ☒ Construct Feature descriptors
- ☐ Not fall into local minima
- ☐ Reduce loss
- ☐ All of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Construct Feature descriptors

4) Deep learning established state-of-the-art performance in the field of

1 point

- ☐ Autonomous driving
- ☐ Natural language processing
- ☐ Medical imaging
- ☒ All of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

All of the above

5) In a MLP (multi layer perceptron) with sigmoid function which layers exhibit vanishing gradient property

1 point

- ☐ Intermediate layers
- ☐ Non-differentiable loss block
- ☒ Layers near loss block
- ☐ Initial layers

No, the answer is incorrect.

Score: 0

Accepted Answers:

Initial layers

6) Given an image classification task which of the following approaches is commonly employed **1 point**

- ☐ Long Short Term Memory
- ☐ HOG + Support vector machines
- ☐ Texture features + Random forests
- ☒ Convolutional neural network with logistic regression

Yes, the answer is correct.

Score: 1

Accepted Answers:

Convolutional neural network with logistic regression

7) Consider a perceptron with weights as [2, 3, 4] and bias as 9. What is the output provided [1, 2, 3] as input? **1 point**

- ☐ 2.22
- ☐ 180
- ☐ 20
- ☒ 29

Yes, the answer is correct.

Score: 1

Accepted Answers:

29

8) Which of the following function is used for classification? **1 point**

- ☒ Negative log likelihood
- ☐ Mean square error
- ☐ Absolute loss
- ☐ KL Divergence

Yes, the answer is correct.

Score: 1

Accepted Answers:

Negative log likelihood

9) Assume a neural network with 100 input neurons, 50 hidden neurons and 2 output neurons. How many parameters are to be learned? **0 points**

- ☐ 10000
- ☐ 50
- ☒ 5152
- ☐ 5100

Yes, the answer is correct.

Score: 0

Accepted Answers:

5152

10) Which of the following is considered for correcting a weight during back propagation? **1 point**

- ☐ Gradient of error
- ☒ Negative gradient of error w.r.t weight
- ☐ Positive gradient of weight
- ☐ Negative gradient of weight

Yes, the answer is correct.

Score: 1

Accepted Answers:

Negative gradient of error w.r.t weight

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Funded by

Government of India
Ministry of Human Resource Development

Google[™]

Unit 4 - Week 3

Course outline

How to access the portal

Week 1

Week 2

Week 3

☐ Lecture 11 : Autoencoder for Representation Learning and MLP Initialization

☐ Lecture 12 : MNIST handwritten digits classification using autoencoders

☐ Lecture 13 : Fashion MNIST classification using autoencoders

☐ Lecture 14 : ALL-IDB Classification using autoencoders

☐ Lecture 15 : Retinal Vessel Detection using autoencoders

☐ Week 3: Lecture Slides

☐ Quiz : Assignment 3

☐ Week 3: Assignment Solutions

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 3

The due date for submitting this assignment has passed.

Due on 2018-02-14, 23:59 IST.

Assignment submitted on 2018-02-14, 23:49 IST

1) Which of the following models can be employed for unsupervised learning

1 point

☐

Autoencoder

☐

Deep Belief Networks

☒

None

☐

Both

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both

2) Which of the following statements are true for a autoencoder (neglect bias):

1 point

(i) Number of input perceptrons are equal to number of output perceptrons

(ii) It needs supervised labels

(iii) It is a regression algorithm

☐

(i) and (ii)

☐

(ii) and (iii)

☐

(i), (ii) and (iii)

☒

(i) and (iii)

Yes, the answer is correct.

Score: 1

Accepted Answers:

(i) and (iii)

3) What is the dimension of encoder weight matrix of an autoencoder (hidden units=400) constructed to handle 10 dimensional input samples

1 point

☒

rows = 400 and columns = 11

☐

rows = 400 and columns = 10

☐

rows = 11 and columns = 400

☐

rows = 10 and columns = 401

Yes, the answer is correct.

Score: 1

Accepted Answers:

rows = 400 and columns = 11

4) What is the dimension of decoder weight matrix of an autoencoder (hidden units=400) constructed to handle 10 dimensional input samples

1 point

☐

rows = 11 and columns = 400

☒

rows = 10 and columns = 401

☐

rows = 400 and columns = 11

☐

rows = 400 and columns = 10

Yes, the answer is correct.

Score: 1

Accepted Answers:

rows = 10 and columns = 401

5) Which of the following cases is best suited for training SAE and transferring those weights to initialize deep neural network for classification **1 point**

- ☐ Ample unlabelled data and limited labelled data
- ☐ Big data and GPU
- ☒ Ample labelled data
- ☐ Any of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Ample unlabelled data and limited labelled data

6) Which of the following statement is true for a trained SAE ($n=3$) with E1, E2 and E3 being autoencoders **1 point**

- ☐ None
- ☒ E3 is hierarchically more representative
- ☐ E1 is hierarchically more representative
- ☐ Number of E3 weights should be greater than E1

Yes, the answer is correct.

Score: 1

Accepted Answers:

E3 is hierarchically more representative

7) What should $E_n(n^{th})$ block represent for an ideal SAE trained on face dataset **1 point**

- ☐ Edges
- ☐ Eigen face
- ☒ Curves
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Eigen face

8) While exporting DNN as feature extractor for patch classification what should be the last block? **1 point**

- ☐ Logistic regression
- ☒ Random forest
- ☐ Support vector machine
- ☐ Any of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Any of the above

9) What should E_1 (1^{st} encoder block) represent for an ideal SAE (stacked autoencoder) trained on MRI dataset **1 point**

- ☐ Corners
- ☒ Organs
- ☐ Edges
- ☐ Pathology

No, the answer is incorrect.

Score: 0

Accepted Answers:

Edges

10) Which loss function is used while training autoencoder **1 point**

- ☐ Logistic regression
- ☐ Hinge loss
- ☒ Any regression loss
- ☐ Any classification loss

Yes, the answer is correct.

Score: 1

Accepted Answers:

Any regression loss

[Previous Page](#)

[End](#)

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Funded by

Government of India
Ministry of Human Resource Development

Google[™]

Unit 5 - Week 4

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

- ☐ Lecture 16: Stacked Autoencoders
- ☐ Lecture 17: MNIST and Fashion MNIST with Stacked Autoencoders
- ☐ Lecture 18: Denoising and Sparse Autoencoders
- ☐ Lecture 19: Sparse Autoencoders for MNIST classification
- ☐ Lecture 20: Denoising Autoencoders for MNIST classification
- ☐ Feedback for Week 4
- ☐ Week 4: Lecture Slides
- ☐ Quiz : Assignment 4
- ☐ Week 4: Assignment Solutions

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 4

The due date for submitting this assignment has passed.

Due on 2018-02-21, 23:59 IST.

Assignment submitted on 2018-02-21, 17:55 IST

1) Given that E_n and D_n are encoder and decoder blocks of n^{th} autoencoder in SAE (Stacked autoencoder). **1 point**
 What is the sequence of blocks during end-to-end training of SAE (with $n = 2$)

☐ $Input \rightarrow E_1 \rightarrow D_1 \rightarrow E_2 \rightarrow D_2 \rightarrow Input$ ☐ $Input \rightarrow E_1 \rightarrow E_2 \rightarrow D_1 \rightarrow D_2 \rightarrow Input$ ☒ $Input \rightarrow E_1 \rightarrow E_2 \rightarrow D_2 \rightarrow D_1 \rightarrow Input$ ☐ Any of the above**Yes, the answer is correct.****Score: 1****Accepted Answers:** $Input \rightarrow E_1 \rightarrow E_2 \rightarrow D_2 \rightarrow D_1 \rightarrow Input$

2) Given a trained SAE ($n = 2$), how should the blocks be arranged for weight refinement (classification task) **1 point**

☐ $Input \rightarrow E_1 \rightarrow E_2 \rightarrow D_1 \rightarrow D_2 \rightarrow \text{Logistic regression}$ ☒ $Input \rightarrow E_1 \rightarrow E_2 \rightarrow \text{Logistic regression}$ ☐ $Input \rightarrow E_1 \rightarrow E_2 \rightarrow D_1 \rightarrow D_2 \rightarrow \text{Logistic regression}$ ☐ Any of the above**Yes, the answer is correct.****Score: 1****Accepted Answers:** $Input \rightarrow E_1 \rightarrow E_2 \rightarrow \text{Logistic regression}$

3) Given input x and linear autoencoder (no bias) with random weights (W for encoder and W' for decoder), **1 point**
 what mathematical form is minimized to achieve optimal weights

☐ $|x - (W' \cdot W \cdot x)|$ ☐ $|x - (W' \cdot N_{\beta}(W \cdot x))|$ ☒ $|x - N_{\beta}(W' \cdot N_{\beta}(W \cdot x))|$ ☐ None of the above**No, the answer is incorrect.****Score: 0****Accepted Answers:** $|x - (W' \cdot W \cdot x)|$

4) Given an linear autoencoder which encodes input x to z . For learning hierarchically high-level representation what should be the learning arrangement of second linear autoencoder (with weights W_2 and W'_2) **1 point**

- ☐ $|x - (W_2' \cdot W_2 \cdot x)|$
- ☐ $|z - (W_2' \cdot W_2 \cdot z)|$
- ☐ $|z - (W_2 \cdot W_1 \cdot x)|$
- ☒ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

$$|z - (W_2' \cdot W_2 \cdot z)|$$

5) In a de-noising autoencoder, noise is added to input for

1 point

- ☐ Avoiding overfitting
- ☒ Robust feature extraction
- ☐ Data augmentation
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

All of the above

6) In a linear autoencoder (without regularizer), if hidden layer perceptrons are equal to input layer perceptron then encoder and decoder weights are indulged to learn

1 point

- ☐ Optimal representations
- ☒ Identity matrix
- ☐ Sparse representations
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Identity matrix

7) The role of regularizer in cost function is to

1 point

- ☐ Avoid overfitting
- ☐ Induce sparsity
- ☐ Simpler hypothesis
- ☒ All of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

All of the above

8) Given feature vector X and corresponding label (y), logistic regression relates X and y in the form of (B is parameters to be learned)

1 point

- ☒ $\log\left(\frac{y}{1-y}\right) = BX$
- ☐ $y = BX$
- ☐ $y = \frac{1}{1+e^{BX}}$
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

$$\log\left(\frac{y}{1-y}\right) = BX$$

9) Given feature vector X (with dimension j), corresponding label y (binary class) and weights (b_1, b_2, \dots, b_k) of logistic regressor, z be output (expected) of logistic regressor. What is the loss function (L) and gradient computed to correct the b_k based on chain rule

1 point

- ☐

$y \log(z)$ and $(y - z)x_k$

☐

$y - \log(z)$ and $\frac{\partial z}{\partial b_k}$

☒

$y \log(z) + (1 - y)(1 - \log(z))$ and $\frac{\partial L}{\partial z} \frac{\partial z}{\partial b_k}$

☐

$y \log(z) + (1 - y)(1 - \log(z))$ and $(y + z)x_k$

Yes, the answer is correct.

Score: 1

Accepted Answers:

$y \log(z) + (1 - y)(1 - \log(z))$ and $\frac{\partial L}{\partial z} \frac{\partial z}{\partial b_k}$

10) What are the advantages of initializing MLP with pretrained autoencoder weights

1 point

(i) Faster Convergence

(ii) Avoid overfitting

(iii) Simpler hypothesis

☐ (i) and (ii)

☐ (ii) and (iii)

☒ (i) and (iii)

☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

(i) and (ii)

[Previous Page](#)

[End](#)

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 6 - Week 5

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

- ☐ Lecture 21: Cost Function
- ☐ Lecture 22: Classification cost functions
- ☐ Lecture 23: Optimization Techniques and Learning Rules
- ☐ Lecture 24: Gradient Descent Learning Rule
- ☐ Lecture 25: SGD and ADAM Learning Rules
- ☐ Week 5: Lecture Slides
- ☐ Quiz : Assignment 5
- ☐ Week 5: Assignment Solutions

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 5

The due date for submitting this assignment has passed.

Due on 2018-02-28, 23:59 IST.

Assignment submitted on 2018-02-28, 21:03 IST

- 1) Which of the following functions are used for classification
- (i) Binary cross entropy
 - (ii) Soft margin loss
 - (iii) Absolute loss
 - (iv) Mean squared error

- ☒ (i) and (ii)
- ☐ (ii) and (iii)
- ☐ (iii) and (iv)
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

(i) and (ii)

1 point

- 2) Which of the following functions are used for regression
- (i) Binary cross entropy
 - (ii) Soft margin loss
 - (iii) Absolute loss
 - (iv) Mean squared error

- ☐ (i) and (ii)
- ☐ (ii) and (iii)
- ☒ (iii) and (iv)
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

(iii) and (iv)

1 point

- 3) Which of the following loss function is employed for multi-class classification
- ☒ Binary cross entropy
 - ☐ Negative log likelihood
 - ☐ L1 Loss
 - ☐ MSE

No, the answer is incorrect.

Score: 0

Accepted Answers:

Negative log likelihood

1 point

- 4) Given a neural network with one output neuron (with sigmoid activation) for two class classification, which of the following loss function is used

- ☒ Binary cross entropy
- ☐ Negative log likelihood
- ☐ L1 Loss
- ☐ MSE

Yes, the answer is correct.

Score: 1

Accepted Answers:

Binary cross entropy

1 point

- 5) Given a neural network with two output neurons (with log softmax activation) for two class classification, 1 point

which of the following loss function is used

- ☐ Binary cross entropy
- ☒ Negative log likelihood
- ☐ L1 Loss
- ☐ MSE

Yes, the answer is correct.

Score: 1

Accepted Answers:

Negative log likelihood

6) To employ margin loss for classification which transfer function should be used to transform the responses of output neurons

1 point

- ☐ Sigmoid
- ☐ ReLU
- ☐ Leaky ReLU
- ☒ Tanh

Yes, the answer is correct.

Score: 1

Accepted Answers:

Tanh

7) Which of the following loss is asymmetric in nature

1 point

- ☐ L1 Loss
- ☐ MSE Loss
- ☒ Kullback-Leibler Divergence
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Kullback-Leibler Divergence

8) Which of the following loss is non differential

1 point

- ☒ L1 Loss
- ☐ MSE Loss
- ☐ Kullback-Leibler Divergence
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

L1 Loss

9) Which of the following losses are combined while training sparse autoencoder

1 point

- (i) MSE
- (ii) KL divergence
- (iii) Absolute loss

- ☒ (i) and (ii)
- ☐ (ii) and (iii)
- ☐ (iii) and (i)
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

(i) and (ii)

10) Which of the following regression losses is more prone to outliers

1 point

- ☒ MSE Loss
- ☐ L1 Loss
- ☐ Minimum (MSE loss, L1 loss)
- ☐ Cross entropy

Yes, the answer is correct.

Score: 1

Accepted Answers:

MSE Loss

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 7 - Week 6

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

- ☐ Lecture 26: Convolutional Neural Network Building Blocks
- ☐ Lecture 27: Simple CNN Model: LeNet
- ☐ Lecture 28: LeNet Definition
- ☐ Lecture 29: Training a LeNet for MNIST Classification
- ☐ Lecture 30: Modifying a LeNet for CIFAR
- ☐ Feedback for Week 6
- ☐ Week 6: Lecture Slides
- ☐ Quiz : Assignment 6
- ☐ Week 6: Assignment Solutions

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 6

The due date for submitting this assignment has passed.

Due on 2018-03-07, 23:59 IST.

Assignment submitted on 2018-03-07, 23:29 IST

1) What should be the response dimension if an image of dimension $3 \times 25 \times 25$ is convolved with a filter of dimension $3 \times 5 \times 5$? **1 point**

- ☒ $1 \times 21 \times 21$
- ☐ $3 \times 25 \times 25$
- ☐ $1 \times 25 \times 25$
- ☐ $25 \times 25 \times 1$

Yes, the answer is correct.

Score: 1

Accepted Answers:

$1 \times 21 \times 21$

2) What should be the response dimension if an image of dimension $3 \times 25 \times 25$ is padded with width of 2 and convolved with a filter of dimension $3 \times 5 \times 5$? **1 point**

- ☐ $1 \times 21 \times 21$
- ☐ $3 \times 25 \times 25$
- ☒ $1 \times 25 \times 25$
- ☐ $25 \times 25 \times 1$

Yes, the answer is correct.

Score: 1

Accepted Answers:

$1 \times 25 \times 25$

3) What should be the response dimension if an image of dimension $3 \times 25 \times 25$ is convolved with a filter of dimension $3 \times 5 \times 5$ and considered stride as 2 ? **1 point**

- ☐ $1 \times 11 \times 11$
- ☐ $3 \times 12.5 \times 12.5$
- ☐ $1 \times 12.5 \times 12.5$
- ☒ $1 \times 12 \times 12$

No, the answer is incorrect.

Score: 0

Accepted Answers:

$1 \times 11 \times 11$

4) Including maxpooling equips the model to be invariant to _____ with in the limits of maxpooling kernel **1 point**

- ☐ Scale
- ☐ Translation



Rotation

☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Translation

5) Which of the following filter is functionally equivalent to maxpooling operation

1 point

☐ Erosion

☐ Dilation

☐ Rank Filter

☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Dilation

6) If the encoder part of an autoencoder with 784 input neurons and 100 hidden neurons can be rewrapped as a n convolutional filters each with a, b and c as input channels, filter height and filter width. What are the values of n, a, b and c

Hint: Autoencoder is trained on gray scale image patches of size 28×28

☐ 1, 100, 28 and 28

☐ 100, 1, 28 and 28

☐ 28, 100, 1 and 28

☒ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

100, 1, 28 and 28

7) Which operation needs max pooling indices or switch variables?

1 point

☐ Pooling

☐ Unpooling

☐ Activation

☒ Deconvolution

No, the answer is incorrect.

Score: 0

Accepted Answers:

Unpooling

8) Which operation needs learnable weights?

1 point

☐ Pooling

☐ Unpooling

☐ Activation

☒ Deconvolution

Yes, the answer is correct.

Score: 1

Accepted Answers:

Deconvolution

9) What of the following activation function has no gradient for negative responses

1 point

☐ Sigmoid

☐ Tanh

☒ ReLU

☐ Absolute

Yes, the answer is correct.

Score: 1

Accepted Answers:

ReLU

10) LeNet is designed for classification of

1 point

☐ Alphabets

☒ Numbers or digits

☐ Images

☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Numbers or digits

[Previous Page](#)

[End](#)

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 8 - Week 7

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

- ☐ Lecture 31 : Convolutional Autoencoder and Deep CNN
- ☐ Lecture 32 : Convolutional Autoencoder for Representation Learning
- ☐ Lecture 33 : AlexNet
- ☐ Lecture 34 : VGGNet
- ☐ Lecture 35 : Revisiting AlexNet and VGGNet for Computational Complexity
- ☐ Feedback for Week 7
- ☐ Week 7: Lecture Slides
- ☐ Quiz : Assignment 7

Week 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 7

The due date for submitting this assignment has passed.

Due on 2018-03-14, 23:59 IST.

Assignment submitted on 2018-03-14, 16:52 IST

1) What advantage does convolutional autoencoder offer in comparison to vanilla autoencoder

1 point

- ☐ Scalable to large images
- ☐ Feature extraction
- ☐ Unsupervised
- ☒ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Scalable to large images

2) In convolutional autoencoder pooling layer is employed to

1 point

- ☐ Distribute gradients effectively
- ☒ Increase receptive field with same kernel size in subsequent layers
- ☐ Employ unpooling layer
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Increase receptive field with same kernel size in subsequent layers

3) In convolutional autoencoder the middle layers are fully connected because

1 point

- ☒ This effectively extracts global features
- ☐ Convolutional AE is built upon vanilla AE
- ☐ Increase speed of operations
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

This effectively extracts global features

4) Which layer should be used in decoder part of Convolutional autoencoder if convolution layer with stride is used in encoder part

1 point

- ☐ Unpooling
- ☒ Deconvolution
- ☐ Bilinear Interpolation
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Deconvolution

5) What is the architectural difference between VGG and Alexnet

1 point

- ☒ VGG has single feature extraction stream and Alexnet has two
- ☐ Deconvolution
- ☐ Bilinear interpolation

☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

VGG has single feature extraction stream and Alexnet has two

6) Which of the architecture has most number of layers and parameters

1 point

- ☒ VGG Net
- ☐ Alex Net
- ☐ LeNet
- ☐ All have same number of parameters

Yes, the answer is correct.

Score: 1

Accepted Answers:

VGG Net

7) Local response normalization is employed to

1 point

- ☐ Increase the local maxima response and subdue the neighboring responses
- ☒ Augment activation performance
- ☐ Sparsify gradients
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Increase the local maxima response and subdue the neighboring responses

8) If CNN filters (no bias) of size 3×3 are employed for transforming an image with 3 channels into 64 responses. How many weights need to be learned

1 point

- ☐ 1378
- ☒ 1728
- ☐ 1738
- ☐ 2000

Yes, the answer is correct.

Score: 1

Accepted Answers:

1728

9) If max pooling kernels of size 3×3 are employed for transforming an image with 3 channels into 3 responses. How many weights need to be learned

1 point

- ☐ 27
- ☐ 18
- ☐ 9
- ☒ 0

Yes, the answer is correct.

Score: 1

Accepted Answers:

0

10) Local response normalization is performed

1 point

- ☐ Mean of the channels
- ☒ Across channels
- ☐ Individual channel
- ☐ None

No, the answer is incorrect.

Score: 0

Accepted Answers:

Individual channel

Previous Page

End

[© 2014 NPTEL](#) - [Privacy & Terms](#) - [Honor Code](#) - [FAQs](#) -

A project of

In association with

Funded by



NPTEL

National Programme on
Technology Enhanced Learning

NASSCOM[®]

Powered by

Google[™]

Government of India
Ministry of Human Resource Development

Unit 9 - Week 8

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

☐ Lecture 36: GoogLeNet - Going very deep with convolutions

☐ Lecture 37: GoogLeNet

☐ Lecture 38: ResNet - Residual Connections within Very Deep Networks and DenseNet - Densely connected networks

☐ Lecture 39: ResNet

☐ Lecture 40: DenseNet

☐ Feedback for Week 8

☐ Week 8: Lecture Slides

☐ Quiz : Assignment 8

Week 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 8

The due date for submitting this assignment has passed.

Due on 2018-03-21, 23:59 IST.

Assignment submitted on 2018-03-21, 23:52 IST

1) In inception block the input information is processed through how many parallel channels?

1 point

- ☐ 2
☐ 3
☒ 4
☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

4

2) In inception block the processed input information is combined using which operation?

1 point

- ☐ Sum
☐ Multiplication
☒ Concatenation
☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Concatenation

3) In inception block, what kernel sizes are employed for convolution?

1 point

- ☐ 1×1
☐ 2×2
☒ 3×3
☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

All of the above

4) In inception block, what is the contribution of Maxpooling?

1 point

- ☐ To extract features at multiple scales
☒ To reduce compute complexity
☐ To dilate the response values
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

To dilate the response values

5) The idea for residual layer has originated from training _____ layers effectively.

1 point

- ☐ Initial
☒ Final
☐ Both
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Initial

6) The mathematical equivalence of skip connection in residual block is

1 point

- ☐ Identity matrix
- ☒ Summation
- ☐ Convolution
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Identity matrix

7) In which case does the loss saturates with less epochs for deeper networks

1 point

- ☐ Network with residual block
- ☒ Network without residual block
- ☐ It is subjective
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Network without residual block

8) Which network needs less amount of memory for equal performance

1 point

- ☐ Densenet
- ☒ Residual net
- ☐ VGG net
- ☐ All are same

No, the answer is incorrect.

Score: 0

Accepted Answers:

Densenet

9) In densenet the information of current is passed on to

1 point

- ☐ Subsequent layer
- ☐ Subsequent layers
- ☒ User defined
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Subsequent layers

10) In densenet such passed on information is

1 point

- ☐ Summed
- ☒ Concatenated
- ☐ Multiplied
- ☐ None of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

Concatenated

Previous Page

End

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 10 - Week 9

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

☐ Lecture 41 : Space and Computational Complexity in DNN

☐ Lecture 42 : Assessing the space and computational complexity of very deep CNNs

☐ Lecture 43 : Domain Adaptation and Transfer Learning in Deep Neural Networks

☐ Lecture 44 : Transfer Learning a GoogLeNet

☐ Lecture 45 : Transfer Learning a ResNet

☐ Feedback for Week 9

☐ Week 9: Lecture Slides

☐ Quiz : Assignment 9

Week 10

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 9

The due date for submitting this assignment has passed.

Due on 2018-03-28, 23:59 IST.

Assignment submitted on 2018-03-28, 23:56 IST

1) What is the space complexity of a fully connected layer (double precision floating with bias) with 100 input neurons and 10 output neurons?

1 point

- ☐ ~8 KB
☒ ~64 KB
☐ ~32 KB
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

~8 KB

2) What is the operational complexity of a fully connected layer (double precision floating with bias) with 100 input neurons and 10 output neurons?

1 point

- ☐ ~189 Kb
☐ ~17 KB
☒ ~138 Kb
☐ ~20 KB

No, the answer is incorrect.

Score: 0

Accepted Answers:

~17 KB

3) What is the space complexity of a CNN block (double precision floating with bias) with 10 kernels each with channels, height and width being 3, 5 and 5 respectively?

1 point

- ☒ ~47 KB
☐ ~46.8 Kb
☐ ~6 KB
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

~6 KB

4) What is the operational complexity of a CNN block (double precision floating with bias) with 10 kernels each with channels, height and width being 3, 5 and 5 respectively?

1 point

- ☒ ~47 Mb
☐ ~17 MB
☐ ~ 46.8 Mb
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

None of the above

5) Data batch size is determined by?

1 point

- ☐ Model Size
☐ RAM Size
☐ Hard Drive Size
☒ Both Model and RAM Size

Yes, the answer is correct.

Score: 1

Accepted Answers:

Both Model and RAM Size

6) Which of the following are placed on RAM during training?

1 point

- ☐ Model parameters
- ☐ Model gradients
- ☐ Partial data
- ☒ All of the above

Yes, the answer is correct.

Score: 1

Accepted Answers:

All of the above

7) Which transform is used to accelerate the compute?

1 point

- ☐ Fourier
- ☐ Hilbert
- ☐ PCA
- ☒ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Fourier

8) What technique is employed to introduce domain adaptation in stacked autoencoder?

1 point

- ☐ Systematic dropout
- ☐ Conditional dictionary learning
- ☒ Feature sampling
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Systematic dropout

9) What conditions are required for employing domain adaptation

1 point

- ☐ Existence of common domain
- ☒ Ample amount of labelled data in source domain
- ☐ Ample amount of labelled data in target domain
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Existence of common domain

10) Domain adaptation has application towards

1 point

- ☐ Semantic segmentation
- ☒ Object localization
- ☐ Image classification
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

All of the above

Previous Page

End

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 11 - Week 10

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

☐ Feedback for Week 10

☐ Lecture 46: Activation pooling for object localization

☐ Lecture 47: Region Proposal Networks (rCNN and Faster rCNN)

☐ Lecture 48: GAP + rCNN

☐ Lecture 49: Semantic Segmentation with CNN

☐ Lecture 50: UNet and SegNet for Semantic Segmentation

☐ Quiz : Assignment 10

☐ Week 10: Lecture Slides

Week 11

Week 12

DOWNLOAD VIDEOS

Assignment 10

The due date for submitting this assignment has passed.
As per our records you have not submitted this assignment.

Due on 2018-04-04, 23:59 IST.

1) What is the input to region proposal network (rpn) ?

1 point

- ☐ RGB images
- ☐ Object Responses
- ☐ Both of the above
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

RGB images

2) What is the output of rpn ?

1 point

- ☐ Probability of the object class
- ☐ Bounding box parameters of the object
- ☐ Both of the above
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both of the above

3) Which losses govern the rpn ?

1 point

- ☐ Classification loss
- ☐ Regression loss
- ☐ Both of the above
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both of the above

4) What kind of classifier is employed in rpn ?

1 point

- ☐ One class
- ☐ Two class
- ☐ Multi class
- ☐ No classifier is employed

No, the answer is incorrect.

Score: 0

Accepted Answers:

Multi class

5) Multiple anchor boxes are generated by changing

1 point

- ☐ Aspect ratio
- ☐ Scale
- ☐ Centre
- ☐ Both aspect ratio and scale

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both aspect ratio and scale

6) Which of the following results in multi scale feature extraction

1 point

- ☐ Multiple filter sizes
- ☐ Multiple versions of rescaled input image
- ☐ Both of the above
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both of the above

7) rpn fails in case of

1 point

- ☐ overlapping objects from different class
- ☐ overlapping objects from same class
- ☐ overlapping objects
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

None of the above

8) Can an object classifier trained on image patches can propose regions on a canvas image

1 point

- ☐ Yes
- ☐ No
- ☐ yes as long as input statistics stay the same
- ☐ None

No, the answer is incorrect.

Score: 0

Accepted Answers:

yes as long as input statistics stay the same

9) How many outputs are predicted for a rpn with k anchor boxes

1 point

- ☐ 2k
- ☐ 4k
- ☐ 6k
- ☐ None

No, the answer is incorrect.

Score: 0

Accepted Answers:

6k

10) What is the dimension of the vector based on which the above outputs are generated

1 point

- ☐ 256
- ☐ 128
- ☐ Subjective to anchor boxes number
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

256

Previous Page

End



NPTEL

Technology Enhanced Learning

NASSCOM

Ministry of Human Resource Development

Powered by

Google

Unit 12 - Week 11

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

- ☐ Lecture 51 : Autoencoders and Latent Spaces
- ☐ Lecture 52 : Principle of Generative Modeling
- ☐ Lecture 53 : Adversarial Autoencoders
- ☐ Lecture 54 : Adversarial Autoencoder for Synthetic Sample Generation
- ☐ Lecture 55 : Adversarial Autoencoder for Classification
- ☐ Feedback for Week 11
- ☐ Quiz : Assignment 11
- ☐ Week 11: Lecture Slides

Week 12

DOWNLOAD VIDEOS

Assignment 11

The due date for submitting this assignment has passed.
As per our records you have not submitted this assignment.

Due on 2018-04-11, 23:59 IST.

1) What is the role of decoder in adversarial autoencoder?

1 point

- ☐ Generate the images for given latent space information
- ☐ For reducing MSE loss
- ☐ For constructing better latent space
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Generate the images for given latent space information

2) What could be a solution for generative model training

1 point

- ☐ By appending an auxiliary branch to distinguish between fake and real images
- ☐ Be reducing number of parameters in the model
- ☐ Data augmentation through various morphological transformations
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

By appending an auxiliary branch to distinguish between fake and real images

3) What is the property of a well trained generative model

1 point

- ☐ It can clearly distinguish between fake and real images
- ☐ Given a set of images it can generated a good latent space
- ☐ Given a a random noise the model is capable of generating realistic images
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Given a a random noise the model is capable of generating realistic images

4) Which of the following is true for adversarial autoencoder

1 point

- ☐ The information tapped out from decoder input is used to classify real or fake samples
- ☐ The information sampled from Gaussian distribution is used to classify real or fake samples
- ☐ Both a and b
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both a and b

5) Which of the following is true for adversarial autoencoder (AAE)

1 point

- ☐ It is supervised framework as a classifier is used for distinguishing positive and negative samples
- ☐ It is unsupervised framework
- ☐ The sampling space should be Gaussian
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

It is unsupervised framework

6) What is the distinction between AAE and AAE with regularization

1 point

- ☐ Inclusion of class label during classification of positive or negative samples
- ☐ Inclusion of class label during reconstruction of real sample
- ☐ Removal of classification
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Inclusion of class label during classification of positive or negative samples

7) What is true for Supervised AAE

1 point

- ☐ Inclusion of class label during classification of positive or negative samples
- ☐ Inclusion of class label during reconstruction of real sample
- ☐ Removal of classification
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Inclusion of class label during reconstruction of real sample

8) In the code snippet given what is the encoder? □□

1 point

```
class Q_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(Q_net, self).__init__()
        self.lin3gauss = nn.Linear(X_dim, z_dim)
    def forward(self, x):
        return xgauss
class P_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(P_net, self).__init__()
        self.lin1 = nn.Linear(z_dim,X_dim)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.25, training=self.training)
        return F.sigmoid(x)
class D_net_gauss(nn.Module):
    def __init__(self,N,z_dim):
        super(D_net_gauss, self).__init__()
        self.lin1 = nn.Linear(z_dim, N)
        self.lin3 = nn.Linear(N, 1)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.2, training=self.training)
        x = F.relu(x)
        return F.sigmoid(self.lin3(x))
```

- ☐ Q_net
- ☐ P_net
- ☐ D_net_gauss
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Q_net

9) In the code snippet given what is the decoder?

1 point


```

class Q_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(Q_net, self).__init__()
        self.lin3gauss = nn.Linear(X_dim, z_dim)
    def forward(self, x):
        return xgauss
class P_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(P_net, self).__init__()
        self.lin1 = nn.Linear(z_dim,X_dim)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.25, training=self.training)
        return F.sigmoid(x)
class D_net_gauss(nn.Module):
    def __init__(self,N,z_dim):
        super(D_net_gauss, self).__init__()
        self.lin1 = nn.Linear(z_dim, N)
        self.lin3 = nn.Linear(N, 1)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.2, training=self.training)
        x = F.relu(x)
        return F.sigmoid(self.lin3(x))

```

- ☐ Q_net
☐ P_net
☐ D_net_gauss
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

P_net

10) In the code snippet given what is the classifier?

1 point

```

class Q_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(Q_net, self).__init__()
        self.lin3gauss = nn.Linear(X_dim, z_dim)
    def forward(self, x):
        return xgauss
class P_net(nn.Module):
    def __init__(self,X_dim,N,z_dim):
        super(P_net, self).__init__()
        self.lin1 = nn.Linear(z_dim,X_dim)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.25, training=self.training)
        return F.sigmoid(x)
class D_net_gauss(nn.Module):
    def __init__(self,N,z_dim):
        super(D_net_gauss, self).__init__()
        self.lin1 = nn.Linear(z_dim, N)
        self.lin3 = nn.Linear(N, 1)
    def forward(self, x):
        x = F.dropout(self.lin1(x), p=0.2, training=self.training)
        x = F.relu(x)
        return F.sigmoid(self.lin3(x))

```

- ☐ Q_net
☐ P_net
☐ D_net_gauss
☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

D_net_gauss

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development

Unit 13 - Week 12

Course outline

How to access the portal

Week 1

Week 2

Week 3

Week 4

Week 5

Week 6

Week 7

Week 8

Week 9

Week 10

Week 11

Week 12

- ☐ Lecture 56 : Understanding Video Analysis
- ☐ Lecture 57 : Recurrent Neural Networks and Long Short-Term Memory
- ☐ Lecture 58 : Spatio-Temporal Deep Learning for Video Analysis
- ☐ Lecture 59 : Activity recognition using 3D-CNN
- ☐ Lecture 60 : Activity recognition using CNN-LSTM
- ☐ Feedback for Week 12
- ☐ Quiz : Assignment 12
- ☐ Week 12: Lecture Slides

DOWNLOAD VIDEOS

Assignment 12

The due date for submitting this assignment has passed.
As per our records you have not submitted this assignment.

Due on 2018-04-18, 23:59 IST.

1) Which of the following topology is true for RNN?

1 point

- ☐ Many to one
- ☐ Many to many
- ☐ One to many
- ☐ Any of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Any of the above

2) Which of the following parameters are needed for RNN in addition to input transformation weights ($W_{h,x,t}$)

1 point

- ☐ $W_{h,h,t}$
- ☐ h_{t-1}
- ☐ Both a and b
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both a and b

3) Which of the following gates are used in LSTM?

1 point

- ☐ Input
- ☐ Forget
- ☐ Output
- ☐ All of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

All of the above

4) Given a sequence of T color images of size 224 x 224, how are they organized for tensor processing ?

1 point

- ☐ $3 \times T \times 224 \times 224$
- ☐ $T \times 3 \times 224 \times 224$
- ☐ $3 \times T \times M \times M$
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

$3 \times T \times 224 \times 224$

5) Given a sequence of 100 color images of size 224 x 224 and kernel of size 3, no padding, 18 channels and single stride. What is the convolution output

1 point

- ☐ 18 x 100 x 222 x 222
- ☐ 18 x 98 x 222 x 222
- ☐ 18 x 98 x 224 x 224

☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

18 x 98 x 222 x 222

6) For temporal learning which architecture is most preferable

1 point

- ☐ Autoencoder
- ☐ LSTM
- ☐ CNN
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

LSTM

7) Which of the following hurdles of RNN were overcome by LSTM

1 point

- ☐ Learning long term dependencies
- ☐ Exponential decay of learning rate along time
- ☐ Both a and b
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Both a and b

8) Which of the following commands create a LSTM with input dimension as 3 and output dimension as 3 through nn module

1 point

- ☐ nn.LSTM(3, 3)
- ☐ nn.GRU(3, 3).LSTM
- ☐ nn.RNN(3, 3).LSTM
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

nn.LSTM(3, 3)

9) How many variables are generated upon feed forwarding LSTM for 5 step

1 point

- ☐ output variables
- ☐ output and hidden variables
- ☐ output, hidden and input storage variable
- ☐ None

No, the answer is incorrect.

Score: 0

Accepted Answers:

output, hidden and input storage variable

10) How many variables are fed for lstm

1 point

- ☐ Input
- ☐ Input and previous hidden state
- ☐ Input, previous hidden and previous output
- ☐ None of the above

No, the answer is incorrect.

Score: 0

Accepted Answers:

Input and previous hidden state

© 2014 NPTEL - Privacy & Terms - Honor Code - FAQs -

A project of



NPTEL

National Programme on
Technology Enhanced Learning

In association with

NASSCOM[®]

Powered by

Google[™]

Funded by

Government of India
Ministry of Human Resource Development