

TRCIDR4, ID Register 4

The TRCIDR4 characteristics are:

Purpose

Returns the tracing capabilities of the trace unit.

Configuration

External register TRCIDR4 bits [31:0] are architecturally mapped to AArch64 System register [TRCIDR4\[31:0\]](#).

This register is present only when FEAT_ETE is implemented and FEAT_TRC_EXT is implemented. Otherwise, direct accesses to TRCIDR4 are res0.

Attributes

TRCIDR4 is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
NUMVMIDC				NUMCIDC				NUMSSC				NUMRSPAIN				NUMPC				RES0		SUPPDAC		NUMDVC		NUMACP		AIRS			

NUMVMIDC, bits [31:28]

Indicates the number of Virtual Context Identifier Comparators that are available for tracing.

NUMVMIDC	Meaning
0b0000	No Virtual Context Identifier Comparators are available.
0b0001	The implementation has one Virtual Context Identifier Comparator.
0b0010	The implementation has two Virtual Context Identifier Comparators.
0b0011	The implementation has three Virtual Context Identifier Comparators.

0b0100	The implementation has four Virtual Context Identifier Comparators.
0b0101	The implementation has five Virtual Context Identifier Comparators.
0b0110	The implementation has six Virtual Context Identifier Comparators.
0b0111	The implementation has seven Virtual Context Identifier Comparators.
0b1000	The implementation has eight Virtual Context Identifier Comparators.

All other values are reserved.

NUMCIDC, bits [27:24]

Indicates the number of Context Identifier Comparators that are available for tracing.

NUMCIDC	Meaning
0b0000	No Context Identifier Comparators are available.
0b0001	The implementation has one Context Identifier Comparator.
0b0010	The implementation has two Context Identifier Comparators.
0b0011	The implementation has three Context Identifier Comparators.
0b0100	The implementation has four Context Identifier Comparators.
0b0101	The implementation has five Context Identifier Comparators.
0b0110	The implementation has six Context Identifier Comparators.
0b0111	The implementation has seven Context Identifier Comparators.
0b1000	The implementation has eight Context Identifier Comparators.

All other values are reserved.

NUMSSCC, bits [23:20]

Indicates the number of Single-shot Comparator Controls that are available for tracing.

NUMSSCC	Meaning
0b0000	No Single-shot Comparator Controls are available.
0b0001	The implementation has one Single-shot Comparator Control.
0b0010	The implementation has two Single-shot Comparator Controls.
0b0011	The implementation has three Single-shot Comparator Controls.
0b0100	The implementation has four Single-shot Comparator Controls.
0b0101	The implementation has five Single-shot Comparator Controls.
0b0110	The implementation has six Single-shot Comparator Controls.
0b0111	The implementation has seven Single-shot Comparator Controls.
0b1000	The implementation has eight Single-shot Comparator Controls.

All other values are reserved.

NUMRSPAIR, bits [19:16]

Indicates the number of resource selector pairs that are available for tracing.

NUMRSPAIR	Meaning
0b0000	The implementation has zero resource selectors.
0b0001	The implementation has two resource selector pairs.

0b0010	The implementation has three resource selector pairs.
0b0011	The implementation has four resource selector pairs.
0b0100	The implementation has five resource selector pairs.
0b0101	The implementation has six resource selector pairs.
0b0110	The implementation has seven resource selector pairs.
0b0111	The implementation has eight resource selector pairs.
0b1000	The implementation has nine resource selector pairs.
0b1001	The implementation has ten resource selector pairs.
0b1010	The implementation has eleven resource selector pairs.
0b1011	The implementation has twelve resource selector pairs.
0b1100	The implementation has thirteen resource selector pairs.
0b1101	The implementation has fourteen resource selector pairs.
0b1110	The implementation has fifteen resource selector pairs.
0b1111	The implementation has sixteen resource selector pairs.

All other values are reserved.

NUMPC, bits [15:12]

Indicates the number of PE Comparator Inputs that are available for tracing.

NUMPC	Meaning
0b0000	No PE Comparator Inputs are available.
0b0001	The implementation has one PE Comparator Input.
0b0010	The implementation has two PE Comparator Inputs.
0b0011	The implementation has three PE Comparator Inputs.
0b0100	The implementation has four PE Comparator Inputs.
0b0101	The implementation has five PE Comparator Inputs.
0b0110	The implementation has six PE Comparator Inputs.
0b0111	The implementation has seven PE Comparator Inputs.
0b1000	The implementation has eight PE Comparator Inputs.

All other values are reserved.

Bits [11:9]

Reserved, res0.

SUPPDAC, bit [8]

When TRCIDR4.NUMACPAIRS != 0b0000:

Indicates whether data address comparisons are implemented. Data address comparisons are not implemented in ETE and are reserved for other trace architectures. Allocated in other trace architectures.

SUPPDAC	Meaning
0b0	Data address comparisons not implemented.
0b1	Data address comparisons implemented.

This field reads as 0.

Otherwise:

Reserved, res0.

NUMDVC, bits [7:4]

Indicates the number of data value comparators. Data value comparators are not implemented in ETE and are reserved for other trace architectures. Allocated in other trace architectures.

NUMDVC	Meaning
0b0000	No data value comparators implemented.
0b0001	One data value comparator implemented.
0b0010	Two data value comparators implemented.
0b0011	Three data value comparators implemented.
0b0100	Four data value comparators implemented.
0b0101	Five data value comparators implemented.
0b0110	Six data value comparators implemented.
0b0111	Seven data value comparators implemented.
0b1000	Eight data value comparators implemented.

All other values are reserved.

This field reads as 0b0000.

NUMACPAIRS, bits [3:0]

Indicates the number of Address Comparator pairs that are available for tracing.

NUMACPAIRS	Meaning
0b0000	No Address Comparator pairs are available.
0b0001	The implementation has one Address Comparator pair.
0b0010	The implementation has two Address Comparator pairs.
0b0011	The implementation has three Address Comparator pairs.

0b0100	The implementation has four Address Comparator pairs.
0b0101	The implementation has five Address Comparator pairs.
0b0110	The implementation has six Address Comparator pairs.
0b0111	The implementation has seven Address Comparator pairs.
0b1000	The implementation has eight Address Comparator pairs.

All other values are reserved.

Accessing TRCIDR4

TRCIDR4 can be accessed through the external debug interface:

Component	Offset	Instance
ETE	0x1F0	TRCIDR4

This interface is accessible as follows:

- When OSLockStatus() or !IsTraceCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.