RCWSCLRP, RCWSCLRPA, RCWSCLRPL, RCWSCLRPAL

Read Check Write Software atomic bit Clear on quadword in memory atomically loads a 128-bit quadword from memory, performs a bitwise AND with the complement of the value held in a pair of registers on it, and conditionally stores the result back to memory. Storing of the result back to memory is conditional on RCW Checks and RCWS Checks. The value initially loaded from memory is returned in the same pair of registers. This instruction updates the condition flags based on the result of the update of memory.

- `RCWSCLRPA` and `RCWSCLRPAL` load from memory with acquire semantics.
- `RCWSCLRPL` and `RCWSCLRPAL` store to memory with release semantics.
- `RCWSCLRP` has neither acquire nor release semantics.

Integer
(FEAT_D128 && FEAT_THE)



RCWSCLRP (A == 0 && R == 0)

```
RCWSCLRP <Xt1>, <Xt2>, [<Xn|SP>]
```

RCWSCLRPA (A == 1 && R == 0)

```
RCWSCLRPA <Xt1>, <Xt2>, [<Xn|SP>]
```

RCWSCLRPAL (A == 1 && R == 1)

```
RCWSCLRPAL <Xt1>, <Xt2>, [<Xn|SP>]
```

RCWSCLRPL (A == 0 && R == 1)

```
RCWSCLRPL <Xt1>, <Xt2>, [<Xn|SP>]
```

```
if !IsFeatureImplemented(FEAT_D128) || !IsFeatureImplemented(FEAT_THE) then UNDEFINED;
if Rt == '11111' then UNDEFINED;
if Rt2 == '11111' then UNDEFINED;
integer t = UInt(Rt);
integer t2 = UInt(Rt2);
integer n = UInt(Rn);

boolean acquire = A == '1';
```

```
boolean release = R == '1';
boolean tagchecked = n != 31;

boolean rt_unknown = FALSE;

if t == t2 then
    Constraint c = ConstrainUnpredictable(Unpredictable_LSE128OVERLAP);
    assert c IN {Constraint_UNKNOWN, Constraint_UNDEF, Constraint_NOP};
    case c of
        when Constraint_UNKNOWN rt_unknown = TRUE;    // result is UNKN
        when Constraint_UNDEF   UNDEFINED;
        when Constraint_NOP     EndOfInstruction();
```

Assembler Symbols

<Xt1>	Is the 64-bit name of the first general-purpose register to be transferred, encoded in the "Rt" field.
<Xt2>	Is the 64-bit name of the second general-purpose register to be transferred, encoded in the "Rt2" field.
<Xn|SP>	Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.

Operation

```
if !IsD128Enabled(PSTATE.EL) then UNDEFINED;
bits(64) address;
bits(64) value1;
bits(64) value2;
bits(128) newdata;
bits(128) readdata;
bits(4) nzcv;

AccessDescriptor accdesc = CreateAccDescRCW(MemAtomicOp_BIC, TRUE, acqu

if n == 31 then
    CheckSPAlignment();
    address = SP[];
else
    address = X[n, 64];

value1 = X[t, 64];
value2 = X[t2, 64];

newdata = if BigEndian(accdesc.acctype) then value1:value2 else value2:

bits(128) compdata = bits(128) UNKNOWN;    // Irrelevant when not execu
(nzcv, readdata) = MemAtomicRCW(address, compdata, newdata, accdesc);

PSTATE.<N,Z,C,V> = nzcv;
if rt_unknown then
    readdata = bits(128) UNKNOWN;

if BigEndian(accdesc.acctype) then
    X[t, 64] = readdata<127:64>;
    X[t2, 64] = readdata<63:0>;
else
```

```
    X[t, 64] = readdata<63:0>;
    X[t2, 64] = readdata<127:64>;
```

Operational information

If PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored.

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56