

ERXMISC2_EL1, Selected Error Record Miscellaneous Register 2

The ERXMISC2_EL1 characteristics are:

Purpose

Accesses [ERR<n>MISC2](#) for the error record <n> selected by [ERRSELR_EL1](#).SEL.

Configuration

AArch64 System register ERXMISC2_EL1 bits [31:0] are architecturally mapped to AArch32 System register [ERXMISC4\[31:0\]](#).

AArch64 System register ERXMISC2_EL1 bits [63:32] are architecturally mapped to AArch32 System register [ERXMISC5\[31:0\]](#).

This register is present only when FEAT_RASv1p1 is implemented. Otherwise, direct accesses to ERXMISC2_EL1 are undefined.

Attributes

ERXMISC2_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
ERR<n>MISC2																															
ERR<n>MISC2																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:0]

ERXMISC2_EL1 accesses [ERR<n>MISC2](#), where <n> is the value in [ERRSELR_EL1](#).SEL.

Accessing ERXMISC2_EL1

If [ERRIDR_EL1](#).NUM is 0x0000 or [ERRSELR_EL1](#).SEL is greater than or equal to [ERRIDR_EL1](#).NUM, then one of the following occurs:

- An unknown error record is selected.
- ERXMISC2_EL1 is RAZ/WI.
- Direct reads and writes of ERXMISC2_EL1 are NOPs.
- Direct reads and writes of ERXMISC2_EL1 are undefined.

[ERR<n>MISC2](#) describes additional constraints that also apply when [ERR<n>MISC2](#) is accessed through ERXMISC2_EL1.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, ERXMISC2_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0101	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && SCR_EL3.TERR == '1' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TERR == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HFGTR_EL2.ERXMISCn_EL1 ==
    '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.TERR == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = ERXMISC2_EL1;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && SCR_EL3.TERR == '1' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.TERR == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = ERXMISC2_EL1;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = ERXMISC2_EL1;
```

MSR ERXMISC2_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0101	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && SCR_EL3.TERR == '1' then
        UNDEFINED;
    elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
    '1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
    priority when SDD == '1'" && SCR_EL3.TWERR == '1'
    then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.TERR == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HFGWTR_EL2.ERXMISCN_EL1 ==
    '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.TERR == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        elsif HaveEL(EL3) && SCR_EL3.TWERR == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                ERXMISC2_EL1 = X[t, 64];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && SCR_EL3.TERR == '1' then
            UNDEFINED;
        elsif Halted() && HaveEL(EL3) && EDSCR.SDD ==
        '1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
        priority when SDD == '1'" && SCR_EL3.TWERR == '1'
        then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.TERR == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        elsif HaveEL(EL3) && SCR_EL3.TWERR == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
```

```
else
    ERXMISC2_EL1 = X[t, 64];
elsif PSTATE.EL == EL3 then
    ERXMISC2_EL1 = X[t, 64];
```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.