

BIC (vector, immediate)

Bitwise bit Clear (vector, immediate). This instruction reads each vector element from the destination SIMD&FP register, performs a bitwise AND between each result and the complement of an immediate constant, places the result into a vector, and writes the vector to the destination SIMD&FP register.

Depending on the settings in the [CPACR_EL1](#), [CPTR_EL2](#), and [CPTR_EL3](#) registers, and the current Security state and Exception level, an attempt to execute the instruction might be trapped.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	Q	1	0	1	1	1	1	0	0	0	0	0	a	b	c	x	x	x	1	0	1	d	e	f	g	h	Rd				
op													cmode																		

16-bit (cmode == 10x1)

```
BIC <Vd>.<T>, #<imm8>{, LSL #<amount>}
```

32-bit (cmode == 0xx1)

```
BIC <Vd>.<T>, #<imm8>{, LSL #<amount>}
```

```
integer rd = UInt(Rd);

constant integer datasize = 64 << UInt(Q);
bits(datasize) imm;
bits(64) imm64;

ImmediateOp operation;
case cmode:op of
  when '0xx01' operation = ImmediateOp_MVNI;
  when '0xx11' operation = ImmediateOp_BIC;
  when '10x01' operation = ImmediateOp_MVNI;
  when '10x11' operation = ImmediateOp_BIC;
  when '110x1' operation = ImmediateOp_MVNI;
  when '1110x' operation = ImmediateOp_MOVI;
  when '11111'
    // FMOV Dn,#imm is in main FP instruction set
    if Q == '0' then UNDEFINED;
    operation = ImmediateOp_MOVI;

imm64 = AdvSIMDExpandImm(op, cmode, a:b:c:d:e:f:g:h);
imm = Replicate(imm64, datasize DIV 64);
```

Assembler Symbols

<Vd> Is the name of the SIMD&FP register, encoded in the "Rd" field.

<T>

For the 16-bit variant: is an arrangement specifier, encoded in "Q":

Q	<T>
0	4H
1	8H

For the 32-bit variant: is an arrangement specifier, encoded in "Q":

Q	<T>
0	2S
1	4S

<imm8>

Is an 8-bit immediate encoded in "a:b:c:d:e:f:g:h".

<amount>

For the 16-bit variant: is the shift amount encoded in "cmode<1>":

cmode<1>	<amount>
0	0
1	8

defaulting to 0 if LSL is omitted.

For the 32-bit variant: is the shift amount encoded in "cmode<2:1>":

cmode<2:1>	<amount>
00	0
01	8
10	16
11	24

defaulting to 0 if LSL is omitted.

Operation

```
CheckFPAdvSIMDEnabled64 ();
bits(datasize) operand;
bits(datasize) result;

case operation of
    when ImmediateOp\_MOVI
        result = imm;
    when ImmediateOp\_MVNI
        result = NOT(imm);
    when ImmediateOp\_ORR
        operand = V[rd, datasize];
        result = operand OR imm;
```

```
when ImmediateOp\_BIC  
    operand = V[rd, datasize];  
    result = operand AND NOT(imm);  
  
V[rd, datasize] = result;
```

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseu](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode
no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This
document is Non-Confidential.