

## TRCIDR11, ID Register 11

The TRCIDR11 characteristics are:

### Purpose

Returns the tracing capabilities of the trace unit.

### Configuration

External register TRCIDR11 bits [31:0] are architecturally mapped to AArch64 System register [TRCIDR11\[31:0\]](#).

This register is present only when FEAT\_ETE is implemented and FEAT\_TRC\_EXT is implemented. Otherwise, direct accesses to TRCIDR11 are res0.

### Attributes

TRCIDR11 is a 32-bit register.

### Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
NUMP1SPC																															

#### NUMP1SPC, bits [31:0]

When TRCIDR0.TRCDATA != 0b00:

Indicates the number of special P1 right-hand keys. Data tracing is not implemented in ETE and this field is reserved for other trace architectures. Allocated in other trace architectures.

#### Otherwise:

Reserved, res0.

### Accessing TRCIDR11

TRCIDR11 can be accessed through the external debug interface:

Component	Offset	Instance
ETE	0x18C	TRCIDR11

This interface is accessible as follows:

- When OSLockStatus() or !IsTraceCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

---

[AArch32  
Registers](#)

[AArch64  
Registers](#)

[AArch32  
Instructions](#)

[AArch64  
Instructions](#)

[Index by  
Encoding](#)

[External  
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.