

GICC_STATUSR, CPU Interface Status Register

The GICC_STATUSR characteristics are:

Purpose

Provides software with a mechanism to detect:

- Accesses to reserved locations.
- Writes to read-only locations.
- Reads of write-only locations.

Configuration

This register is present only when FEAT_GICv3_LEGACY is implemented. Otherwise, direct accesses to GICC_STATUSR are res0.

If the GIC implementation supports two Security states this register is Banked to provide Secure and Non-secure copies.

This register is used only when System register access is not enabled. If System register access is enabled, this register is not updated. Equivalent functionality might be provided by appropriate traps and exceptions.

Attributes

GICC_STATUSR is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0					
RES0																									ASVWRODRWODWRDRRD											

Bits [31:5]

Reserved, res0.

ASV, bit [4]

Attempted security violation.

ASV	Meaning
0b0	Normal operation.
0b1	A Non-secure access to a Secure register has been detected.

Note

This bit is not set to 1 for registers where any of the fields are Non-secure.

WROD, bit [3]

Write to an RO location.

WROD	Meaning
0b0	Normal operation.
0b1	A write to an RO location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

RWOD, bit [2]

Read of a WO location.

RWOD	Meaning
0b0	Normal operation.
0b1	A read of a WO location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

WRD, bit [1]

Write to a reserved location.

WRD	Meaning
0b0	Normal operation.
0b1	A write to a reserved location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

RRD, bit [0]

Read of a reserved location.

RRD	Meaning
0b0	Normal operation.
0b1	A read of a reserved location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

Accessing GICC_STATUSR

This is an optional register. If the register is not implemented, the location is RAZ/WI.

If this register is implemented, [GICV_STATUSR](#) must also be implemented.

GICC_STATUSR can be accessed through the memory-mapped interfaces:

Component	Offset	Instance
GIC CPU interface	0x002C	GICC_STATUSR (S)

This interface is accessible as follows:

- When GICD_CTLR.DS == 0, accesses to this register are **RW**.
- When an access is Secure, accesses to this register are **RW**.

Component	Offset	Instance
GIC CPU interface	0x002C	GICC_STATUSR (NS)

This interface is accessible as follows:

- When GICD_CTLR.DS == 0, accesses to this register are **RW**.
- When an access is Non-secure, accesses to this register are **RW**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.