GICD_ISACTIVER<n>E, Interrupt Set-Active Registers (extended SPI range), n = 0 - 31

The GICD_ISACTIVER<n>E characteristics are:

Purpose

Adds the active state to the corresponding SPI in the extended SPI range.

Configuration

This register is present only when FEAT_GICv3p1 is implemented. Otherwise, direct accesses to GICD_ISACTIVER<n>E are res0.

When GICD_TYPER.ESPI==0, these registers are res0.

When GICD_TYPER.ESPI==1, the number of implemented GICD_ISACTIVER<n>E registers is (GICD_TYPER.ESPI_range+1). Registers are numbered from 0.

Attributes

GICD_ISACTIVER<n>E is a 32-bit register.

Field descriptions

31	30	29	28	27	26
Set_active_bit31	Set_active_bit30	Set_active_bit29	Set_active_bit28	Set_active_bit27	Set_active_bit26

Set_active_bit<x>, bit [x], for x = 31 to 0

For the extended SPIs, adds the active state to interrupt number x. Reads and writes have the following behavior:

Set_active_bit<x>	Meaning
0b0	If read, indicates that the corresponding interrupt is not active, and is not active and pending. If written, has no effect.

0b1	If read, indicates that the corresponding interrupt is active, or active and pending on this PE. If written, activates the corresponding interrupt, if the interrupt is not already active. If the interrupt is already active, the write has no effect. After a write of 1 to this bit, a subsequent read of this bit returns 1.

The reset behavior of this field is:

- On a GIC reset, this field resets to 0.

For INTID m, when DIV and MOD are the integer division and modulo operations:

- The corresponding GICD_ISACTIVER<n>E number, n, is given by n = (m-4096) DIV 32.
- The offset of the required GICD_ISACTIVER<n>E is (0x1A00 + (4*n)).
- The bit number of the required group modifier bit in this register is (m-4096) MOD 32.

Accessing GICD_ISACTIVER<n>E

When affinity routing is not enabled for the Security state of an interrupt in GICD_ISACTIVER<n>E, the corresponding bit is res0.

When GICD_CTLR.DS==0, bits corresponding to Secure SPIs are RAZ/WI to Non-secure accesses.

Bits corresponding to unimplemented interrupts are RAZ/WI.

GICD_ISACTIVER<n>E can be accessed through the memory-mapped interfaces:

Component	Frame	Offset	Instance
GIC Distributor	Dist_base	0x1A00 + (4 * n)	GICD_ISACTIVER<n>E

Accesses on this interface are **RW**.

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94