TRBBASER_EL1, Trace Buffer Base Address Register

The TRBBASER_EL1 characteristics are:

Purpose

Defines the base address for the trace buffer.

Configuration

AArch64 System register TRBBASER_EL1 bits [63:0] are architecturally mapped to External register TRBBASER_EL1[63:0] when FEAT_TRBE_EXT is implemented.

This register is present only when FEAT_TRBE is implemented. Otherwise, direct accesses to TRBBASER_EL1 are undefined.

Attributes

TRBBASER_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
BASE																															
BASE																				RES0											
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

BASE, bits [63:12]

Trace Buffer Base pointer address. (TRBBASER_EL1.BASE << 12) is the address of the first byte in the trace buffer. Bits [11:0] of the Base pointer address are always zero. If the smallest implemented translation granule is not 4KB, then TRBBASER_EL1[N-1:12] are res0, where N is the implementation defined value Log_2(smallest implemented translation granule).

The reset behavior of this field is:

- On a Cold reset, this field resets to an architecturally unknown value.

Bits [11:0]

Reserved, res0.

Accessing TRBBASER_EL1

The PE might ignore a write to TRBBASER_EL1 if any of the following apply:

- TRBLIMITR_EL1.E == 1, and either FEAT_TRBE_EXT is not implemented or the Trace Buffer Unit is using Self-hosted mode.
- TRBLIMITR_EL1.XE == 1, FEAT_TRBE_EXT is implemented, and the Trace Buffer Unit is using External mode.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRBBASER_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b1001	0b1011	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRBBASER_EL1 ==
'1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && MDCR_EL2.E2TB == 'x0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRBBASER_EL1;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
```

```
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        UNDEFINED;
    elsif HaveEL(EL3) && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRBBASER_EL1;
elsif PSTATE.EL == EL3 then
    X[t, 64] = TRBBASER_EL1;
```

MSR TRBBASER_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b1001	0b1011	0b010

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRBBASER_EL1 ==
'1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && MDCR_EL2.E2TB == 'x0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRBBASER_EL1 = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
```

```
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        UNDEFINED;
    elsif HaveEL(EL3) && (MDCR_EL3.NSTB[0] == '0' ||
MDCR_EL3.NSTB[1] != SCR_EL3.NS ||
(IsFeatureImplemented(FEAT_RME) && MDCR_EL3.NSTBE !=
SCR_EL3.NSE)) then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRBBASER_EL1 = X[t, 64];
elsif PSTATE.EL == EL3 then
    TRBBASER_EL1 = X[t, 64];
```

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94