

## ST3W (scalar plus scalar)

Contiguous store three-word structures from three vectors (scalar index)

Contiguous store three-word structures, each from the same element number in three vector registers to the memory address generated by a 64-bit scalar base and a 64-bit scalar index register scaled by the element size (LSL option) and added to the base address. After each structure access the index value is incremented by three. The index register is not updated by the instruction.

Each predicate element applies to the same element number in each of the three vector registers, or equivalently to the three consecutive words in memory which make up each structure. Inactive structures are not written to memory.

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	0	0	1	0	1	0	1	0	Rm			0	1	1	Pg			Rn			Zt								
msz<1>msz<0>																															

**ST3W** { <Zt1>.S, <Zt2>.S, <Zt3>.S }, <Pg>, [<Xn|SP>, <Xm>, LSL #2]

```
if !HaveSVE() && !HaveSME() then UNDEFINED;
if Rm == '11111' then UNDEFINED;
integer t = UInt(Zt);
integer n = UInt(Rn);
integer m = UInt(Rm);
integer g = UInt(Pg);
constant integer esize = 32;
constant integer nreg = 3;
```

### Assembler Symbols

<Zt1>	Is the name of the first scalable vector register to be transferred, encoded in the "Zt" field.
<Zt2>	Is the name of the second scalable vector register to be transferred, encoded as "Zt" plus 1 modulo 32.
<Zt3>	Is the name of the third scalable vector register to be transferred, encoded as "Zt" plus 2 modulo 32.
<Pg>	Is the name of the governing scalable predicate register P0-P7, encoded in the "Pg" field.
<Xn SP>	Is the 64-bit name of the general-purpose base register or stack pointer, encoded in the "Rn" field.
<Xm>	Is the 64-bit name of the general-purpose offset register, encoded in the "Rm" field.

### Operation

```

CheckSVEEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer elements = VL DIV esize;
bits(64) base;
bits(PL) mask = P[g, PL];
bits(64) offset;
constant integer mbytes = esize DIV 8;
array [0..2] of bits(VL) values;
boolean contiguous = TRUE;
boolean nontemporal = FALSE;
boolean tagchecked = TRUE;
AccessDescriptor accdesc = CreateAccDescSVE(MemOp\_STORE, nontemporal, c

if !AnyActiveElement(mask, esize) then
    if n == 31 && ConstrainUnpredictableBool(Unpredictable\_CHECKSPNONEA
        CheckSPAlignment();
else
    if n == 31 then CheckSPAlignment();
    base = if n == 31 then SP[] else X[n, 64];
    offset = X[m, 64];

for r = 0 to nreg-1
    values[r] = Z[(t+r) MOD 32, VL];

for e = 0 to elements-1
    for r = 0 to nreg-1
        if ActivePredicateElement(mask, e, esize) then
            integer eoff = UInt(offset) + (e * nreg) + r;
            bits(64) addr = base + eoff * mbytes;
            Mem[addr, mbytes, accdesc] = Elem[values[r], e, esize];

```

## Operational information

If FEAT\_SVE2 is implemented or FEAT\_SME is implemented, then if PSTATE.DIT is 1, the timing of this instruction is insensitive to the value of the data being loaded or stored when its governing predicate register contains the same value for each execution.

[Base  
Instructions](#)

[SIMD&FP  
Instructions](#)

[SVE  
Instructions](#)

[SME  
Instructions](#)

[Index by  
Encoding](#)

[Sh  
Pseud](#)

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode  
no\_diffs\_2023\_09\_RC2, sve v2023-06\_rel ; Build timestamp: 2023-09-18T17:56

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This  
document is Non-Confidential.