AArch64
Instructions

Index by Encoding

External Registers

SPMEVTYPER<n>_EL0, System Performance Monitors Event Type Register, n = 0 - 63

The SPMEVTYPER<n> EL0 characteristics are:

Purpose

With <u>SPMEVFILTR<n>_EL0</u> and <u>SPMEVFILT2R<n>_EL0</u>, configures when event counter <u>SPMEVCNTR<n>_EL0</u> in System PMU <s> increments.

The contents of this register are implementation defined. An Event Type Select Register typically contains:

- A field defining the event that the counter is responsive to, in the least-significant bits.
- Controls for per-counter filtering, such as by mode or state.
- Additional controls, such as for a per-counter state machine.

Configuration

This register is present only when FEAT_SPMU is implemented. Otherwise, direct accesses to SPMEVTYPER<n>_EL0 are undefined.

Attributes

SPMEVTYPER<n>_EL0 is a 64-bit register.

Field descriptions

63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32

IMPLEMENTATION DEFINED
IMPLEMENTATION DEFINED

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

IMPLEMENTATION DEFINED, bits [63:0]

implementation defined.

Accessing SPMEVTYPER<n> EL0

To access SPMEVTYPER<n>_EL0 for System PMU <s>, set SPMSELR EL0. SYSPMUSEL to s and SPMSELR EL0. BANK to n[5:4].

SPMEVTYPER<n>_EL0 reads-as-zero and ignores writes if event counter <n> is not implemented by System PMU <s>.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, SPMEVTYPER<m>_EL0 ; Where m = 0-15

op0	op1	CRn	CRm	op2
0b10	0b011	0b1110	0b001:m[3]	m[2:0]

```
integer m = UInt(CRm<0>:op2<2:0>);
if PSTATE.EL == ELO then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR\_EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) &&
HDFGRTR2_EL2.nSPMEVTYPERn_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] =
SPMEVTYPER_ELO[UInt(SPMSELR_ELO.SYSPMUSEL),
(UInt(SPMSELR ELO.BANK) * 16) + m];
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR\_EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) &&
HDFGRTR2_EL2.nSPMEVTYPERn_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] =
```

```
SPMEVTYPER ELO[UInt(SPMSELR ELO.SYSPMUSEL),
(UInt(SPMSELR ELO.BANK) * 16) + m];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] =
SPMEVTYPER_EL0[UInt(SPMSELR_EL0.SYSPMUSEL),
(UInt(SPMSELR_ELO.BANK) * 16) + m];
elsif PSTATE.EL == EL3 then
    X[t, 64] =
SPMEVTYPER ELO[UInt(SPMSELR ELO.SYSPMUSEL),
(UInt(SPMSELR ELO.BANK) * 16) + m];
```

MSR SPMEVTYPER<m>_EL0, <Xt>; Where m = 0-15

op0	op1	CRn	CRm	op2
0b10	0b011	0b1110	0b001:m[3]	m[2:0]

```
integer m = UInt(CRm<0>:op2<2:0>);
if PSTATE.EL == ELO then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.<E2H, TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR_EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.<E2H,TGE> != '11'
&& IsFeatureImplemented(FEAT_FGT2) &&
HDFGWTR2_EL2.nSPMEVTYPERn_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMEVTYPER_EL0[UInt(SPMSELR_EL0.SYSPMUSEL),
(UInt(SPMSELR_ELO.BANK) * 16) + m] = X[t, 64];
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
```

```
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) && HaveEL(EL3) &&
SCR EL3.FGTEn2 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
IsFeatureImplemented(FEAT_FGT2) &&
HDFGWTR2_EL2.nSPMEVTYPERn_EL0 == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && MDCR EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED:
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMEVTYPER_EL0[UInt(SPMSELR_EL0.SYSPMUSEL),
(UInt(SPMSELR_ELO.BANK) * 16) + m] = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION DEFINED "EL3 trap priority
when SDD == '1'" && MDCR EL3.EnPM2 == '0' then
        UNDEFINED;
    elsif HaveEL(EL3) && MDCR_EL3.EnPM2 == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        SPMEVTYPER ELO[UInt(SPMSELR ELO.SYSPMUSEL),
(UInt(SPMSELR_ELO.BANK) * 16) + m] = X[t, 64];
elsif PSTATE.EL == EL3 then
    SPMEVTYPER_EL0[UInt(SPMSELR_EL0.SYSPMUSEL),
(UInt(SPMSELR ELO.BANK) * 16) + m] = X[t, 64];
```

AArch32 AArch64 AArch32 AArch64 Index by External Registers Registers Instructions Instructions Encoding Registers

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright A© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.