<u>SME</u>	Index by
Instructions	Encoding

SIMD&FP Base **Instructions Instructions**

SVE Instructions

Pseu

FMOPA (widening)

Half-precision floating-point sum of outer products and accumulate

The half-precision floating-point sum of outer products and accumulate instruction works with a 32-bit element ZA tile.

This instruction widens the SVL_S×2 sub-matrix of half-precision floatingpoint values held in the first source vector to single-precision floating-point values and multiplies it by the widened 2A—SVL_s sub-matrix of half-

precision floating-point values in the second source vector to singleprecision floating-point values.

Each source vector is independently predicated by a corresponding governing predicate. When a 16-bit source element is Inactive it is treated as having the value +0.0, but if both pairs of source vector elements that correspond to a 32-bit destination element contain Inactive elements, then the destination element remains unmodified.

The resulting SVL_S×SVL_S single-precision floating-point sum of outer products is then destructively added to the single-precision floating-point destination tile. This is equivalent to performing a 2-way dot product and accumulate to each of the destination tile elements.

Each 32-bit container of the first source vector holds 2 consecutive column elements of each row of a SVL_S×2 sub-matrix. Similarly, each 32-bit container of the second source vector holds 2 consecutive row elements of each column of a 2Å—SVL_S sub-matrix.

This instruction follows SME ZA-targeting floating-point behaviors.

SME (FEAT_SME)

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0
1 0 0 0 0 0 0 1 1 0 1
                             Zm
                                      Pm
                                              Pn
                                                       Zn
                                                              0 0 0 ZAda
```

FMOPA $\langle ZAda \rangle$. S, $\langle Pn \rangle / M$, $\langle Pm \rangle / M$, $\langle Zn \rangle$. H, $\langle Zm \rangle$. H

```
if ! Have SME () then UNDEFINED;
integer a = UInt(Pn);
integer b = \overline{UInt}(Pm);
integer n = UInt(Zn);
integer m = UInt(Zm);
integer da = UInt(ZAda);
boolean sub_op = FALSE;
```

Assembler Symbols

<ZAda> Is the name of the ZA tile ZAO-ZA3, encoded in the "ZAda" field.

<Pn> Is the name of the first governing scalable predicate register P0-P7, encoded in the "Pn" field.
<Pm> Is the name of the second governing scalable predicate register P0-P7, encoded in the "Pm" field.
<Zn> Is the name of the first source scalable vector register, encoded in the "Zn" field.
<Zm> Is the name of the second source scalable vector register, encoded in the "Zm" field.

Operation

```
CheckStreamingSVEAndZAEnabled();
constant integer VL = CurrentVL;
constant integer PL = VL DIV 8;
constant integer dim = VL DIV 32;
bits(PL) mask1 = P[a, PL];
bits(PL) mask2 = P[b, PL];
bits(VL) operand1 = \underline{Z}[n, VL];
bits(VL) operand2 = \underline{Z}[m, VL];
bits(dim*dim*32) operand3 = \underline{ZAtile}[da, 32, dim*dim*32];
bits(dim*dim*32) result;
for row = 0 to dim-1
    for col = 0 to dim-1
         // determine row/col predicates
         boolean prow_0 = (ActivePredicateElement (mask1, 2*row + 0, 16))
         boolean prow_1 = (<u>ActivePredicateElement</u>(mask1, 2*row + 1, 16))
         boolean pcol_0 = (ActivePredicateElement(mask2, 2*col + 0, 16))
         boolean pcol 1 = (ActivePredicateElement (mask2, 2*col + 1, 16))
         bits (32) sum = \underline{\text{Elem}}[operand3, row*dim+col, 32];
         if (prow_0 && pcol_0) | (prow_1 && pcol_1) then
             bits(16) erow_0 = (if prow_0 then Elem[operand1, 2*row + 0,
             bits(16) erow_1 = (if prow_1 then Elem[operand1, 2*row + 1,
             bits(16) ecol_0 = (if pcol_0 then Elem[operand2, 2*col + 0,
             bits(16) ecol_1 = (if pcol_1 then Elem[operand2, 2*col + 1,
             if sub_op then
                  if prow_0 then erow_0 = \underline{FPNeq} (erow_0);
                  if prow_1 then erow_1 = FPNeq(erow_1);
             sum = FPDotAdd ZA(sum, erow_0, erow_1, ecol_0, ecol_1, FPCF
         Elem[result, row*dim+col, 32] = sum;
\underline{ZAtile}[da, 32, dim*dim*32] = result;
```

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel; Build timestamp: 2023-09-18T17:56

Sh

Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.