

GICR_STATUSR, Error Reporting Status Register

The GICR_STATUSR characteristics are:

Purpose

Provides software with a mechanism to detect:

- Accesses to reserved locations.
- Writes to read-only locations.
- Reads of write-only locations.

Configuration

A copy of this register is provided for each Redistributor.

If the GIC implementation supports two Security states this register is Banked to provide Secure and Non-secure copies.

Attributes

GICR_STATUSR is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																WROD		RWOD		WRD		RRD									

Bits [31:4]

Reserved, res0.

WROD, bit [3]

Write to an RO location.

WROD	Meaning
0b0	Normal operation.
0b1	A write to an RO location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

RWOD, bit [2]

Read of a WO location.

RWOD	Meaning
0b0	Normal operation.
0b1	A read of a WO location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

WRD, bit [1]

Write to a reserved location.

WRD	Meaning
0b0	Normal operation.
0b1	A write to a reserved location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

RRD, bit [0]

Read of a reserved location.

RRD	Meaning
0b0	Normal operation.
0b1	A read of a reserved location has been detected.

When a violation is detected, software must write 1 to this register to reset it.

Accessing GICR_STATUSR

This is an optional register. If the register is not implemented, the location is RAZ/WI.

GICR_STATUSR can be accessed through the memory-mapped interfaces:

Component	Frame	Offset	Instance
GIC Redistributor	RD_base	0x0010	GICR_STATUSR (S)

This interface is accessible as follows:

- When an access is Secure, accesses to this register are **RW**.

- When FEAT_RME is implemented and an access is Root, accesses to this register are **RW**.

Component	Frame	Offset	Instance
GIC Redistributor	RD_base	0x0010	GICR_STATUSR (NS)

This interface is accessible as follows:

- When an access is Non-secure, accesses to this register are **RW**.
- When FEAT_RME is implemented and an access is Realm, accesses to this register are **RW**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.