

BFADD

BFloat16 floating-point add multi-vector to ZA array vector accumulators

Destructively add all elements of the two or four source vectors to the corresponding BFloat16 elements of the ZA single-vector groups. The vector numbers forming the single-vector group within each half of or each quarter of the ZA array are selected by the sum of the vector select register and immediate offset, modulo half or quarter the number of ZA array vectors.

The vector group symbol, VGx2 or VGx4, indicates that the ZA operand consists of two or four ZA single-vector groups respectively. The vector group symbol is preferred for disassembly, but optional in assembler source code.

This instruction follows SME2.1 ZA-targeting non-widening BFloat16 numerical behaviors.

This instruction is unpredicated.

ID_AA64SMFR0_EL1.B16B16 indicates whether this instruction is implemented.

It has encodings from 2 classes: [Two ZA single-vectors](#) and [Four ZA single-vectors](#)

Two ZA single-vectors (FEAT_SVE_B16B16)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	1	1	1	0	0	1	0	0	0	Rv	1	1	1		Zm			0	0	0		off3		
SZ										S																					

BFADD ZA.H[<Wv>, <offs>{, VGx2}], { <Zm1>.H-<Zm2>.H }

```
if !HaveSME2() || !IsFeatureImplemented(FEAT_SVE_B16B16) then UNDEFINED
integer v = UInt('010':Rv);
integer m = UInt(Zm:'0');
integer offset = UInt(off3);
constant integer nreg = 2;
```

Four ZA single-vectors (FEAT_SVE_B16B16)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	1	1	1	0	0	1	0	1	0	Rv	1	1	1	Zm	0	0	0	0	off3					
SZ										S																					

```
BFADD ZA.H[<Wv>, <offs>{, VGx4}], { <Zm1>.H-<Zm4>.H }
```

```
if !HaveSME2() || !IsFeatureImplemented(FEAT_SVE_B16B16) then UNDEFINED
integer v = UInt('010':Rv);
integer m = UInt(Zm:'00');
integer offset = UInt(off3);
constant integer nreg = 4;
```

Assembler Symbols

<Wv>	Is the 32-bit name of the vector select register W8-W11, encoded in the "Rv" field.
<offs>	Is the vector select offset, in the range 0 to 7, encoded in the "off3" field.
<Zm1>	For the two ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zm" times 2. For the four ZA single-vectors variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zm" times 4.
<Zm4>	Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zm" times 4 plus 3.
<Zm2>	Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zm" times 2 plus 1.

Operation

```
CheckStreamingSVEAndZAAEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV 16;
integer vectors = VL DIV 8;
integer vstride = vectors DIV nreg;
bits(32) vbase = X[v, 32];
integer vec = (UInt(vbase) + offset) MOD vstride;
bits(VL) result;

for r = 0 to nreg-1
    bits(VL) operand1 = ZAvector[vec, VL];
    bits(VL) operand2 = Z[m+r, VL];
    for e = 0 to elements-1
        bits(16) element1 = Elem[operand1, e, 16];
        bits(16) element2 = Elem[operand2, e, 16];
        Elem[result, e, 16] = BFAdd_ZA(element1, element2, FPCR[]);
    ZAvector[vec, VL] = result;
    vec = vec + vstride;
```

[Base
Instructions](#)

[SIMD&FP
Instructions](#)

[SVE
Instructions](#)

[SME
Instructions](#)

[Index by
Encoding](#)

[Sh
Pseudocode](#)

