

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	0	0	1	0	Zm		0	Rv	1	1	1	Zn			0	1	off3							
SZ																		S													

FMLS ZA.H[<Wv>, <offs>{, VGx2}], { <Zn1>.H-<Zn2>.H }, <Zm>.H

```
if !HaveSME2() || !IsFeatureImplemented(FEAT_SME_F16F16) then UNDEFINED;
integer v = UInt('010':Rv);
constant integer esize = 16;
integer n = UInt(Zn);
integer m = UInt('0':Zm);
integer offset = UInt(off3);
boolean sub_op = TRUE;
constant integer nreg = 2;
```

Four ZA single-vectors (FEAT_SME2)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	0	sz	1	1		Zm		0	Rv	1	1	0		Zn		0	1		off3					
																											S				

FMLS ZA.<T>[<Wv>, <offs>{, VGx4}], { <Zn1>.<T>-<Zn4>.<T> }, <Zm>.<T>

```
if !HaveSME2() then UNDEFINED;
if sz == '1' && !HaveSMEF64F64() then UNDEFINED;
integer v = UInt('010':Rv);
constant integer esize = 32 << UInt(sz);
integer n = UInt(Zn);
integer m = UInt('0':Zm);
integer offset = UInt(off3);
boolean sub_op = TRUE;
constant integer nreg = 4;
```

Four ZA single-vectors of half precision elements (FEAT_SME_F16F16)

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	0	0	0	1	0	0	1	1	Zm		0	Rv	1	1	1	Zn			0	1	off3							
SZ										S																					

FMLS ZA.H[<Wv>, <offs>{, VGx4}], { <Zn1>.H-<Zn4>.H }, <Zm>.H

```
if !HaveSME2() || !IsFeatureImplemented(FEAT_SME_F16F16) then UNDEFINED;
integer v = UInt('010':Rv);
constant integer esize = 16;
integer n = UInt(Zn);
integer m = UInt('0':Zm);
integer offset = UInt(off3);
boolean sub_op = TRUE;
constant integer nreg = 4;
```

Assembler Symbols

<T>
Is the size specifier, encoded in "sz":

sz	<T>
0	S
1	D

- <Wv> Is the 32-bit name of the vector select register W8-W11, encoded in the "Rv" field.
- <offs> Is the vector select offset, in the range 0 to 7, encoded in the "off3" field.
- <Zn1> Is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zn".
- <Zn4> Is the name of the fourth scalable vector register of a multi-vector sequence, encoded as "Zn" plus 3 modulo 32.
- <Zn2> Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zn" plus 1 modulo 32.
- <Zm> Is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.

Operation

```
CheckStreamingSVEAndZAAEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
integer vectors = VL DIV 8;
integer vstride = vectors DIV nreg;
bits(32) vbase = X[v, 32];
integer vec = (UInt(vbase) + offset) MOD vstride;
bits(VL) result;

for r = 0 to nreg-1
  bits(VL) operand1 = Z[(n+r) MOD 32, VL];
  bits(VL) operand2 = Z[m, VL];
  bits(VL) operand3 = ZAvector[vec, VL];
  for e = 0 to elements-1
    bits(esize) element1 = Elem[operand1, e, esize];
    bits(esize) element2 = Elem[operand2, e, esize];
    bits(esize) element3 = Elem[operand3, e, esize];
    if sub_op then element1 = FPNeg(element1);
    Elem[result, e, esize] = FPMulAdd_ZA(element3, element1, element2);
  ZAvector[vec, VL] = result;
  vec = vec + vstride;
```

