
TLBIP RVALE1IS, TLBIP RVALE1ISNXS, TLB Range Invalidate by VA, Last level, EL1, Inner Shareable

The TLBIP RVALE1IS, TLBIP RVALE1ISNXS characteristics are:

Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 128-bit stage 1 translation table entry, from any level of the translation table walk up to the level indicated in the TTL hint.

Or the entry is a 64-bit stage 1 translation table entry, if TTL is 0b00.

- The entry would be used to translate any of the VAs in the specified address range, and one of the following applies:
 - The entry is a global entry from the final level of lookup.
 - The entry is a non-global entry from the final level of lookup that matches the specified ASID.
- The entry is within the address range determined by the formula $[\text{BaseADDR} \leq \text{VA} < \text{BaseADDR} + ((\text{NUM} + 1) * 2^{(5 * \text{SCALE} + 1)} * \text{Translation_Granule_Size})]$.
- When EL2 is implemented and enabled in the current Security state:
 - If [HCR_EL2](#).{E2H, TGE} is not {1, 1}, the entry would be used with the current VMID and would be required to translate any of the VAs in the specified address range using the EL1&0 translation regime for the Security state.
 - If [HCR_EL2](#).{E2H, TGE} is {1, 1}, the entry would be required to translate any of the VAs in the specified address range using the EL2&0 translation regime for the Security state.

- When EL2 is not implemented or is disabled in the current Security state, the entry would be required to translate any of the VAs in the specified address range using the EL1&0 translation regime for the Security state.

The Security state is indicated by the value of [SCR_EL3.NS](#) if FEAT_RME is not implemented, or [SCR_EL3.{NSE, NS}](#) if FEAT_RME is implemented.

The invalidation applies to all PEs in the same Inner Shareable shareability domain as the PE that executes this System instruction.

Note

When a TLB maintenance instruction is generated to the Secure EL1&0 translation regime and is defined to pass a VMID argument, or would be defined to pass a VMID argument if [SCR_EL3.EEL2==1](#), then:

- A PE with [SCR_EL3.EEL2==1](#) is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR_EL3.EEL2==0](#).
- A PE with [SCR_EL3.EEL2==0](#) is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR_EL3.EEL2==1](#).
- A PE is architecturally required to invalidate all relevant entries in the Secure EL1&0 translation of a System MMU in the same required shareability domain with a VMID of 0.

For 128-bit translation table entry, the range of addresses invalidated is unpredictable when Block or Page size corresponding to TTL and TG, for the translation system is not aligned.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

This instruction is present only when FEAT_D128 is implemented. Otherwise, direct accesses to TLBIP RVALE1IS, TLBIP RVALE1ISNXS are undefined.

Attributes

TLBIP RVALE1IS, TLBIP RVALE1ISNXS is a 128-bit System instruction.

Field descriptions

127	126	125	124	123	122	121	120	119	118	117	116	115	114	113	112	111	110	109	108	107	106	105	104	103	102	101	100	99	98	97	96				
RES0																		BaseADDR[55:12]																	
95	94	93	92	91	90	89	88	87	86	85	84	83	82	81	80	79	78	77	76	75	74	73	72	71	70	69	68	67	66	65	64				
BaseADDR[55:12]																																			
63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32				
ASID																TG		SCALE		NUM				TTL		RES0									
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0				
RES0																																			

Bits [127:108]

Reserved, res0.

BaseADDR[55:12], bits [107:64]

The starting address for the range of the maintenance instructions. This field is BaseADDR[55:12] for all translation granules.

ASID, bits [63:48]

ASID value to match. Any TLB entries that match the ASID value and VA value will be affected by this System instruction.

Global TLB entries that match the VA value will be affected by this System instruction, regardless of the value of the ASID field.

If the implementation supports 16 bits of ASID, then the upper 8 bits of the ASID must be written to 0 by software when the context being invalidated only uses 8 bits.

TG, bits [47:46]

Translation granule size.

TG	Meaning
0b00	Reserved.
0b01	4K translation granule.
0b10	16K translation granule.
0b11	64K translation granule.

The instruction takes a translation granule size for the translations that are being invalidated. If the translations used a different translation granule size than the one being specified, then the architecture does not require that the instruction invalidates any entries.

SCALE, bits [45:44]

The exponent element of the calculation that is used to produce the upper range.

NUM, bits [43:39]

The base element of the calculation that is used to produce the upper range.

TTL, bits [38:37]

TTL Level hint. The TTL hint is only guaranteed to invalidate:

- Non-leaf-level entries in the range up to but not including the level described by the TTL hint.
- Leaf-level entries in the range that match the level described by the TTL hint.

TTL	Meaning
0b00	The entries in the range can be using any level for the translation table entries.
0b01	The TTL hint indicates level 1. If FEAT_LPA2 is not implemented, when using a 16KB translation granule, this value is reserved and hardware should treat this field as 0b00.
0b10	The TTL hint indicates level 2.
0b11	The TTL hint indicates level 3.

Bits [36:0]

Reserved, res0.

Executing TLBIP RVALE1IS, TLBIP RVALE1ISNXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBIP RVALE1IS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1000	0b0010	0b101

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() && HCR_EL2.TTLBIS == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') && HFGITR_EL2.TLBIRVALE1IS ==
        '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    else
        if IsFeatureImplemented(FEAT_XS) &&
        IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
        && HCRX_EL2.FnXS == '1' then

        AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
        Regime_EL10, VMID[], Shareability_ISH,
        TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        else

        AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
        Regime_EL10, VMID[], Shareability_ISH,
        TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
    elsif PSTATE.EL == EL2 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
            Regime_EL20, VMID_NONE, Shareability_ISH,
            TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
        else
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
    elsif PSTATE.EL == EL3 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
            Regime_EL20, VMID_NONE, Shareability_ISH,
            TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
        else
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);

```

TLBIP RVALE1ISNXS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1001	0b0010	0b101

```

if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() && HCR_EL2.TTLBIS == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') &&
        IsFeatureImplemented(FEAT_HCX) && (!
        IsHCRXEL2Enabled() || HCRX_EL2.FGTnXS == '0') &&
        HFGITR_EL2.TLBIRVALE1IS == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    else
        AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
        Regime_EL10, VMID[], Shareability_ISH,
        TLBIlevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
    elsif PSTATE.EL == EL2 then
        if HCR_EL2.<E2H,TGE> == '11' then
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
            Regime_EL20, VMID_NONE, Shareability_ISH,
            TLBIlevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        else
            AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBIlevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        elsif PSTATE.EL == EL3 then
            if HCR_EL2.<E2H,TGE> == '11' then
                AArch64.TLBIP_RVA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_ISH,
                TLBIlevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            else
                AArch64.TLBIP_RVA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_ISH,
                TLBIlevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

