

TFSRE0_EL1, Tag Fault Status Register (EL0).

The TFSRE0_EL1 characteristics are:

Purpose

Holds accumulated Tag Check Faults occurring in EL0 that are not taken precisely.

Configuration

This register is present only when FEAT_MTE2 is implemented. Otherwise, direct accesses to TFSRE0_EL1 are undefined.

Attributes

TFSRE0_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
RES0																															TFIFO
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:2]

Reserved, res0.

TF1, bit [1]

Tag Check Fault. Asynchronously set to 1 when a Tag Check Fault using a virtual address with bit[55] == 0b1 occurs.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

TF0, bit [0]

Tag Check Fault. Asynchronously set to 1 when a Tag Check Fault using a virtual address with bit[55] == 0b0 occurs.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing TFSRE0_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TFSRE0_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0110	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.ATA == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TFSRE0_EL1;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TFSRE0_EL1;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = TFSRE0_EL1;
```

MSR TFSRE0_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0110	0b001

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elsif EL2Enabled() && HCR_EL2.ATA == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TFSRE0_EL1 = X[t, 64];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                TFSRE0_EL1 = X[t, 64];
    elsif PSTATE.EL == EL3 then
        TFSRE0_EL1 = X[t, 64];
```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.