<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	Encoding

Pseu

SMAX (multiple and single vector)

Multi-vector signed maximum by vector

Determine the signed maximum of elements of the second source vector and the corresponding elements of the two or four first source vectors and destructively place the results in the corresponding elements of the two or four first source vectors.

This instruction is unpredicated.

It has encodings from 2 classes: Two registers and Four registers

Two registers (FEAT SME2)

```
SMAX { <Zdn1>.<T>-<Zdn2>.<T> }, { <Zdn1>.<T>-<Zdn2>.<T> }, <Zm>.<T>
if !HaveSME2() then UNDEFINED;
constant integer esize = 8 << UInt(size);
integer dn = UInt(Zdn:'0');
integer m = UInt('0':Zm);
constant integer nreg = 2;
boolean unsigned = FALSE;</pre>
```

Four registers (FEAT_SME2)

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 1 1 1 0 0 0 0 0 1 size 1 0 Zm 1 0 1 0 1 0 0 0 0 0 0 Zdn 0 0
```

```
if !HaveSME2() then UNDEFINED;
constant integer esize = 8 << UInt(size);
integer dn = UInt(Zdn:'00');
integer m = UInt('0':Zm);
constant integer nreg = 4;
boolean unsigned = FALSE;</pre>
```

Assembler Symbols

<Zdn1> For the two registers variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zdn" times 2.

For the four registers variant: is the name of the first scalable vector register of a multi-vector sequence, encoded as "Zdn" times 4.

<T>

Is the size specifier, encoded in "size":

size	<t></t>		
00	В		
01	Н		
10	S		
11	D		

<Zdn4>

Is the name of the fourth scalable vector register of a multivector sequence, encoded as "Zdn" times 4 plus 3.

<Zdn2>

Is the name of the second scalable vector register of a multi-vector sequence, encoded as "Zdn" times 2 plus 1.

<Zm>

Is the name of the second source scalable vector register Z0-Z15, encoded in the "Zm" field.

Operation

```
CheckStreamingSVEEnabled();
constant integer VL = CurrentVL;
constant integer elements = VL DIV esize;
array [0..3] of bits(VL) results;

for r = 0 to nreg-1
    bits(VL) operand1 = Z[dn+r, VL];
    bits(VL) operand2 = Z[m, VL];
    for e = 0 to elements-1
        integer element1 = Int(Elem[operand1, e, esize], unsigned);
    integer element2 = Int(Elem[operand2, e, esize], unsigned);
    integer res = Max(element1, element2);
        Elem[results[r], e, esize] = res<esize-1:0>;

for r = 0 to nreg-1
        Z[dn+r, VL] = results[r];
```

Operational information

If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
 - The values of the data supplied in any of its registers.
 - The values of the NZCV flags.

BaseSIMD&FPSVESMEIndex byInstructionsInstructionsInstructionsInstructions

Internal version only: isa v33.64, AdvSIMD v29.12, pseudocode no_diffs_2023_09_RC2, sve v2023-06_rel ; Build timestamp: 2023-09-18T17:56

Sh Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.