

SMIDR_EL1, Streaming Mode Identification Register

The SMIDR_EL1 characteristics are:

Purpose

Provides additional identification mechanisms for scheduling purposes, for a PE that supports Streaming SVE mode.

Configuration

This register is present only when FEAT_SME is implemented. Otherwise, direct accesses to SMIDR_EL1 are undefined.

Attributes

SMIDR_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
Implementer								Revision								SMPRES0				Affinity											
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:32]

Reserved, res0.

Implementer, bits [31:24]

The Implementer code. This field must hold an implementer code that has been assigned by Arm. Assigned codes include the following:

Implementer	Meaning
0x00	Reserved for software use.
0x41	Arm Limited.
0x42	Broadcom Corporation.
0x43	Cavium Inc.
0x44	Digital Equipment Corporation.

0x46	Fujitsu Ltd.
0x49	Infineon Technologies AG.
0x4D	Motorola or Freescale Semiconductor Inc.
0x4E	NVIDIA Corporation.
0x50	Applied Micro Circuits Corporation.
0x51	Qualcomm Inc.
0x56	Marvell International Ltd.
0x69	Intel Corporation.
0xC0	Ampere Computing.

Arm can assign codes that are not published in this manual. All values not assigned by Arm are reserved and must not be used.

It is not required that this value is the same as the value of [MIDR_EL1](#). Implementer.

This field has an implementation defined value.

Access to this field is **RO**.

Revision, bits [23:16]

Revision number for the Streaming Mode Compute Unit (SMCU).

This field has an implementation defined value.

Access to this field is **RO**.

SMPS, bit [15]

Indicates support for Streaming SVE mode execution priority.

SMPS	Meaning
0b0	Priority control not supported.
0b1	Priority control supported.

Bits [14:12]

Reserved, res0.

Affinity, bits [11:0]

The SMCU affinity of the accessing PE.

- A value of zero indicates that the PE's implementation of Streaming SVE mode is not shared with other PEs.

- Otherwise, the value identifies which SMCU is associated with this PE. The Affinity value associated with each SMCU is unique within the system as a whole.

Accessing SMIDR_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, SMIDR_EL1

op0	op1	CRn	CRm	op2
0b11	0b001	0b0000	0b0000	0b110

```

if PSTATE.EL == EL0 then
    if IsFeatureImplemented(FEAT_IDST) then
        if EL2Enabled() && HCR_EL2.TGE == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            AArch64.SystemAccessTrap(EL1, 0x18);
        else
            UNDEFINED;
    elsif PSTATE.EL == EL1 then
        if EL2Enabled() && HCR_EL2.TID1 == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            X[t, 64] = SMIDR_EL1;
    elsif PSTATE.EL == EL2 then
        X[t, 64] = SMIDR_EL1;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = SMIDR_EL1;

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.