

TFSR_EL1, Tag Fault Status Register (EL1)

The TFSR_EL1 characteristics are:

Purpose

Holds accumulated Tag Check Faults occurring in EL1 that are not taken precisely.

Configuration

This register is present only when FEAT_MTE2 is implemented. Otherwise, direct accesses to TFSR_EL1 are undefined.

Attributes

TFSR_EL1 is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																															TFIFO

Bits [63:2]

Reserved, res0.

TF1, bit [1]

Tag Check Fault. Asynchronously set to 1 when a Tag Check Fault using a virtual address with bit[55] == 0b1 occurs.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

TF0, bit [0]

Tag Check Fault. Asynchronously set to 1 when a Tag Check Fault using a virtual address with bit[55] == 0b0 occurs.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing TFSR_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TFSR_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0110	0b000

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elseif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==
'011' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() && HCR_EL2.ATA == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && SCR_EL3.ATA == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elseif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==
'111' then
        X[t, 64] = NVMem[0x190];
    else
        X[t, 64] = TFSR_EL1;
elseif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elseif HaveEL(EL3) && SCR_EL3.ATA == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elseif HCR_EL2.E2H == '1' then
        X[t, 64] = TFSR_EL2;
    else
        X[t, 64] = TFSR_EL1;
elseif PSTATE.EL == EL3 then
    X[t, 64] = TFSR_EL1;

```

MSR TFSR_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b0101	0b0110	0b000

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elseif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==

```

```

'011' then
    AArch64.SystemAccessTrap(EL2, 0x18);
elseif EL2Enabled() && HCR_EL2.ATA == '0' then
    AArch64.SystemAccessTrap(EL2, 0x18);
elseif HaveEL(EL3) && SCR_EL3.ATA == '0' then
    if Halted() && EDSCR.SDD == '1' then
        UNDEFINED;
    else
        AArch64.SystemAccessTrap(EL3, 0x18);
    elseif EL2Enabled() && HCR_EL2.<NV2,NV1,NV> ==
'111' then
        NVMem[0x190] = X[t, 64];
    else
        TFSR_EL1 = X[t, 64];
elseif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
        UNDEFINED;
    elseif HaveEL(EL3) && SCR_EL3.ATA == '0' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elseif HCR_EL2.E2H == '1' then
        TFSR_EL2 = X[t, 64];
    else
        TFSR_EL1 = X[t, 64];
elseif PSTATE.EL == EL3 then
    TFSR_EL1 = X[t, 64];

```

MRS <Xt>, TFSR_EL12

op0	op1	CRn	CRm	op2
0b11	0b101	0b0101	0b0110	0b000

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV1,NV> == '101'
then
        X[t, 64] = NVMem[0x190];
    elseif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elseif PSTATE.EL == EL2 then
    if HCR_EL2.E2H == '1' then
        if Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elseif HaveEL(EL3) && SCR_EL3.ATA == '0' then

```

```

        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TFSR_EL1;
        else
            UNDEFINED;
    elsif PSTATE.EL == EL3 then
        if EL2Enabled() && !ELUsingAArch32(EL2) &&
HCR_EL2.E2H == '1' then
            X[t, 64] = TFSR_EL1;
        else
            UNDEFINED;

```

MSR TFSR_EL12, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b101	0b0101	0b0110	0b000

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV1,NV> == '101'
then
        NVMem[0x190] = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    if HCR_EL2.E2H == '1' then
        if Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TFSR_EL1 = X[t, 64];
    else
        UNDEFINED;
elsif PSTATE.EL == EL3 then
    if EL2Enabled() && !ELUsingAArch32(EL2) &&
HCR_EL2.E2H == '1' then
        TFSR_EL1 = X[t, 64];
    else
        UNDEFINED;

```

MRS <Xt>, TFSR_EL2

op0	op1	CRn	CRm	op2
0b11	0b100	0b0101	0b0110	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
        if Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elsif EL2Enabled() && HCR_EL2.ATA == '0' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TFSR_EL1;
        elsif EL2Enabled() && HCR_EL2.NV == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        else
            UNDEFINED;
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
            UNDEFINED;
        elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TFSR_EL2;
    elsif PSTATE.EL == EL3 then
        X[t, 64] = TFSR_EL2;
```

MSR TFSR_EL2, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b100	0b0101	0b0110	0b000

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
```

```

        if EL2Enabled() && HCR_EL2.<NV2,NV> == '11' then
            if Halted() && HaveEL(EL3) && EDSCR.SDD ==
'1' && boolean IMPLEMENTATION_DEFINED "EL3 trap
priority when SDD == '1'" && SCR_EL3.ATA == '0' then
                UNDEFINED;
            elsif EL2Enabled() && HCR_EL2.ATA == '0' then
                AArch64.SystemAccessTrap(EL2, 0x18);
            elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
                if Halted() && EDSCR.SDD == '1' then
                    UNDEFINED;
                else
                    AArch64.SystemAccessTrap(EL3, 0x18);
                else
                    TFSR_EL1 = X[t, 64];
            elsif EL2Enabled() && HCR_EL2.NV == '1' then
                AArch64.SystemAccessTrap(EL2, 0x18);
            else
                UNDEFINED;
        elsif PSTATE.EL == EL2 then
            if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.ATA == '0' then
                UNDEFINED;
            elsif HaveEL(EL3) && SCR_EL3.ATA == '0' then
                if Halted() && EDSCR.SDD == '1' then
                    UNDEFINED;
                else
                    AArch64.SystemAccessTrap(EL3, 0x18);
                else
                    TFSR_EL2 = X[t, 64];
            elsif PSTATE.EL == EL3 then
                TFSR_EL2 = X[t, 64];

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.