

TLBIP RVAALE1IS, TLBIP RVAALE1ISNXS, TLB Range Invalidate by VA, All ASID, Last Level, EL1, Inner Shareable

The TLBIP RVAALE1IS, TLBIP RVAALE1ISNXS characteristics are:

Purpose

Invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 128-bit stage 1 translation table entry, from the leaf level of the translation table walk, indicated by the TTL hint.
Or the entry is a 64-bit stage 1 translation table entry, from the leaf level of the translation table walk, if TTL is 0b00.
- The entry is within the address range determined by the formula $[\text{BaseADDR} \leq \text{VA} < \text{BaseADDR} + ((\text{NUM} + 1) * 2^{(5 * \text{SCALE} + 1)} * \text{Translation_Granule_Size})]$.
- When EL2 is implemented and enabled in the current Security state:
 - If [HCR_EL2](#).{E2H, TGE} is not {1, 1}, the entry would be used with the current VMID and would be required to translate any of the VAs in the specified address range using the EL1&0 translation regime for the Security state.
 - If [HCR_EL2](#).{E2H, TGE} is {1, 1}, the entry would be required to translate any of the VAs in the specified address range using the EL2&0 translation regime for the Security state.
- When EL2 is not implemented or is disabled in the current Security state, the entry would be required to translate any of the VAs in the specified address range using the EL1&0 translation regime for the Security state.

The Security state is indicated by the value of [SCR_EL3](#).NS if FEAT_RME is not implemented, or [SCR_EL3](#).{NSE, NS} if FEAT_RME is implemented.

The invalidation applies to all PEs in the same Inner Shareable shareability domain as the PE that executes this System instruction.

Note

When a TLB maintenance instruction is generated to the Secure EL1&0 translation regime and is defined to pass a VMID argument, or would be defined to pass a VMID argument if [SCR_EL3.EEL2==1](#), then:

- A PE with [SCR_EL3.EEL2==1](#) is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR_EL3.EEL2==0](#).
- A PE with [SCR_EL3.EEL2==0](#) is not architecturally required to invalidate any entries in the Secure EL1&0 translation of a PE in the same required shareability domain with [SCR_EL3.EEL2==1](#).
- A PE is architecturally required to invalidate all relevant entries in the Secure EL1&0 translation of a System MMU in the same required shareability domain with a VMID of 0.

Note

For the EL1&0 and EL2&0 translation regimes, the invalidation applies to both global entries and non-global entries with any ASID.

For 128-bit translation table entry, the range of addresses invalidated is unpredictable when Block or Page size corresponding to TTL and TG, for the translation system is not aligned.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.


Configuration

This instruction is present only when FEAT_D128 is implemented. Otherwise, direct accesses to TLBIP RVAALE1IS, TLBIP RVAALE1ISNXS are undefined.

Attributes

TLBIP RVAALE1IS, TLBIP RVAALE1ISNXS is a 128-bit System instruction.

Field descriptions



Bits [127:108]

Reserved, res0.

BaseADDR[55:12], bits [107:64]

The starting address for the range of the maintenance instructions. This field is BaseADDR[55:12] for all translation granules.

Bits [63:48]

Reserved, res0.

TG, bits [47:46]

Translation granule size.

TG	Meaning
0b00	Reserved.
0b01	4K translation granule.
0b10	16K translation granule.
0b11	64K translation granule.

The instruction takes a translation granule size for the translations that are being invalidated. If the translations used a different translation granule size than the one being specified, then the architecture does not require that the instruction invalidates any entries.

SCALE, bits [45:44]

The exponent element of the calculation that is used to produce the upper range.

NUM, bits [43:39]

The base element of the calculation that is used to produce the upper range.

TTL, bits [38:37]

TTL Level hint. The TTL hint is only guaranteed to invalidate:

- Non-leaf-level entries in the range up to but not including the level described by the TTL hint.
- Leaf-level entries in the range that match the level described by the TTL hint.

TTL	Meaning
0b00	The entries in the range can be using any level for the translation table entries.
0b01	The TTL hint indicates level 1. If FEAT_LPA2 is not implemented, when using a 16KB translation granule, this value is reserved and hardware should treat this field as 0b00.
0b10	The TTL hint indicates level 2.
0b11	The TTL hint indicates level 3.

Bits [36:0]

Reserved, res0.

Executing TLBIP RVAALE1IS, TLBIP RVAALE1ISNXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBIP RVAALE1IS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1000	0b0010	0b111

```

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.TTLB == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() && HCR_EL2.TTLBIS == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    elsif EL2Enabled() &&
        IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
        SCR_EL3.FGTEn == '1') && HFGITR_EL2.TLBIRVAALE1IS ==
        '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    else
        if IsFeatureImplemented(FEAT_XS) &&
        IsFeatureImplemented(FEAT_HCX) && IsHCRXEL2Enabled()
        && HCRX_EL2.FnXS == '1' then

        AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
        Regime_EL10, VMID[], Shareability_ISH,
        TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        else

        AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
        Regime_EL10, VMID[], Shareability_ISH,
        TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
        elsif PSTATE.EL == EL2 then
            if HCR_EL2.<E2H,TGE> == '11' then
                AArch64.TLBIP_RVAA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_ISH,
                TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
            else
                AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_ISH,
                TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
            elsif PSTATE.EL == EL3 then
                if HCR_EL2.<E2H,TGE> == '11' then
                    AArch64.TLBIP_RVAA(SecurityStateAtEL(EL2),
                    Regime_EL20, VMID_NONE, Shareability_ISH,
                    TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
                else
                    AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
                    Regime_EL10, VMID[], Shareability_ISH,
                    TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);

```

TLBIP RVAALE1ISNXS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b000	0b1001	0b0010	0b111

```

if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then

```

```

        UNDEFINED;
    elsif PSTATE.EL == EL1 then
        if EL2Enabled() && HCR_EL2.TTLB == '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        elsif EL2Enabled() && HCR_EL2.TTLBIS == '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        elsif EL2Enabled() &&
            IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
            SCR_EL3.FGTEn == '1') &&
            IsFeatureImplemented(FEAT_HCX) && (!
            IsHCRXEL2Enabled() || HCRX_EL2.FGTnXS == '0') &&
            HFGITR_EL2.TLBIRVAALE1IS == '1' then
            AArch64.SystemAccessTrap(EL2, 0x14);
        else
            AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
            Regime_EL10, VMID[], Shareability_ISH,
            TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
        elsif PSTATE.EL == EL2 then
            if HCR_EL2.<E2H,TGE> == '11' then
                AArch64.TLBIP_RVAA(SecurityStateAtEL(EL2),
                Regime_EL20, VMID_NONE, Shareability_ISH,
                TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            else
                AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
                Regime_EL10, VMID[], Shareability_ISH,
                TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            elsif PSTATE.EL == EL3 then
                if HCR_EL2.<E2H,TGE> == '11' then
                    AArch64.TLBIP_RVAA(SecurityStateAtEL(EL2),
                    Regime_EL20, VMID_NONE, Shareability_ISH,
                    TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
                else
                    AArch64.TLBIP_RVAA(SecurityStateAtEL(EL1),
                    Regime_EL10, VMID[], Shareability_ISH,
                    TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
            end
        end
    end
end

```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbdd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.