# CMEQ (zero)

Compare bitwise Equal to zero (vector). This instruction reads each vector element in the source SIMD&FP register and if the value is equal to zero sets every bit of the corresponding vector element in the destination SIMD&FP register to one, otherwise sets every bit of the corresponding vector element in the destination SIMD&FP register to zero.

Depending on the settings in the *CPACR\_EL1*, *CPTR\_EL2*, and *CPTR\_EL3* registers, and the current Security state and Exception level, an attempt to execute the instruction might be trapped.

It has encodings from 2 classes: Scalar and Vector

#### Scalar

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

0 1 0 1 1 1 1 0 size 1 0 0 0 0 0 1 1 0 0 1 1 0 Rn Rd

U op
```

## CMEQ $\langle V \rangle \langle d \rangle$ , $\langle V \rangle \langle n \rangle$ , #0

```
integer d = UInt(Rd);
integer n = UInt(Rn);

if size != '11' then UNDEFINED;
constant integer esize = 8 << UInt(size);
constant integer datasize = esize;
integer elements = 1;

CompareOp comparison;
case op:U of
   when '00' comparison = CompareOp GT;
   when '01' comparison = CompareOp GE;
   when '10' comparison = CompareOp EQ;
   when '11' comparison = CompareOp LE;</pre>
```

### Vector

```
31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0 0 0 0 0 1 1 1 1 0 size 1 0 0 0 0 0 1 1 0 0 1 1 0 0 Rn Rd U
```

```
CMEQ \langle Vd \rangle . \langle T \rangle, \langle Vn \rangle . \langle T \rangle, #0
```

```
integer d = UInt(Rd);
integer n = UInt(Rn);

if size:Q == '110' then UNDEFINED;
constant integer esize = 8 << UInt(size);
constant integer datasize = 64 << UInt(Q);
integer elements = datasize DIV esize;</pre>
```

```
CompareOp comparison;
case op:U of
  when '00' comparison = CompareOp GT;
  when '01' comparison = CompareOp GE;
  when '10' comparison = CompareOp EQ;
  when '11' comparison = CompareOp LE;
```

## **Assembler Symbols**

<V>

Is a width specifier, encoded in "size":

size	<v></v>
0x	RESERVED
10	RESERVED
11	D

<d>

Is the number of the SIMD&FP destination register, encoded in the "Rd" field.

<n>

Is the number of the SIMD&FP source register, encoded in the "Rn" field.

<Vd>

Is the name of the SIMD&FP destination register, encoded in the "Rd" field.

<T>

Is an arrangement specifier, encoded in "size:Q":

size	Q	<t></t>
00	0	8B
00	1	16B
01	0	4H
01	1	8H
10	0	2S
10	1	4S
11	0	RESERVED
11	1	2D

<Vn>

Is the name of the SIMD&FP source register, encoded in the "Rn" field.

## **Operation**

```
CheckFPAdvSIMDEnabled64();
bits(datasize) operand = V[n, datasize];
bits(datasize) result;
integer element;
boolean test_passed;

for e = 0 to elements-1
    element = SInt(Elem[operand, e, esize]);
    case comparison of
        when CompareOp GT test_passed = element > 0;
        when CompareOp GE test_passed = element >= 0;
```

```
when CompareOp_EQ test_passed = element == 0;
when CompareOp_LE test_passed = element <= 0;
when CompareOp_LT test_passed = element < 0;
Elem[result, e, esize] = if test_passed then Ones(esize) else Zeros
V[d, datasize] = result;</pre>
```

## **Operational information**

## If PSTATE.DIT is 1:

- The execution time of this instruction is independent of:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.
- The response of this instruction to asynchronous exceptions does not vary based on:
  - The values of the data supplied in any of its registers.
  - The values of the NZCV flags.

<u>Base</u>	SIMD&FP	<u>SVE</u>	<u>SME</u>	Index by
<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<u>Instructions</u>	<b>Encoding</b>

 $Internal\ version\ only: is a\ v33.64,\ AdvSIMD\ v29.12,\ pseudocode\ no\_diffs\_2023\_09\_RC2,\ sve\ v2023-06\_rel\ ;\ Build\ timestamp:\ 2023-09-18T17:56$ 

Sh Pseu

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.