

TRBCIDR3, Component Identification Register 3

The TRBCIDR3 characteristics are:

Purpose

Provides discovery information about the component.

For additional information, see the CoreSight Architecture Specification.

Configuration

This register is present only when FEAT_TRBE_EXT is implemented. Otherwise, direct accesses to TRBCIDR3 are res0.

TRBCIDR3 is in the Core power domain.

Attributes

TRBCIDR3 is a 32-bit register.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																PRMBL 3															

Bits [31:8]

Reserved, res0.

PRMBL_3, bits [7:0]

Component identification preamble, segment 3.

Reads as 0xB1.

Access to this field is **RO**.

Accessing TRBCIDR3

TRBCIDR3 can be accessed through the external debug interface:

Component	Offset	Instance
-----------	--------	----------

TRBE	0xFFC	TRBCIDR3
------	-------	----------

This interface is accessible as follows:

- When DoubleLockStatus() or !IsCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.