

## TRCVMIDCVR<n>, Virtual Context Identifier Comparator Value Register <n>, n = 0 - 7

The TRCVMIDCVR<n> characteristics are:

### Purpose

Contains the Virtual Context Identifier Comparator value.

### Configuration

AArch64 System register TRCVMIDCVR<n> bits [63:0] are architecturally mapped to External register [TRCVMIDCVR<n>\[63:0\]](#).

This register is present only when FEAT\_ETE is implemented, FEAT\_TRC\_SR is implemented and  $\text{UInt}(\text{TRCIDR4.NUMVMIDC}) > n$ . Otherwise, direct accesses to TRCVMIDCVR<n> are undefined.

### Attributes

TRCVMIDCVR<n> is a 64-bit register.

### Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
VALUE																															
VALUE																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

#### VALUE, bits [63:0]

Virtual context identifier value. The width of this field is indicated by [TRCIDR2.VMIDSIZE](#). Unimplemented bits are res0. After a PE Reset, the trace unit assumes that the Virtual context identifier is zero until the PE updates the Virtual context identifier .

The reset behavior of this field is:

- On a Trace unit reset, this field resets to an architecturally unknown value.

## Accessing TRCVMIDCVR<n>

Must be programmed if any of the following are true:

- [TRCRSCTLR<a>](#).GROUP == 0b0111 and [TRCRSCTLR<a>](#).VMID[n] == 1.
- [TRCACATR<a>](#).CONTEXTTYPE == 0b10 or 0b11 and [TRCACATR<a>](#).CONTEXT == n.

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCVMIDCVR<m> ; Where m = 0-7

op0	op1	CRn	CRm	op2
0b10	0b001	0b0011	m[2:0]:0b0	0b001

```
integer m = UInt(CRm<3:1>);

if m >=
    NUM_TRACE_VIRTUAL_CONTEXT_IDENTIFIER_COMPARATORS then
    UNDEFINED;
elseif PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elseif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elseif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    else
        X[t, 64] = TRCVMIDCVR[m];
elseif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elseif CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
```

```

        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCVMIDCVR[m];
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCVMIDCVR[m];

```

**MSR TRCVMIDCVR<m>, <Xt> ; Where m = 0-7**

op0	op1	CRn	CRm	op2
0b10	0b001	0b0011	m[2:0]:0b0	0b001

```

integer m = UInt(CRm<3:1>);

if m >=
    NUM_TRACE_VIRTUAL_CONTEXT_IDENTIFIER_COMPARATORS then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCVMIDCVR[m] = X[t, 64];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then

```

```
        UNDEFINED;
    else
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCVMIDCVR[m] = X[t, 64];
elseif PSTATE.EL == EL3 then
    if CPTR_EL3.TTA == '1' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        TRCVMIDCVR[m] = X[t, 64];
```

---

[AArch32  
Registers](#)

[AArch64  
Registers](#)

[AArch32  
Instructions](#)

[AArch64  
Instructions](#)

[Index by  
Encoding](#)

[External  
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.