TLBIP RIPAS2LE1IS, TLBIP RIPAS2LE1ISNXS, TLB Range Invalidate by Intermediate Physical Address, Stage 2, Last level, EL1, Inner Shareable

The TLBIP RIPAS2LE1IS, TLBIP RIPAS2LE1ISNXS characteristics are:

Purpose

If EL2 is implemented and enabled in the current Security state, invalidates cached copies of translation table entries from TLBs that meet all the following requirements:

- The entry is a 128-bit stage 2 only translation table entry, from the leaf level of the translation table walk, indicated by the TTL hint.

  Or if FEAT_D128 is implemented, and the entry is a 64-bit stage 2 only translation table entry, from the leaf level of the translation table walk, if TTL is `0b00`.

- If FEAT_RME is implemented, one of the following applies:
  - SCR_EL3.{NSE, NS} is {0, 0} and the entry would be required to translate any IPA in the specified address range using the Secure EL1&0 translation regime.
  - SCR_EL3.{NSE, NS} is {0, 1} and the entry would be required to translate any IPA in the specified address range using the Non-secure EL1&0 translation regime.
  - SCR_EL3.{NSE, NS} is {1, 1} and the entry would be required to translate any IPA in the specified address range using the Realm EL1&0 translation regime.

- If FEAT_RME is not implemented, one of the following applies:
  - SCR_EL3.NS is 0 and the entry would be required to translate any IPA in the specified address range using the Secure EL1&0 translation regime.
  - SCR_EL3.NS is 1 and the entry would be required to translate any IPA in the specified address range using the Non-secure EL1&0 translation regime.

- The entry would be used with the current VMID.

- The entry is within the address range determined by the formula [BaseADDR <= VA < BaseADDR + ((NUM +1)*2$^{(5*SCALE +1)}$ * Translation_Granule_Size)].

The invalidation is not required to apply to caching structures that combine stage 1 and stage 2 translation table entries.

The invalidation applies to all PEs in the same Inner Shareable shareability domain as the PE that executes this System instruction.

For 128-bit translation table entry, the range of addresses invalidated is unpredictable when Block or Page size corresponding to TTL and TG, for the translation system is not aligned.

For more information about the architectural requirements for this System instruction, see 'Invalidation of TLB entries from stage 2 translations'.

If FEAT_XS is implemented, the nXS variant of this System instruction is defined.

Both variants perform the same invalidation, but the TLBI System instruction without the nXS qualifier waits for all memory accesses using in-scope old translation information to complete before it is considered complete.

The TLBI System instruction with the nXS qualifier is considered complete when the subset of these memory accesses with XS attribute set to 0 are complete.

Configuration

This instruction is present only when FEAT_D128 is implemented. Otherwise, direct accesses to TLBIP RIPAS2LE1IS, TLBIP RIPAS2LE1ISNXS are undefined.

Attributes

TLBIP RIPAS2LE1IS, TLBIP RIPAS2LE1ISNXS is a 128-bit System instruction.

Field descriptions



Bits [127:108]

Reserved, res0.

BaseADDR[55:12], bits [107:64]

The starting address for the range of the maintenance instructions. This field is BaseADDR[55:12] for all translation granules.

NS, bit [63]
When FEAT_RME is implemented:

When the instruction is executed and SCR_EL3.{NSE, NS} == {0, 0}, NS selects the IPA space.

NS	Meaning
0b0	IPA is in the Secure IPA space.
0b1	IPA is in the Non-secure IPA space.

When the instruction is executed and SCR_EL3.{NSE, NS} == {1, 1}, this field is res0, and the instruction applies only to the Realm IPA space.

When the instruction is executed and SCR_EL3.{NSE, NS} == {0, 1}, this field is res0, and the instruction applies only to the Non-secure IPA space.

When FEAT_SEL2 is implemented and FEAT_RME is not implemented:

Not Secure. Specifies the IPA space.

NS	Meaning
0b0	IPA is in the Secure IPA space.
0b1	IPA is in the Non-secure IPA space.

When the instruction is executed in Non-secure state, this field is res0, and the instruction applies only to the Non-secure IPA space.

When FEAT_SEL2 is not implemented, or if EL2 is disabled in the current Security state, this field is res0.

Otherwise:

Reserved, res0.

Bits [62:48]

Reserved, res0.

TG, bits [47:46]

Translation granule size.

TG	Meaning
0b00	Reserved.
0b01	4K translation granule.
0b10	16K translation granule.
0b11	64K translation granule.

The instruction takes a translation granule size for the translations that are being invalidated. If the translations used a different translation granule size than the one being specified, then the architecture does not require that the instruction invalidates any entries.

SCALE, bits [45:44]

The exponent element of the calculation that is used to produce the upper range.

NUM, bits [43:39]

The base element of the calculation that is used to produce the upper range.

TTL, bits [38:37]

TTL Level hint. The TTL hint is only guaranteed to invalidate:

- Non-leaf-level entries in the range up to but not including the level described by the TTL hint.
- Leaf-level entries in the range that match the level described by the TTL hint.

TTL	Meaning
0b00	The entries in the range can be using any level for the translation table entries.
0b01	The TTL hint indicates level 1. If FEAT_LPA2 is not implemented, when using a 16KB translation granule, this value is reserved and hardware should treat this field as 0b00.
0b10	The TTL hint indicates level 2.
0b11	The TTL hint indicates level 3.

Bits [36:0]

Reserved, res0.

Executing TLBIP RIPAS2LE1IS, TLBIP RIPAS2LE1ISNXS

Accesses to this instruction use the following encodings in the System instruction encoding space:

TLBIP RIPAS2LE1IS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b100	0b1000	0b0000	0b110

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    else
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    AArch64.TLBIP_RIPAS2(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
elsif PSTATE.EL == EL3 then
    if !EL2Enabled() then
        return;
    else
        AArch64.TLBIP_RIPAS2(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_AllAttr, X[t2, 64]:X[t, 64]);
```

TLBIP RIPAS2LE1ISNXS{, <Xt>, <Xt2>}

op0	op1	CRn	CRm	op2
0b01	0b100	0b1001	0b0000	0b110

```
if !IsFeatureImplemented(FEAT_XS) then
    UNDEFINED;
elsif PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if EL2Enabled() && HCR_EL2.NV == '1' then
        AArch64.SystemAccessTrap(EL2, 0x14);
    else
```

```
        UNDEFINED;
elsif PSTATE.EL == EL2 then
    AArch64.TLBIP_RIPAS2(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
elsif PSTATE.EL == EL3 then
    if !EL2Enabled() then
        return;
    else
        AArch64.TLBIP_RIPAS2(SecurityStateAtEL(EL1),
Regime_EL10, VMID[], Shareability_ISH,
TLBILevel_Last, TLBI_ExcludeXS, X[t2, 64]:X[t, 64]);
```

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94