ICV_CTLR_EL1, Interrupt Controller Virtual Control Register

The ICV_CTLR_EL1 characteristics are:

Purpose

Controls aspects of the behavior of the GIC virtual CPU interface and provides information about the features implemented.

Configuration

AArch64 System register ICV_CTLR_EL1 bits [31:0] are architecturally mapped to AArch32 System register ICV_CTLR[31:0].

This register is present only when FEAT_GICv3 is implemented and EL2 is implemented. Otherwise, direct accesses to ICV_CTLR_EL1 are undefined.

Attributes

ICV_CTLR_EL1 is a 64-bit register.

Field descriptions



Bits [63:20]

Reserved, res0.

ExtRange, bit [19]

Extended INTID range (read-only).

ExtRange	Meaning

0b0	CPU interface does not support INTIDs in the range 1024..8191. • Behavior is unpredictable if the IRI delivers an interrupt in the range 1024 to 8191 to the CPU interface. **Note** Arm strongly recommends that the IRI is not configured to deliver interrupts in this range to a PE that does not support them.
0b1	CPU interface supports INTIDs in the range 1024..8191 • All INTIDs in the range 1024..8191 are treated as requiring deactivation.

ICV_CTLR_EL1.ExtRange is an alias of ICC_CTLR_EL1.ExtRange.

RSS, bit [18]

Range Selector Support. Possible values are:

RSS	Meaning
0b0	Targeted SGIs with affinity level 0 values of 0 - 15 are supported.
0b1	Targeted SGIs with affinity level 0 values of 0 - 255 are supported.

This bit is read-only.

Bits [17:16]

Reserved, res0.

A3V, bit [15]

Affinity 3 Valid. Read-only and writes are ignored. Possible values are:

A3V	Meaning
0b0	The virtual CPU interface logic only supports zero values of Affinity 3 in SGI generation System registers.
0b1	The virtual CPU interface logic supports nonzero values of Affinity 3 in SGI generation System registers.

SEIS, bit [14]

SEI Support. Read-only and writes are ignored. Indicates whether the virtual CPU interface supports local generation of SEIs:

SEIS	Meaning
0b0	The virtual CPU interface logic does not support local generation of SEIs.
0b1	The virtual CPU interface logic supports local generation of SEIs.

IDbits, bits [13:11]

Identifier bits. Read-only and writes are ignored. The number of virtual interrupt identifier bits supported:

IDbits	Meaning
0b000	16 bits.
0b001	24 bits.

All other values are reserved.

PRIbits, bits [10:8]

Priority bits. Read-only and writes are ignored. The number of priority bits implemented, minus one.

An implementation must implement at least 32 levels of physical priority (5 priority bits).

Note

This field always returns the number of priority bits implemented.

The division between group priority and subpriority is defined in the binary point registers ICV_BPR0_EL1 and ICV_BPR1_EL1.

Bits [7:2]

Reserved, res0.

EOImode, bit [1]

Virtual EOI mode. Controls whether a write to an End of Interrupt register also deactivates the virtual interrupt:

EOImode	Meaning
0b0	ICV_EOIR0_EL1 and ICV_EOIR1_EL1 provide both priority drop and interrupt deactivation functionality. Accesses to ICV_DIR_EL1 are unpredictable.
0b1	ICV_EOIR0_EL1 and ICV_EOIR1_EL1 provide priority drop functionality only. ICV_DIR_EL1 provides interrupt deactivation functionality.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

CBPR, bit [0]

Common Binary Point Register. Controls whether the same register is used for interrupt preemption of both virtual Group 0 and virtual Group 1 interrupts:

CBPR	Meaning
0b0	ICV_BPR1_EL1 determines the preemption group for virtual Group 1 interrupts.

0b1	Non-secure reads of ICV_BPR1_EL1 return ICV_BPR0_EL1 plus one, saturated to 0b111. Non-secure writes to ICV_BPR1_EL1 are ignored. Secure reads of ICV_BPR1_EL1 return ICV_BPR0_EL1. Secure writes of ICV_BPR1_EL1 modify ICV_BPR0_EL1.

The reset behavior of this field is:

- On a Warm reset, this field resets to an architecturally unknown value.

Accessing ICV_CTLR_EL1

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, ICC_CTLR_EL1

op0	op1	CRn	CRm	op2
0b11	0b000	0b1100	0b1100	0b100

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.<IRQ,FIQ> == '11' then
        UNDEFINED;
    elsif ICC_SRE_EL1.SRE == '0' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && ICH_HCR_EL2.TC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.FMO == '1' then
        X[t, 64] = ICV_CTLR_EL1;
    elsif EL2Enabled() && HCR_EL2.IMO == '1' then
        X[t, 64] = ICV_CTLR_EL1;
    elsif HaveEL(EL3) && SCR_EL3.<IRQ,FIQ> == '11'
then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) then
        if SCR_EL3.NS == '0' then
            X[t, 64] = ICC_CTLR_EL1_S;
        else
```

```
            X[t, 64] = ICC_CTLR_EL1_NS;
    else
        X[t, 64] = ICC_CTLR_EL1;
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.<IRQ,FIQ> == '11' then
        UNDEFINED;
    elsif ICC_SRE_EL2.SRE == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.<IRQ,FIQ> == '11'
then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) then
        if SCR_EL3.NS == '0' then
            X[t, 64] = ICC_CTLR_EL1_S;
        else
            X[t, 64] = ICC_CTLR_EL1_NS;
    else
        X[t, 64] = ICC_CTLR_EL1;
elsif PSTATE.EL == EL3 then
    if ICC_SRE_EL3.SRE == '0' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        if SCR_EL3.NS == '0' then
            X[t, 64] = ICC_CTLR_EL1_S;
        else
            X[t, 64] = ICC_CTLR_EL1_NS;
```

MSR ICC_CTLR_EL1, <Xt>

op0	op1	CRn	CRm	op2
0b11	0b000	0b1100	0b1100	0b100

```
if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.<IRQ,FIQ> == '11' then
        UNDEFINED;
    elsif ICC_SRE_EL1.SRE == '0' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && ICH_HCR_EL2.TC == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() && HCR_EL2.FMO == '1' then
        ICV_CTLR_EL1 = X[t, 64];
    elsif EL2Enabled() && HCR_EL2.IMO == '1' then
        ICV_CTLR_EL1 = X[t, 64];
    elsif HaveEL(EL3) && SCR_EL3.<IRQ,FIQ> == '11'
```

```
then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) then
        if SCR_EL3.NS == '0' then
            ICC_CTLR_EL1_S = X[t, 64];
        else
            ICC_CTLR_EL1_NS = X[t, 64];
    else
        ICC_CTLR_EL1 = X[t, 64];
elsif PSTATE.EL == EL2 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
&& boolean IMPLEMENTATION_DEFINED "EL3 trap priority
when SDD == '1'" && SCR_EL3.<IRQ,FIQ> == '11' then
        UNDEFINED;
    elsif ICC_SRE_EL2.SRE == '0' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && SCR_EL3.<IRQ,FIQ> == '11'
then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
    elsif HaveEL(EL3) then
        if SCR_EL3.NS == '0' then
            ICC_CTLR_EL1_S = X[t, 64];
        else
            ICC_CTLR_EL1_NS = X[t, 64];
    else
        ICC_CTLR_EL1 = X[t, 64];
elsif PSTATE.EL == EL3 then
    if ICC_SRE_EL3.SRE == '0' then
        AArch64.SystemAccessTrap(EL3, 0x18);
    else
        if SCR_EL3.NS == '0' then
            ICC_CTLR_EL1_S = X[t, 64];
        else
            ICC_CTLR_EL1_NS = X[t, 64];
```


28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94