

PMCIDR3, Performance Monitors Component Identification Register 3

The PMCIDR3 characteristics are:

Purpose

Provides information to identify a Performance Monitor component.

For more information, see 'About the Component Identification scheme'.

Configuration

This register is present only when FEAT_PMUv3_EXT is implemented and an implementation implements PMCIDR3. Otherwise, direct accesses to PMCIDR3 are res0.

If FEAT_DoPD is implemented, this register is in the Core power domain. If FEAT_DoPD is not implemented, this register is in the Debug power domain.

This register is required for CoreSight compliance.

Attributes

PMCIDR3 is a 32-bit register.

This register is part of the [PMU](#) block.

Field descriptions

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
RES0																PRMBL 3															

Bits [31:8]

Reserved, res0.

PRMBL_3, bits [7:0]

Preamble.

Reads as 0xB1.

Access to this field is **RO**.

Accessing PMCIDR3

Accesses to this register use the following encodings:

Accessible at offset 0xFFC from PMU

- When FEAT_DoPD is implemented and !IsCorePowered(), accesses to this register generate an error response.
- Otherwise, accesses to this register are **RO**.

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:01; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright Â© 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.