

TRCIMSPEC<n>, IMP DEF Register <n>, n = 1 - 7

The TRCIMSPEC<n> characteristics are:

Purpose

These registers might return information that is specific to an implementation, or enable features specific to an implementation to be programmed. The product Technical Reference Manual describes these registers.

Configuration

AArch64 System register TRCIMSPEC<n> bits [31:0] are architecturally mapped to External register [TRCIMSPEC<n>\[31:0\]](#).

This register is present only when the trace unit implements this OPTIONAL register, FEAT_ETE is implemented and FEAT_TRC_SR is implemented. Otherwise, direct accesses to TRCIMSPEC<n> are undefined.

Attributes

TRCIMSPEC<n> is a 64-bit register.

Field descriptions

63	62	61	60	59	58	57	56	55	54	53	52	51	50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32
RES0																															
IMPLEMENTATION DEFINED																															
31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Bits [63:32]

Reserved, res0.

IMPLEMENTATION DEFINED, bits [31:0]

implementation defined.

This field reads as an implementation defined value and writes to this field have implementation defined behavior.

Accessing TRCIMSPEC<n>

Accesses to this register use the following encodings in the System register encoding space:

MRS <Xt>, TRCIMSPEC<m> ; Where m = 1-7

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b0:m[2:0]	0b111

```
integer m = UInt(CRm<2:0>);

if PSTATE.EL == EL0 then
    UNDEFINED;
elsif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elsif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elsif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGRTR_EL2.TRCIMSPECn ==
    '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            X[t, 64] = TRCIMSPEC[m];
    elsif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elsif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elsif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                X[t, 64] = TRCIMSPEC[m];
    elsif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
```

```
X[t, 64] = TRCIMSPEC[m];
```

MSR TRCIMSPEC<m>, <Xt> ; Where m = 1-7

op0	op1	CRn	CRm	op2
0b10	0b001	0b0000	0b0:m[2:0]	0b111

```
integer m = UInt(CRm<2:0>);

if PSTATE.EL == EL0 then
    UNDEFINED;
elseif PSTATE.EL == EL1 then
    if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
    && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
    when SDD == '1'" && CPTR_EL3.TTA == '1' then
        UNDEFINED;
    elseif CPACR_EL1.TTA == '1' then
        AArch64.SystemAccessTrap(EL1, 0x18);
    elseif EL2Enabled() && CPTR_EL2.TTA == '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif EL2Enabled() &&
    IsFeatureImplemented(FEAT_FGT) && (!HaveEL(EL3) ||
    SCR_EL3.FGTEn == '1') && HDFGWTR_EL2.TRCIMSPEcn ==
    '1' then
        AArch64.SystemAccessTrap(EL2, 0x18);
    elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
        if Halted() && EDSCR.SDD == '1' then
            UNDEFINED;
        else
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCIMSPEC[m] = X[t, 64];
    elseif PSTATE.EL == EL2 then
        if Halted() && HaveEL(EL3) && EDSCR.SDD == '1'
        && boolean IMPLEMENTATION_DEFINED "EL3 trap priority
        when SDD == '1'" && CPTR_EL3.TTA == '1' then
            UNDEFINED;
        elseif CPTR_EL2.TTA == '1' then
            AArch64.SystemAccessTrap(EL2, 0x18);
        elseif HaveEL(EL3) && CPTR_EL3.TTA == '1' then
            if Halted() && EDSCR.SDD == '1' then
                UNDEFINED;
            else
                AArch64.SystemAccessTrap(EL3, 0x18);
            else
                TRCIMSPEC[m] = X[t, 64];
    elseif PSTATE.EL == EL3 then
        if CPTR_EL3.TTA == '1' then
            AArch64.SystemAccessTrap(EL3, 0x18);
        else
            TRCIMSPEC[m] = X[t, 64];
```

[AArch32
Registers](#)

[AArch64
Registers](#)

[AArch32
Instructions](#)

[AArch64
Instructions](#)

[Index by
Encoding](#)

[External
Registers](#)

28/03/2023 16:02; 72747e43966d6b97dcbd230a1b3f0421d1ea3d94

Copyright © 2010-2023 Arm Limited or its affiliates. All rights reserved. This document is Non-Confidential.